**BLUE MAGIC** 

### **SECTION I - IDENTIFICATION**



Car Chem

398 S. King Oak St. Trenton, IL 62293 (618) 224-7445

INFOTRAC :..... (800) 535-5053

Product Number CC BM

Product Name
BLUE MAGIC
Chemical Family
Mixture
CAS Number
Multiple
Date Prepared
5/28/2015
Revision Number
7/3/2020
Recommended Use
BLUE MAGIC
Mixture
7/28/2015
Policy Prepared
DRESSING

## **SECTION II - HAZARDOUS IDENTIFICATION**

# **GHS CLASSIFICATION:**

## Classification

Flammable Liquids

Aspiration Hazard

Category 1

Skin Corrosion/Irritation

Category 2

Specific target organ toxicity, single exposure, R

Category 3

Specific target organ toxicity, single exposure, N

Category 3

Reproductive Toxicity

Category 2

Specific target organ toxicity, repeated exposure

Category 2

# **DANGER!**

#### **GHS LABEL:**







# **Hazard Statements**

H225	Highly flammable gas and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H335	May cause respiratory irritation
H336	May cause dizziness or drowsiness
H361	Suspected of damaging fertility or the unborn child
H373	Causes damage to organs through prolonged or repeated exposure

# **BLUE MAGIC**

# **Precautionary Statements**

Precautionary	<u>Statements</u>
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground or bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures to prevent static discharge.
P260	Do not breathe dust, fumes, gas, mist, vapors or spray.
P261	Avoid breathing dust, fumes, gas, mist, vapors or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, clothing, eye and face protection. Goggles, gloves, face mask/shield and/or a separate approved breathing apparatus if required.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P302+352	IF ON SKIN: Wash with plenty of running water and soap until all is removed.
P303+361+353	IF ON SKIN (or hair): Immediately remove all contaminated clothing. Rinse skin or hair with water or shower.
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P308+313	IF exposed or concerned: seek medical attention.
P312	Call a POISON CENTER or physician if you feel unwell.
P314	Get medical attention if you feel unwell.
P321	Specific treatment: refer to section four, first aid or see a physician.
P331	Do NOT induce vomiting.
P332+313	If skin irritation occurs: get medical attention.
P362+364	Immediatley remove all contaminated clothing and wash them before reuse.
P370+378	In case of fire: Use alcohol resistant foam or CO2 to extinguish.
P403+233	Store in a well ventilated area with container tightly closed.
P403+235	Store in a cool, well ventilated area.
P405	Store locked up.

P501 Dispose of contents or container according to all state, local and federal laws.

### **SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS**

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS#	Component%	OSHA PEL	ACGIH TLV
Hexane	110-54-3	50-60	50 ppm	50 ppm
Hydrotreated Light Naphtha	64742-49-0	25-35	500 ppm	500 ppm

#### **SECTION IV - FIRST AID MEASURES**

Contact with eyes: Flush eyes with running water for ten minutes. Remove contact lenses and continue to

flush. If irritation persists, seek medical attention.

**Skin contact:** If on skin rinse well with clean water and soap. If on clothing remove the contaminated

clothing immediately. Wash clothing before reuse. Seek medical attention/advice if

needed.

**Inhalation:** Remove victim to fresh air. If breathing difficulty seek medical attention. Administer

oxygen or artificial respiration if breathing is affected or stopped. Loosen any tight

clothing.

**Ingestion:** If swallowed. Do not induce vomiting unless instructed to do so by a poison control

center. Rinse mouth. Seek immediate medical attention by calling 911 and seeing a

physician.

# **SECTION V - FIREFIGHTING MEASURES**

**Suitable Extinguishing Media:** Water fog, foam, CO2, dry chemical.

**Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area.

**Unusual Fire Fighting Hazards:** Do not use high volume water jet.

Hazardous gases may form during fire.

#### **SECTION VI - ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Keep all sources of ignition and hot metal surfaces away from spill or

release.

Evacuate all unprotected personnel from the area.

Product in liquid and vapor form is extremely flammable.

**Environmental Precautions:** Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities. Reportable Quantity is 9090 pounds or 1620

gallons.

### **BLUE MAGIC**

**Methods for Cleaning Up:** Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect

spill on absorbent material and put into approved container.

### **SECTION VII - HANDLING AND STORAGE**

### Handling and Storage:

- NFPA Class I storage.
- Vent container carefully before opening.
- Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
- "Empty" containers may retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

#### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

#### **EXPOSURE LIMITS:**

Component Name	CAS#	OSHA PEL	ACGIH TLV
Hexane	110-54-3	50 ppm	50 ppm
Hydrotreated Light Naphtha	64742-49-0	500 ppm	500 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV. Showers, eye wash stations.

**Monitoring:** Follow accepted work practices for handling a flammable material.

Do not eat, drink or smoke in areas where this chemical is used or stored.

Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

**Eye Protection:** Goggles or approved OSHA device with side shields.

**Skin Protection:** Impervious solvent resistent gloves.

Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is

unknown or above the OSHA PEL or ACGIH TLV.

### **SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

# **BLUE MAGIC**

Appearance	Clear, Blue Liquid
Odor	Vanilla
pH@25°C	ND
Melting/Freezing Point	ND
Flashpoint	ND
Specific Gravity	
Soluability	Negligible
Auto-Ignition Temperature	ND
<b>Decomposition Temperature</b>	ND
VOC Content	ND
Odor Threshold	ND
Boiling Range	ND
<b>Evaporation Point</b>	ND
Flammable Limits - Upper	ND
Flammable Limits - Lower	ND
Vapor Pressure	
Vapor Density (Air=1)	ND
Viscosity	ND

## **SECTION X - STABILITY AND REACTIVITY**

Stability: Stable, under normal conditions of storage and handling.

**Conditions to Avoid:** Keep away from heat, hot surfaces, sparks, open flames or

other ignition sources.

Hazardous Decomposition/Byproducts: No known decomposition if stored properly.

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

**Incompatibilities:** Strong Oxidizers and strong reducing agents.

**BLUE MAGIC** 

#### **SECTION XI - TOXICOLOGICAL INFORMATION**

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

**Inhalation:** May cause irritation to the upper respiratory tract and CNS depression.

Low to moderate degree of toxicity by inhalation.

**Eye Contact:** Causes eye irritation including stinging, watering and redness which

may result in corneal injury.

**Skin Contact:** Contact may cause mild stinging and irritation including redness,

burning and drying/cracking of the skin.

No harmful effects from skin adsorption are expected.

**Ingestion:** Aspiration hazard. Can enter the lungs during swallowing or vomiting

and cause chemical pneumonia and edema.

**Acute Toxicity Value:** See Health Hazards below.

**Chronic (Long Term) Effects:** See Health Hazards above.

Suspected of damaging fertility.

## **Toxicity:**

Component Name	LD50	LC50
Hexane	Oral - rat - 25,000 mg/kg; Dermal - rabbit - 2,001 mg/kg	Inhalation - rat - 4H/171.6 mg/l
Hydrotreated Light Naphtha	Oral - Rat - > 2000 mg/kg - Dermal - rat - > 2000 mg/kg	Not Established

**Reproductive Effects** Not Applicable

**Teratogenicity** Not Applicable

Mutagenicity Not Applicable

**Embryotoxicity** Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

**Carcinogenicity** Not Listed as a Carcinogen

### **SECTION XII - ECOLOGICAL INFORMATION**

**Ecotoxicity:** Acute aquatic toxicity.

**BLUE MAGIC** 

**Mobility:** Information not available.

**Degradability:** Information not available.

**BioAccumulation:** Information not available.

### **SECTION XIII - WASTE DISPOSAL CONSIDERATIONS**

Follow Federal, state, and local regulations.

#### **SECTION XIV - TRANSPORT INFORMATION**

#### **DOT SHIPPING INFORMATION**

**Proper Shipping Name:** Flammable liquid, n.o.s. (contains hexanes, petroluem distillates)

Contains:

Hazard Class and Label: 3

Identification Number: UN1993

Packaging Group:

Other Shipping Info:

### **SECTION XV - REGULATORY INFORMATION**

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

# SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

## SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X		X		

### **SARA TITLE III SECTION 313 SUPPLIER INFORMATION:**

Component Name	CAS#	% by wt.
n-hexane	110-54-3	50-60

# **CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:**

#### **BLUE MAGIC**

Component Name	CAS#	% by wt.	RQ (lbs.)
Hexane	110-54-3	50-60	5,000

#### **CALIFORNIA PROPOSITION 65:**

No chemicals in this material are subject to the reporting requirements.

#### **SECTION XVI - OTHER INFORMATION**

Additional: Other Information (XVI) - Revision 3

**Specification Information** 

Department issuing data sheet:

Email address: sales@carchem.com

Training necessary: Always use personal protective equipment when using any type of

chemicals for home or business use.

#### Disclaimer:

THIS SAFETY DATA SHEET CONTAINS CERTAIN INFORMATION OBTAINED FROM OUTSIDE RESOURCES BELIEVED TO BE RELIABLE BUT WE CANNOT BE ASSURED THAT SUCH INFORMATION IS ACCURATE. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE WHATSOEVER IN CONNECTION WITH THIS SAFETY DATA SHEET. CAR CHEM SPECIFICALLY DISCLAIMS THE MAKING OF ANY SUCH WARRANTIES, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE. ALL RISK IS ASSUMED BY THE USER. IN NO EVENT SHALL CAR CHEM BE LIABLE TO ANYONE, WHETHER ARISING OUT OF ERRORS OR OMMISSIONS, NEGLIGENCE, ACCIDENT OR ANY OTHER CAUSE, FOR ANY LOSS OR DAMAGE, INCLUDING, WITHOUT LIMITATION, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES. ANY LIABILITY ON THE PART OF CAR CHEM IS STRICTLY LIMITED TO A REFUND IN THE AMOUNT PAID FOR THE SPECIFIC PRODUCT INVOLVED. IT IS THE USER'S RESPONSIBILITY TO ENSURE SAFE CONDITIONS FOR HANDLING, STORAGE AND DISPOSAL OF THE PRODUCT, AND SUCH USER ASSUMES FULL RESPONSIBILITY AND LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSES DUE TO IMPROPER USE. CAR CHEM EXPRESSLY DISCLAIMS LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.