

Safety Data Sheet
SHOW SHINE WITH SILICONE

SECTION I - IDENTIFICATION



Car Chem
398 S. King Oak St.
Trenton, IL 62293
(618) 224-7445
INFOTRAC :..... (800) 535-5053

Product Number CC SHW
Product Name SHOW SHINE WITH SILICONE
Chemical Family Mixture
CAS Number 111-76-2
Date Prepared 5/28/2015
Revision Number 7/6/2020
Recommended Use DRESSING

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Skin Corrosion/Irritation	Category 3
Serious Eye Damage/Eye Irritation	Category 2B

WARNING!

GHS LABEL:

Hazard Statements

H316	Causes mild skin irritation
H320	Causes eye irritation

Safety Data Sheet
SHOW SHINE WITH SILICONE

Precautionary Statements

- P264 Wash hands thoroughly after handling.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
- P332+313 If skin irritation occurs: get medical attention.
- P337+313 If eye irritation persists get medical attention.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
2-Butoxyethanol	111-76-2	<5	50 ppm	20 ppm

SECTION IV - FIRST AID MEASURES

- Contact with eyes:** Flush eyes with running water for ten minutes. Remove contact lenses and continue to flush. If irritation persists, seek medical attention.
- Skin contact:** If on skin rinse well with clean water and soap. If on clothing remove the contaminated clothing immediately. Wash clothing before reuse. Seek medical attention/advice if needed.
- Inhalation:** Remove victim to fresh air. If breathing difficulty seek medical attention. Administer oxygen or artificial respiration if breathing is affected or stopped. Loosen any tight clothing.
- Ingestion:** Do not use mouth to mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one way valve or other proper respiratory medical device.

SECTION V - FIREFIGHTING MEASURES

- Suitable Extinguishing Media:** Not considered a fire hazard.
- Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area.
- Unusual Fire Fighting Hazards:** No unusual fire hazards known.

Safety Data Sheet
SHOW SHINE WITH SILICONE

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Always wear personal protective equipment to include shielding your eyes, exposed skin and breathing.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Methods for Cleaning Up: Suitable material for taking up: absorbing material, organic, sand. Wash with plenty of water.

SECTION VII - HANDLING AND STORAGE

Handling and Storage:

- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
2-Butoxyethanol	111-76-2	50 ppm	20 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV. Showers, eye wash stations.

Monitoring: Do not eat, drink or smoke in areas where this chemical is used or stored. Wash hands prior to eating, drinking or using the restroom.

Personal Protective Equipment (PPE)

Eye Protection: Use eye protection.

Skin Protection: May use gloves. Wash hands after use.

Respiratory Protection: Always use in a well ventilated area.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet
SHOW SHINE WITH SILICONE

Appearance	Purple or Blue Liquid
Odor	fruity aroma
pH@25°C	ND
Melting/Freezing Point	ND
Flashpoint	143°F, Minimum, (TCC)
Specific Gravity	0.9
Solubility	Complete
Auto-Ignition Temperature	ND
Decomposition Temperature	ND
VOC Content	ND
Odor Threshold	ND
Boiling Range	>212F
Evaporation Point	0.1 (Butyl Acetate =1)
Flammable Limits - Upper	12.7%
Flammable Limits - Lower	1.1%
Vapor Pressure	0.6 mmHg @ 20°C
Vapor Density (Air=1)	4.1 (Air=1)
Viscosity	ND

SECTION X - STABILITY AND REACTIVITY

Stability: Stable, under normal conditions of storage and handling.

Conditions to Avoid: Sparks, fire, and extreme temperatures.
Keep from freezing.

Hazardous Decomposition/Byproducts: CO, CO₂, and noxious smoke under extreme fire conditions

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Strong acids and bases, strong oxidizers

Safety Data Sheet
SHOW SHINE WITH SILICONE

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: May cause respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness.

Eye Contact: Causes eye irritation including stinging, watering and redness which may result in corneal injury.

Skin Contact: Contact may cause mild stinging and irritation including redness, burning and drying/cracking of the skin.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.
Low degree of toxicity by ingestion.

Acute Toxicity Value: See Health Hazards below.

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

Component Name	LD50	LC50
2-Butoxyethanol	Oral - Rat - 470 mg/kg; Dermal - Rabbit - 220 mg/kg;	Inhalation - Rat - 4 h - 450 ppm

Reproductive Effects Not Applicable

Teratogenicity Not Applicable

Mutagenicity Not Applicable

Embryotoxicity Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

Carcinogenicity Not Listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Mobility: Information not available.

Safety Data Sheet
SHOW SHINE WITH SILICONE

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Not Regulated

Contains:

Hazard Class and Label:

Identification Number:

Packaging Group:

Other Shipping Info:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
N/A	N/A	N/A		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Component Name	CAS #	% by wt.	RQ (lbs.)
2-Butoxyethanol	111-76-2	<5	5,000

CALIFORNIA PROPOSITION 65:

Safety Data Sheet
SHOW SHINE WITH SILICONE

No chemicals in this material are subject to the reporting requirements.

SECTION XVI - OTHER INFORMATION

HMIS Health: 1

HMIS Flammability: 0

HMIS Reactivity: 0

Additional: Other Information (XVI) - Revision 3

Specification Information

Department issuing data sheet:

Email address: sales@carchem.com

Training necessary: Always use personal protective equipment when using any type of chemicals for home or business use.

Disclaimer:

THIS SAFETY DATA SHEET CONTAINS CERTAIN INFORMATION OBTAINED FROM OUTSIDE RESOURCES BELIEVED TO BE RELIABLE BUT WE CANNOT BE ASSURED THAT SUCH INFORMATION IS ACCURATE. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE WHATSOEVER IN CONNECTION WITH THIS SAFETY DATA SHEET. CAR CHEM SPECIFICALLY DISCLAIMS THE MAKING OF ANY SUCH WARRANTIES, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE. ALL RISK IS ASSUMED BY THE USER. IN NO EVENT SHALL CAR CHEM BE LIABLE TO ANYONE, WHETHER ARISING OUT OF ERRORS OR OMISSIONS, NEGLIGENCE, ACCIDENT OR ANY OTHER CAUSE, FOR ANY LOSS OR DAMAGE, INCLUDING, WITHOUT LIMITATION, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES. ANY LIABILITY ON THE PART OF CAR CHEM IS STRICTLY LIMITED TO A REFUND IN THE AMOUNT PAID FOR THE SPECIFIC PRODUCT INVOLVED. IT IS THE USER'S RESPONSIBILITY TO ENSURE SAFE CONDITIONS FOR HANDLING, STORAGE AND DISPOSAL OF THE PRODUCT, AND SUCH USER ASSUMES FULL RESPONSIBILITY AND LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSES DUE TO IMPROPER USE. CAR CHEM EXPRESSLY DISCLAIMS LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.