

**Safety Data Sheet**  
**SLICK**

**SECTION I - IDENTIFICATION**



Car Chem  
398 S. King Oak St.  
Trenton, IL 62293  
(618) 224-7445  
INFOTRAC :..... (800) 535-5053

**Product Number** CC SL  
**Product Name** SLICK  
**Chemical Family** Mixture  
**CAS Number** Multiple  
**Date Prepared** 5/28/2015  
**Revision Number** 7/6/2020  
**Recommended Use** Lubricant

**SECTION II - HAZARDOUS IDENTIFICATION**

**GHS CLASSIFICATION:**

**Classification**

Flammable Liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Specific target organ toxicity, single exposure, N	Category 3
Reproductive Toxicity	Category 2
Specific target organ toxicity, repeated exposure	Category 2

**DANGER!**

**GHS LABEL:**



**Hazard Statements**

H225	Highly flammable gas and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause dizziness or drowsiness
H361	Suspected of damaging fertility or the unborn child
H373	Causes damage to organs through prolonged or repeated exposure

# Safety Data Sheet

## SLICK

### Precautionary Statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground or bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures to prevent static discharge.
P260	Do not breathe dust, fumes, gas, mist, vapors or spray.
P261	Avoid breathing dust, fumes, gas, mist, vapors or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, clothing, eye and face protection. Goggles, gloves, face mask/shield and/or a separate approved breathing apparatus if required.
P302+352	IF ON SKIN: Wash with plenty of running water and soap until all is removed.
P303+361+353	IF ON SKIN (or hair): Immediately remove all contaminated clothing. Rinse skin or hair with water or shower.
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P308+313	IF exposed or concerned: seek medical attention.
P312	Call a POISON CENTER or physician if you feel unwell.
P314	Get medical attention if you feel unwell.
P321	Specific treatment: refer to section four, first aid or see a physician.
P332+313	If skin irritation occurs: get medical attention.
P337+313	If eye irritation persists get medical attention.
P362+364	Immediately remove all contaminated clothing and wash them before reuse.
P370+378	In case of fire: Use alcohol resistant foam or CO2 to extinguish.
P403+233	Store in a well ventilated area with container tightly closed.
P403+235	Store in a cool, well ventilated area.
p405	Store locked up.

# Safety Data Sheet

## SLICK

P501

Dispose of contents or container according to all state, local and federal laws.

### SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Hexane	110-54-3	50-60	50 ppm	50 ppm
2- Propanone	67-64-1	5-15	750 ppm	500 ppm

### SECTION IV - FIRST AID MEASURES

**Contact with eyes:** Flush eyes with running water for ten minutes. Remove contact lenses and continue to flush. If irritation persists, seek medical attention.

**Skin contact:** If on skin rinse well with clean water and soap. If on clothing remove the contaminated clothing immediately. Wash clothing before reuse. Seek medical attention/advice if needed.

**Inhalation:** Remove victim to fresh air. If breathing difficulty seek medical attention. Administer oxygen or artificial respiration if breathing is affected or stopped. Loosen any tight clothing.

**Ingestion:** If swallowed. Do not induce vomiting unless instructed to do so by a poison control center. Rinse mouth. Seek immediate medical attention by calling 911 and seeing a physician.

### SECTION V - FIREFIGHTING MEASURES

**Suitable Extinguishing Media:** Water fog, foam, CO2, dry chemical.

**Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area.

**Unusual Fire Fighting Hazards:** Do not use high volume water jet.  
Hazardous gases may form during fire.

### SECTION VI - ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Keep all sources of ignition and hot metal surfaces away from spill or release.  
Evacuate all unprotected personnel from the area.  
Product in liquid and vapor form is extremely flammable.

**Environmental Precautions:** Prevent liquid from entering drains, sewers or waterways.  
Contain spill if it can be done with minimal risk.  
Notify proper authorities. Reportable Quantity is 9090 pounds or 1620 gallons.

## Safety Data Sheet

### SLICK

**Methods for Cleaning Up:** Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.  
Use spark proof equipment. Prevent entry into waterways. Contain and collect spillage with a non combustible absorbent material like sand, vermiculite, diatomous earth.

#### SECTION VII - HANDLING AND STORAGE

- Handling and Storage:**
- NFPA Class I storage.
  - Vent container carefully before opening.
  - Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
  - "Empty" containers may retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
  - Keep containers tightly closed when not in use.
  - Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

#### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

**EXPOSURE LIMITS:**

Component Name	CAS #	OSHA PEL	ACGIH TLV
Hexane	110-54-3	50 ppm	50 ppm
2- Propanone	67-64-1	750 ppm	500 ppm

**Engineering Controls:** Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV. Showers, eye wash stations.

**Monitoring:** Follow accepted work practices for handling a flammable material.  
Do not eat, drink or smoke in areas where this chemical is used or stored.  
Have eye wash stations and safety showers readily available.

**Personal Protective Equipment (PPE)**

**Eye Protection:** Goggles or approved OSHA device with side shields.

**Skin Protection:** Impervious solvent resistant gloves.  
Impervious apron and work boots recommend where splashing may occur.

**Respiratory Protection:** Use the proper respirator in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

#### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

## Safety Data Sheet

### SLICK

Appearance	Clear, Blue Liquid
Odor	fruit scented
pH@25°C	ND
Melting/Freezing Point	ND
Flashpoint	ND
Specific Gravity	
Solubility	Negligible
Auto-Ignition Temperature	ND
Decomposition Temperature	ND
VOC Content	ND
Odor Threshold	ND
Boiling Range	ND
Evaporation Point	ND
Flammable Limits - Upper	ND
Flammable Limits - Lower	ND
Vapor Pressure	ND
Vapor Density (Air=1)	ND
Viscosity	ND

#### SECTION X - STABILITY AND REACTIVITY

**Stability:** Stable, under normal conditions of storage and handling.

**Conditions to Avoid:** Extreme heat and ignition sources.

**Hazardous Decomposition/Byproducts:** CO, CO<sub>2</sub>, and noxious smoke under extreme fire conditions

**Hazardous Polymerization:** Will not occur.

**Polymerization Conditions to Avoid:** None

**Incompatibilities:** Strong oxidizers

# Safety Data Sheet

SLICK

## SECTION XI - TOXICOLOGICAL INFORMATION

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

**Inhalation:** May cause irritation to the upper respiratory tract and CNS depression.  
Low to moderate degree of toxicity by inhalation.

**Eye Contact:** Causes eye irritation including stinging, watering and redness which may result in corneal injury.

**Skin Contact:** Contact may cause mild stinging and irritation including redness, burning and drying/cracking of the skin.  
No harmful effects from skin adsorption are expected.

**Ingestion:** Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.

**Acute Toxicity Value:** See Health Hazards below.

**Chronic (Long Term) Effects:** See Health Hazards above.

### Toxicity:

Component Name	LD50	LC50
Hexane	Oral - rat - 25,000 mg/kg; Dermal - rabbit - 2,001 mg/kg	Inhalation - rat - 4H/171.6 mg/l
2- Propanone	Oral -rat - 7,060 mg/kg	Inhalation -rat - 10H/20,000,000 ppm

**Reproductive Effects** Not Applicable

**Teratogenicity** Not Applicable

**Mutagenicity** Not Applicable

**Embryotoxicity** Not Applicable

**Sensitization to Product** Not Applicable

**Synergistic Products** Not Applicable

**Carcinogenicity** Not Listed as a Carcinogen

## SECTION XII - ECOLOGICAL INFORMATION

**Ecotoxicity:** Information not available.

# Safety Data Sheet

SLICK

**Mobility:** Information not available.

**Degradability:** Information not available.

**BioAccumulation:** Information not available.

## SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

## SECTION XIV - TRANSPORT INFORMATION

### DOT SHIPPING INFORMATION

**Proper Shipping Name:** Flammable liquids, n.o.s., (Contains Hexanes and Acetone)

**Contains:**

**Hazard Class and Label:** 3

**Identification Number:** UN1993

**Packaging Group:** II

**Other Shipping Info:**

## SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:**..... The components of this product are listed on the TSCA Inventory

### SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

### SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X		X		

### SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

Component Name	CAS #	% by wt.
n-hexane	110-54-3	50-60

### CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

## Safety Data Sheet

### SLICK

Component Name	CAS #	% by wt.	RQ (lbs.)
Hexane	110-54-3	50-60	5,000
2- Propanone	67-64-1	5-15	5,000 LBS

#### CALIFORNIA PROPOSITION 65:

No chemicals in this material are subject to the reporting requirements.

#### SECTION XVI - OTHER INFORMATION

HMIS Health: ..... 2

HMIS Flammability: ..... 2

HMIS Reactivity: ..... 0

Additional:

#### Specification Information

Department issuing data sheet:

Email address: sales@carchem.com

Training necessary: Always use personal protective equipment when using any type of chemicals for home or business use.

#### Disclaimer:

THIS SAFETY DATA SHEET CONTAINS CERTAIN INFORMATION OBTAINED FROM OUTSIDE RESOURCES BELIEVED TO BE RELIABLE BUT WE CANNOT BE ASSURED THAT SUCH INFORMATION IS ACCURATE. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE WHATSOEVER IN CONNECTION WITH THIS SAFETY DATA SHEET. CAR CHEM SPECIFICALLY DISCLAIMS THE MAKING OF ANY SUCH WARRANTIES, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE. ALL RISK IS ASSUMED BY THE USER. IN NO EVENT SHALL CAR CHEM BE LIABLE TO ANYONE, WHETHER ARISING OUT OF ERRORS OR OMISSIONS, NEGLIGENCE, ACCIDENT OR ANY OTHER CAUSE, FOR ANY LOSS OR DAMAGE, INCLUDING, WITHOUT LIMITATION, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES. ANY LIABILITY ON THE PART OF CAR CHEM IS STRICTLY LIMITED TO A REFUND IN THE AMOUNT PAID FOR THE SPECIFIC PRODUCT INVOLVED. IT IS THE USER'S RESPONSIBILITY TO ENSURE SAFE CONDITIONS FOR HANDLING, STORAGE AND DISPOSAL OF THE PRODUCT, AND SUCH USER ASSUMES FULL RESPONSIBILITY AND LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSES DUE TO IMPROPER USE. CAR CHEM EXPRESSLY DISCLAIMS LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.