

Safety Data Sheet
WEIGHT SOLUTION

SECTION I - IDENTIFICATION



Car Chem
398 S. King Oak St.
Trenton, IL 62293
(618) 224-7445
INFOTRAC :..... (800) 535-5053

Product Number CC WS55/250
Product Name WEIGHT SOLUTION
Chemical Family Alcohols
CAS Number 67-56-1
Date Prepared 5/28/2015
Revision Number 7/5/2020
Recommended Use Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Flammable Liquids	Category 2
Acute Toxicity, Oral	Category 3
Acute Toxicity, Dermal	Category 3
Acute Toxicity, Inhalation	Category 3
Specific target organ toxicity, single exposure	Category 1

DANGER!

GHS LABEL:



Hazard Statements

H225	Highly flammable gas and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

Safety Data Sheet

WEIGHT SOLUTION

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground or bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures to prevent static discharge.
P260	Do not breathe dust, fumes, gas, mist, vapors or spray.
P261	Avoid breathing dust, fumes, gas, mist, vapors or spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, clothing, eye and face protection. Goggles, gloves, face mask/shield and/or a separate approved breathing apparatus if required.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P302+352	IF ON SKIN: Wash with plenty of running water and soap until all is removed.
P303+361+353	IF ON SKIN (or hair): Immediately remove all contaminated clothing. Rinse skin or hair with water or shower.
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P308+311	IF exposed or concerned: Call POISON CENTER or physician.
P311	Call a POISON CENTER or physician.
P312	Call a POISON CENTER or physician if you feel unwell.
P321	Specific treatment: refer to section four, first aid or see a physician.
P330	Rinse mouth if accidentally swallowed.
P362+364	Immediately remove all contaminated clothing and wash them before reuse.
P370+378	In case of fire: Use alcohol resistant foam or CO2 to extinguish.
P403+233	Store in a well ventilated area with container tightly closed.
P403+235	Store in a cool, well ventilated area.
P405	Store locked up.
P501	Dispose of contents or container according to all state, local and federal laws.

Safety Data Sheet
WEIGHT SOLUTION

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Methanol	67-56-1	23-28%	200 ppm(Skin)	200 ppm(Skin)

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush eyes with running water for ten minutes. Remove contact lenses and continue to flush. If irritation persists, seek medical attention.

Skin contact: If on skin rinse well with clean water and soap. If on clothing remove the contaminated clothing immediately. Wash clothing before reuse. Seek medical attention/advice if needed.

Inhalation: Remove victim to fresh air. If breathing difficulty seek medical attention. Administer oxygen or artificial respiration if breathing is affected or stopped. Loosen any tight clothing.

Ingestion: If swallowed. Do not induce vomiting unless instructed to do so by a poison control center. Rinse mouth. Seek immediate medical attention by calling 911 and seeing a physician.
Call poison control and seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area.

Unusual Fire Fighting Hazards: Do not use high volume water jet.
Hazardous gases may form during fire.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or release.
Evacuate all unprotected personnel from the area.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.
Notify proper authorities. Reportable Quantity is 5,000 pounds or 758 gallons.
Contain spill if it can be done with minimal risk.

Methods for Cleaning Up: Use foam on spills to minimize vapors.
Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.

Safety Data Sheet
WEIGHT SOLUTION

SECTION VII - HANDLING AND STORAGE

- Handling and Storage:**
- NFPA Class I storage.
 - Vent container carefully before opening.
 - Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
 - "Empty" containers may retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
 - Keep containers tightly closed when not in use.
 - Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
Methanol	67-56-1	200 ppm(Skin)	200 ppm(Skin)

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV. Showers, eye wash stations.

Monitoring: Follow accepted work practices for handling a flammable material. Do not eat, drink or smoke in areas where this chemical is used or stored. Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields.

Skin Protection: Impervious solvent resistant gloves.
Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet
WEIGHT SOLUTION

Appearance	Purple Liquid
Odor	Strong Characteristic Alcohol Odor
pH@25°C	-ND
Melting/Freezing Point	ND
Flashpoint	41°C
Specific Gravity	
Solubility	Miscible
Auto-Ignition Temperature	-ND
Decomposition Temperature	-ND
VOC Content	
Odor Threshold	ND
Boiling Range	ND
Evaporation Point	ND
Flammable Limits - Upper	ND
Flammable Limits - Lower	ND
Vapor Pressure	
Vapor Density (Air=1)	
Viscosity	-ND

SECTION X - STABILITY AND REACTIVITY

- Stability:** Stable, under normal conditions of storage and handling.
- Conditions to Avoid:** Extreme heat and ignition sources.
Sparks, fire, and extreme temperatures.
- Hazardous Decomposition/Byproducts:** Vapors may form explosive mixture with air.
- Hazardous Polymerization:** Under normal conditions of storage and use, hazardous reactions should not occur.
- Polymerization Conditions to Avoid:** None known.
- Incompatibilities:** Strong oxidizers such as barium, perchlorate, bromine, and chlorine. Beryllium hydride. Metals such as aluminum, magnesium, potassium and zinc. Chloroform and sodium methoxide. Diethyl zinc. Acetyl bromide. Sodium hypochlorite.

Safety Data Sheet
WEIGHT SOLUTION

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: Toxic after short term inhalation.

Eye Contact: Causes eye irritation including stinging, watering and redness which may result in corneal injury.

Skin Contact: Contact may cause mild stinging and irritation including redness, burning and drying/cracking of the skin.
Toxic after single exposure to the skin. May cause degreasing.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.
Moderate to high degree of toxicity by ingestion. May be harmful or fatal if swallowed.

Acute Toxicity Value: See Health Hazards below.

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

Component Name	LD50	LC50
Methanol	Oral - Human - 143 mg/kg; Oral - rat - 1,187 - 2,769 mg/kg;	Inhalation - rat - 4 h - 128.2 mg/l; Inhalation - rat - 6 h - 87.6 mg/l

Reproductive Effects Not Applicable

Teratogenicity Not Applicable

Mutagenicity Not Applicable

Embryotoxicity Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

Carcinogenicity Not Listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Mobility: Information not available.

Safety Data Sheet
WEIGHT SOLUTION

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Methanol Solution

Contains:

Hazard Class and Label: 3, 6.1

Identification Number: UN1230

Packaging Group: II

Other Shipping Info:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X	X	X		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

Component Name	CAS #	% by wt.
Methanol	67-56-1	23-28%

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Component Name	CAS #	% by wt.	RQ (lbs.)
Methanol	67-56-1	23-28%	5,000

CALIFORNIA PROPOSITION 65:

Safety Data Sheet
WEIGHT SOLUTION

This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

SECTION XVI - OTHER INFORMATION

HMIS Health: 2

HMIS Flammability: 3

HMIS Reactivity: 0

Additional: Other Information (XVI) Revision 2

Specification Information

Department issuing data sheet:

Email address: sales@carchem.com

Training necessary: Always use personal protective equipment when using any type of chemicals for home or business use.

Disclaimer:

THIS SAFETY DATA SHEET CONTAINS CERTAIN INFORMATION OBTAINED FROM OUTSIDE RESOURCES BELIEVED TO BE RELIABLE BUT WE CANNOT BE ASSURED THAT SUCH INFORMATION IS ACCURATE. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE WHATSOEVER IN CONNECTION WITH THIS SAFETY DATA SHEET. CAR CHEM SPECIFICALLY DISCLAIMS THE MAKING OF ANY SUCH WARRANTIES, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE. ALL RISK IS ASSUMED BY THE USER. IN NO EVENT SHALL CAR CHEM BE LIABLE TO ANYONE, WHETHER ARISING OUT OF ERRORS OR OMISSIONS, NEGLIGENCE, ACCIDENT OR ANY OTHER CAUSE, FOR ANY LOSS OR DAMAGE, INCLUDING, WITHOUT LIMITATION, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES. ANY LIABILITY ON THE PART OF CAR CHEM IS STRICTLY LIMITED TO A REFUND IN THE AMOUNT PAID FOR THE SPECIFIC PRODUCT INVOLVED. IT IS THE USER'S RESPONSIBILITY TO ENSURE SAFE CONDITIONS FOR HANDLING, STORAGE AND DISPOSAL OF THE PRODUCT, AND SUCH USER ASSUMES FULL RESPONSIBILITY AND LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSES DUE TO IMPROPER USE. CAR CHEM EXPRESSLY DISCLAIMS LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.