

SPECIFICATION SHEET

Underdesk Power Units with Dual USB & Cat6 Data



Model	Description	Fused	Data	USB	Dimensions
PP2/2DCU	2 Power Underdesk Power with Cat6 & USB	5A	Cat6 In/Out	Type A & C (18W Max)	(L) TBCmm x (W) 62mm x (H) 42mm
PP4/2DCU	2 Power Underdesk Power with Cat6 & USB	5A	Cat6 In/Out	Type A & C (18W Max)	(L) TBCmm x (W) 62mm x (H) 42mm
PP6/DC2U	2 Power Underdesk Power with Cat6 & USB	3.15A	Cat6 In/Out	Type A & C (18W Max)	(L) TBCmm x (W) 62mm x (H) 42mm

Product Description

- Made from high grade engineering plastic materials
- UK sockets Individually fused (20mm Glass Fuse)
- Cat6 input / output assemblies
- USB Type A & C Smart chargers (QC3.0, PD 18W Max)
- Complies with BS-6396: 2022 / BS5733
- 3 pin input power connector
- Screwholes for fixing

The smart charger sends the appropriate power intelligently to the device, the A & C USB charger has a total output of both A&C of 18W max for example:

- USB-A & USB-C QC 3.0, 2V/5A, 5V/3A & 9V/2A, complies with BC1.2 & Apple Protocol
- USB-C PD, 2V/5A, 5V/3A & 9V/2A, complies with BC1.2, PD2.0, QC3.0 & Apple Protocols



Model	Description	Length
PC1	Power cord fitted with 13A UK plug	1 metre
PC2	Power cord fitted with 13A UK plug	2 metre
PC3	Power cord fitted with 13A UK plug	3 metre
PC4	Power cord fitted with 13A UK plug	4 metre
PC5	Power cord fitted with 13A UK plug	5 metre

Longer lengths available upon enquiry

Contact: sales@floorbox.co.uk | Visit: www.floorbox.co.uk

Customer notice: Due to our policy of continuous improvement, Tass Cable Management Ltd reserve the right to change product specifications without notice. Tass Cable Management Ltd © | Floorbox.co.uk © | 2023 | All rights Reserved.