

SPECIFICATION SHEET

Underdesk Modular Power Surge Unit (3 Pin In & Out Connectors)



| Model | Description | Surge Suppression | Max Surge | Connectors (In/Out) | Unit Length |
|--------------|--------------------------|-------------------|-----------|---------------------|-------------|
| P-PACK/SURGE | Modular Power Surge Unit | 1800 Joules | 6500A | 3 Pin / 3 Pin | 140mm |

Product Description

- Tough ABS plastic construction
- Complies with BS-6396 as standard
- 200mm Earth lead
- Checks for L/N reverse
- Unique in-line surge protection
- Unit can retro fitted to existing installations
- Neon Status indicators
- Male 3 Pin Input / Female 3 pin output connectors

Specifications

| | |
|---------------------------|------------------------------------|
| Model: | P-PACK/SURGE |
| Dimensions: | (L) 140mm x (W) 62mm x (H) 42mm |
| Construction: | Tough ABS Plastic |
| Colour: | Black |
| Surge Suppression: | 1,800 Joules |
| Max Surge: | 6500A |
| Max Load: | 250V 13A |
| Clamping Voltage: | 775V |
| Response time: | 1 Nano Second |
| Indicator Lamps | Yes - Power / Surge / L/N Reverse |
| Connection Type: | 3 Pin Connectors In/Out |
| Fixing Type: | Screw Holes |
| Compliance: | BS6396:2008 / UL 94V0 rated / RoHS |

Contact: sales@floorbox.co.uk | **Visit:** www.floorbox.co.uk

Customer notice: Due to our policy of continuous improvement, Tass Cable Management Ltd reserve the right to change product specifications without notice. Tass Cable Management Ltd © | Floorbox.co.uk © | 2021 | All rights Reserved.