

MODEL: ST0287FM/RCD FLUSH MOUNTED RCD SOCKET (WARCDP036)

Suitable for use with: TFB3/80, TFB3/90 & TSB3/80



Technical Information

Plate	ST0287FM/RCD (185 x 89mm)	Trip speed	Less than 40ms at 150mA Residual Current
Plate Colour	Light Grey / RAL:7035	Through Fault Withstand	1500
Socket Material / Colour	Plate/Rocker: Urea (White) / Terminals: Brass	Breaking Capacity	250A (Earth Leakage)
No. of Outlets	2	IP Rating	IP20
Anti Microbial Certified:	Yes	Max. Installation Altitude	2000m
Switched	Yes	Min. Switch Contact Gap	3mm
Indicator Lamps	No	Min. Wall Box Depth	35mm
Resistive Load Withstand	13A	Nature of Supply	AC
Rated Frequency	50 Hz	Warranty	10 years
Rated Voltage	250V	Ambient Operating Temp.	-5 to 40°C (not exceeding 25°C within 24hrs)
Terminal Capacity / Type	3 x 2.5mm, 3 x 4.0mm / Screw	Standards	BS:7288 / 1363 / IEC 62640 / SASO 2203

Note: Due to the sensitive electronics used within the USB & RCD sockets it is important to make sure the sockets are installed in a clean and dust free environment.

Disclaimer: Due to our policy of continuous improvement, Tass Cable Management Ltd reserve the right to change product specifications without notice.

Contact: sales@floorbox.co.uk | **Visit:** www.floorbox.co.uk

Customer notice: Due to our policy of continuous improvement, Tass Cable Management Ltd reserve the right to change product specifications without notice. Tass Cable Management Ltd © | Floorbox.co.uk © | 2023 | All rights Reserved.