

MODEL: ST0291/RCD PLATE (TYPE A) - Latching Type

Suitable for floorboxes and screedboxes with Box depths of 80mm or above.



Technical Information

Plate Dimensions	185 x 89mm	Associated Standards	BS7288-2016
Plate Colour	Light Grey (RAL: 7035)	Fault Current Rating (mA)	30
Socket Material	Thermoset (Moulded)	Fixing Screws	2 x M3.5
No. of Outlets	2	IP Rating	IP2X
Rocker Finish	White Moulded	Max. Installation Altitude	2000m
Switched	Yes	Min. Switch Contact Gap	3mm
Indicator Lamps	No	Min. Wall Box Depth	35mm
Rated Current	13A	Nature of Supply	AC
Rated Frequency	50-60 Hz	Operational Testing	30,000
Rated Voltage	220-250V	Ambient Operating Temp.	-5 to 40°C (24 Hour average not exceeding 25°C)
Terminal Capacity	3 x 2.5mm, 3 x 4.0mm, 2 x 6.0mm		

Note: Due to the sensitive electronics used within the USB & RCD sockets it is important to make sure the sockets are installed in a clean and dust free environment.  
Disclaimer: Due to our policy of continuous improvement, Tass Cable Management Ltd reserve the right to change product specifications without notice.