



### Product Description

- Floor box manufactured from galvanised steel
- 25 & 20mm knockouts to accept flexible conduit
- Frame & lid moulded from high impact polycarbonate, colour equivalent: RAL7031
- Galvanised lid insert for strength
- Easy grip recessed lifting handle
- Compact design 218 x 150mm floor cut-out
- Designed to accept 1 accessory plates
- Large range of accessory plates, colour equivalent: RAL7035
- Special plates available to order
- Clean Earth Sockets available
- ABS Plastic Frame & Lid Load Test 550 KG
- Steel Frame & Lid Load Test 740 KG
- Please note the 65mm depth floor box has restrictive cabling capacity

### Specifications

<b>Floor Cut Out:</b>	218mm x 150mm
<b>Depth:</b>	65mm
<b>Plug Top Clearance:</b>	20mm
<b>Overall Frame &amp; Lid:</b>	230mm x 160mm
<b>Frame Lid Recess:</b>	6mm
<b>Accessory Plates:</b>	185mm x 89mm

#### Customer Notice

Be advised that when installing ST0286 & ST0287 range of accessory plates the Plug Top wiring space is reduced. The 65mm & 75mm Screed boxes are not recommended for RCD sockets due to wiring compartment Depth. For RCD Sockets Please use the TSB1/80 Screed box.

### Plug Top Clearance Diagram

