Butterfly Sprinkler

Applications

- Economical low pressure 'butterfly' type sprinkler with rotating spinner.
- For use in nurseries
- Manufactured from quality engineering plastics with stainless steel spindle

Specifications

- Inlet: 15 mm MBSP
- Jet size: 3.1 mm
- Flows: 4.4 Lpm to 7 Lpm
- Diameters: 9.8 m to 11 m



An economical alternative.

Ordering Information		
Code	Description	
1015192	Butterfly Sprinkler	

Performance Chart				
kPa	Lpm	Dia (m)		
100	4.4	9.8		
150	5.5	11.0		
200	6.4	10.8		
250	7.0	10.5		

Rotoframe[™] Rotating Sprinklers

Applications

Lower pressure 'butterfly' sprinkler with rotating spinner and frame which provides improved water distribution.

- For use in Nurseries and Market Gardens
- Die-cast zinc body, stainless steel spindle, plastic spinner and brass nut

Specifications

- Inlet: 15 mm FBSP and 20 mm FBSP
- Jet size: 5 mm
- Flows: 11.8 Lpm to 16.2 Lpm
- Diameters: 10.9 m to 12.0 m

Ordering Information		
Code	Description	
1015190	15 mm BSP Female	
1015191	20 mm BSP Female	



Rotating spinner and frame provides improved water distribution.

Peri	Performance Chart			
kPa	Lpm	Dia (m)		
100	11.8	10.9		
150	13.2	11.8		
200	14.7	12.0		
250	16.2	11.6		

Company policy is one of constant improvement and therefore changes in specifications may be made without notice and without incurring liability. Please refer to www.toro.com.au Toro Australia Pty Ltd, 53 Howards Road, Beverley, South Australia, 5009. Phone 1300 130 898, fax (08) 8243 2488. A.B.N. 47 001 310 443