

# Advanced Acoustics 22mm SilentBoard Datasheet 600mmx1200mm

## Material Description

SilentBoard is a unique A1 fire rated high density fibre cement floor board designed to be used in a wide range of applications. The high mass properties helps to reduce airborne noise penetration and transfer through separating floors. SilentBoard installed on top of R10 Acoustic Matting provides a very efficient and stable floating floor. This product can also be used in conjunction with our SoundSense Isolation System for improved sound isolation. With it being fibre cement it is not affected by weather/moisture so provides an ideal structural platform to work from, even if exposed to the elements.

SilentBoard has Tongue and Groove on all 4 sides making it simple to fit. It is easy to lay with minimal waste and is frost, moisture and weather resistant. As well as being Class A1 fire resistant it is also 100% completely recyclable. As well as the acoustic improvements that come with this product it will also help to improve thermal properties specifically when used in conjunction with underfloor heating.

SilentBoard has a wide range of suitable applications including flat roofs, loft conversions, renovations, new builds, bathrooms, kitchens, wetrooms, mezzanine flooring and more. It can be laid on metal, timber and concrete structures and any type of floor can be laid on top of it.

By using SilentBoard in your build you are guaranteed to have a squeak free installation when used in conjunction with Green Glue Joist Tape.

SilentBoard comprises of Portland cement, cellulose fibres, sand, water and other minor aggregates. These construction boards completely fulfil the requirements of resistance, safety and durability required in the construction of buildings as well as the most stringent environmental regulations. When exposed to moisture these boards don't change shape, rot or expand like chipboard, plywood or other timber based flooring.



## Technical Specifications

### Product Composition

A1 rated High Density Fibre Cement Construction Board

### Product Dimensions

600mm x 1200mm x 22mm

### Weight per board

24.8kg

### Area per board

0.72sqm

### Density

>1200kg/m<sup>3</sup>

### Thickness Tolerance

+/- 5%

### Dimension Tolerance

+/- 1mm

### Weight Tolerance

+/- 5%

### Modulus Of Rupture EMC - min

10vMPa

### Free Moisture Content

6%

### Water Absorption- submersion after 22 hrs

36%

### Lamina Bond Strength

0.9 MPa

### Thermal Conductivity (K) (30°C Mean Temp)

0.172W/M .k

### pH Value

10.4

### U Value

0.1279 Wm<sup>2</sup>K

### Fire Rating

Class A1