

Advanced Acoustics Euphonic Wedge Standard Acoustic Tile

Data Sheet

Individual Acoustic Tile	15" x 15" (381mm x 381mm)
Sizes Available	
Quantity Of Acoustic Tiles	24
Per Box	
Total Area Covered Per	37.5ft ² (3.48m ²)
Box	
Acoustic Tile Thickness	Plain - 1" (25mm) at the base, 2" (50mm) at the peak
	Profiled $-\frac{3}{4}$ " (20mm) at the base, $1\frac{1}{2}$ " (40mm) at the peak
Noise Reduction	0.80
Coefficient (NRC)	
Acoustic Foam Colour	Charcoal
Acoustic Foam Density	30 kg/m ³
Acoustic Foam	Open Cell Polyurethane Acoustic Foam
Composition	
Fire Classification	Crib 5 and Schedule 1, Part 1 of the Furnishings and
	Furniture (fire)(safety) Regulations 1988 (amended 1989)
Profile Description	An evenly mixed box of CNC cut Wedge Profile tiles with 1 $\frac{1}{2}$ " between peaks and plain faced tiles with a 45 ⁰ taper on all 4 sides, 12 tiles of each

Description

The Euphonic range of acoustic tiles is a very popular choice for studio installers. The mix of plain faced tiles and profiled tiles is a unique idea that offers outstanding performance for the price and thickness. It also adds another insight to what acoustic treatment can look like. By installing clusters of these tiles on the wall you can create a stylish and unique looking studio. But it isn't just the visual appeal that makes this range of acoustic tiles impressive it's the performance that comes with it. The problem with plain faced tiles is that they can look a little bland. However plain faced tiles will give you better absorption over profiled tiles of the same thickness. The problem with profiled tiles is that by removing some of the foam from the tile you reduce performance but they look cooler than plain faced acoustic tiles. So why not combine the two and totally eliminate the problem?

With a total thickness of just 50mm it is amazing that we have been able to get so much absorption from such a thin tile. This performance doesn't just come around by chance. We carefully develop each product to ensure we give you the best absorption possible for the best price possible and if sales of this range are anything to go by, we got this one very right.



www.advancedacoustics-Uk.com/info@advancedacoustics-uk.com/01623 643609

The acoustic foam we use conforms to the more stringent fire tests of Crib 5 and Schedule 1, Part 1 of the Furnishings and Furniture Regulations so you will have peace of mind that the product you are using is safe also. And you also have our guarantee that the foam will stand the test of time. The colour we use has been carefully selected to ensure that it doesn't quickly discolour or fade over time. You won't have the problem of the foam crumbling and turning to dust either. We know that treating your studio is a big investment and we want to make sure that your investment stands the test of time. The only way to ensure that is by sticking with Advanced Acoustics. We have many years of experience in acoustic treatment and soundproofing. Acoustic Treatment and Soundproofing are the only products we deal with. You won't see us selling any other forms of foam or bedding. Acoustic foam is all we do and we are very good at it as our outstanding feedback and previous customers will testify. Our products have been used by a full host of companies including the BBC, Williams F1 Team, McLaren, Cisco, Cadburys and ITN just to mention a few.

This item is kept permanently in stock. The foam we use is an open cell polyurethane acoustic foam and is available in charcoal only. A thicker version of this tile is also available.



Full performance details are on the next page



www.advancedacoustics-uk.com | info@advancedacoustics-uk.com | 01623 643609

٦

SRL

Г

The state is 21/03/2014 in the second with Sample: Temperature: 16.5 °C. Humidity: 55 %RH Pressure: 998 tample Description: Wedge Euphonic Standard Acoustic Tile Pack to uniting Method: A tample Area: 11.5 m2 tamper Volume: 300 m3 to $\frac{1}{1250} \frac{1}{5.55} \frac{1}{5.51} \frac{1}{1250} \frac{1}{5.55} \frac{1}{5.61} \frac{1}{1250} \frac{1}{5.55} \frac{1}{5.61} \frac{1}{1250} \frac{1}{5.52} \frac{1}{5.61} \frac{1}{5.5} \frac{1}{5.61} \frac{1}{5.5} \frac{1}{5.61} \frac{1}{5.5} \frac{1}{5.61} \frac{1}{5.5} \frac{1}{5.5} \frac{1}{5.61} \frac{1}{5.5} \frac{1}{5.5} \frac{1}{5.51} \frac{1}{5.5} \frac{1}{5.5} \frac{1}{5.51} \frac{1}{5.55} \frac{1}{5.55} \frac{1}$											d Acoustics	Advance		lient:
Sempty Room: Temperature: 16.5 °C Humidity: 55 %RH Pressure: 998 Room with Sample: Temperature: 15.4 °C Humidity: 50 %RH Pressure: 998 Sample Description: Wedge Euphonic Standard Acoustic Tile Pack Acounting Method: A Asample Area: 11.5 m2 m2 manual field field <th></th>														
Room with Sample: Temperature: 15.4 °C Humidity: 50 %RH Pressure: 998 Sample Description: Wedge Euphonic Standard Acoustic Tile Pack Mounting Method: A Sample Area: 11.5 m2 The set 9 Tracital Trees 19 Precision Stample Area: 300 Trees 10 Trees 10 Trees 10 Freeder 50° 6.44 5.55 0.11 100 7.26 7.26 5.82 000 6.43 0.72.6 5.82 0.66 0.36 5.90 7.26 1250 7.26 0.64 3.23 0.66 0.87 630 5.56 1.10 1.09 2500 7.26 1.58 2.44 0.93 0.95 1.58 1.44 1.00 1.12 1.00	0	000		0/011					10 5			21/03/20		
Sample Description: Wedge Euphonic Standard Acoustic Tile Pack Mounting Method: A Sample Area: 11.5 m2 Schamber Volume: 300 m3 $\frac{\overline{req}}{160} \frac{1}{11} \frac{1}{12} \frac{1}{12}$														
Mounting Method: A Bample Area: 11.5 m2 Chamber Volume: 300 m3 $\frac{rest 9}{rest 11.5 m2}$ Chamber Volume: 300 m3 $\frac{rest 9}{rest 11.5 m2}$ Chamber Volume: 300 m3 $\frac{rest 9}{rest 11.5 m2}$ Chamber Volume: 300 m3 $\frac{rest 9}{rest 11.5 m2}$ Coeff Coeff Absorption Coefficient 100 7.26 5.82 0.14 100 7.26 5.82 0.14 100 7.26 5.82 0.14 100 6.43 3.23 0.66 0.35 500 5.37 2.64 0.82 0.80 633 5.06 2.49 0.87 1000 5.54 2.51 0.93 0.95 1000 5.54 2.61 0.93 0.95 1000 5.54 2.61 0.93 0.95 1000 5.55 2.46 0.96 1.00 1000 5.55 2.46 0.96 1.00 1000 5.56 2.49 0.87 1000 5.57 2.55 0.11 1.3 1.00 2000 4.59 2.13 1.05 1.00 2000 4.59 2.13 1.05 1.01 2000 4.59 2.13 1.05 1.00 2000 4.59 2.13 1.05 1.00 2000 4.59 2.13 1.05 1.01 2000 4.59 2.13 1.05 1.01 2000 4.59 2.13 1.05 1.00 2000 4.59 2.13 1.05 1.01 2000 4.50 0.50 0.50 0.50 0.50 0.50 0.50 0	8 mbar	isure: 998	Pressure	%RH	50	umidity:								
Chamber Volume: 302 mail Freq T1 Tz Cooff # 50° 4.13 4.40 -0.06 63° 5.45 5.57 -0.02 n/a 80° 6.44 5.55 0.11 - 100 7.26 5.82 0.14 - 125 7.13 5.65 0.16 - 200 6.71 5.14 0.19 - 250 7.26 4.52 0.36 - 500 5.57 2.26 0.84 - 250 7.26 4.52 0.36 - 000 5.54 2.51 0.93 - 1000 5.75 2.54 0.93 - 1000 5.58 2.46 0.96 - 1250 5.58 2.46 0.93 - 1000 5.75 2.54 0.93 - 1000 5.76 1.13 1.05							•		JUSUC 11	andard Ad		A	lethod:	Nounting N
Freq Ti Tz Absorp Practical Absorp 50° 4.13 4.40 -0.06 Absorp Sourd Absorption Coefficient 63° 6.44 5.55 0.11 Image: Control of the state of th											m3	300		in the second se
Freq T1 T2 Coeff Absorp 507 4.13 4.40 -0.06 Coeff # 63° 6.45 5.67 -0.02 n/a 80° 6.44 5.55 0.11 1 100 7.26 5.82 0.14 1 125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 0.9 200 6.71 5.14 0.19 0.8 200 6.71 5.14 0.19 0.8 315 7.13 3.75 0.54 0.82 630 5.66 2.49 0.87 0.83 000 5.54 2.66 0.96 1500 5.10 2.25 1.04 0200 4.59 2.13 1.05 1250 5.58 2.46 0.96 1600 5.10 1.20 0.84 0300 ² 2.11 1.26 1.18 </th <th></th> <th>st 9</th> <th>Te</th> <th></th> <th></th>											st 9	Te		
Hz sec sec Coeff # 50° 4.13 4.40 -0.06 6 80° 6.44 5.55 0.11 1 100 7.26 5.82 0.14 1 125 7.13 5.65 0.11 1 125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 1 200 6.71 5.14 0.19 1 250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 0.96 630 5.06 2.49 0.82 0.80 630 5.56 2.64 0.96 0.6 1250 5.58 2.46 0.96 0.4 2500 4.00 1.98 1.04 2000 4.59 2.13 1.05 1.00 2500 2.67 1.50 1.13 1.00 30000° 1.48														
50° 4.13 4.40 -0.06 n/a 63° 5.45 5.57 -0.02 n/a 80° 6.44 5.55 0.11 1 100 7.26 5.82 0.14 1 125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 0.16 200 6.71 5.14 0.19 0.3 250 7.26 4.52 0.33 0.35 315 7.13 3.75 0.64 0.80 4000 6.43 3.23 0.66 0.87 500 5.54 2.46 0.82 0.80 1250 5.58 2.46 0.96 0.51 1250 5.58 2.46 0.96 0.01 1000 5.75 1.13 1.00 2500 4.00 1.98 1.04 0.20 3150 3.89 1.74 1.12 1.04 0.20 </td <td></td> <td>Coeff</td> <td></td> <td></td> <td></td>											Coeff			
03 0.43 0.57 -0.02 Na 80° 6.44 5.55 0.11 100 7.26 5.82 0.14 125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 0.15 200 6.71 5.14 0.19 0.9 250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 0.80 500 5.37 2.64 0.82 0.80 630 5.06 2.49 0.87 8000 5.54 2.65 0.93 1000 5.75 2.54 0.93 1250 5.58 2.46 0.96 1250 5.58 2.46 0.96 1000 5.70 1.13 1.00 2500 4.00 1.98 1.04 3150 3.89 1.74 1.12 0000* 2.67 1.50			1000								-0.06			
100 7.26 5.82 0.14 125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 200 6.71 5.14 0.19 250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 400 6.43 3.23 0.66 530 5.54 2.64 0.82 0.80 630 5.06 2.49 0.87 0.6 1000 5.75 2.54 0.93 0.95 1250 5.58 2.46 0.96 0.5 1000 5.75 2.54 0.33 0.95 1250 5.58 2.46 0.96 0.4 0.2000 4.59 2.13 1.05 1.00 2500 4.00 1.98 1.04 0.2 0.300 2.11 1.26 1.18 0.2 03000 [*] 1.48 0.98 1.34 0.09 10000 [*] 0.87 0.63 1.34		it	Coefficient	sorption C	Sound Ab					n/a	-0.02	5.57	5.45	63*
100 7.26 5.82 0.14 125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 0.16 200 6.71 5.14 0.19 0.8 250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 0.80 500 5.37 2.64 0.82 0.80 630 5.06 2.49 0.87 0.8 1000 5.75 2.54 0.93 0.95 1250 5.58 2.46 0.96 1000 5.75 2.54 0.93 0.95 1250 5.58 2.46 0.96 0.4 02000 4.59 2.13 1.05 1.00 2500 4.00 1.98 1.04 0.2 3150 3.89 1.74 1.12 0.11 0.1 0000* 2.67 1.50 1.13 1.00 0.1 0.2 0.1 0.2 0000* 0.87 0.63 1.34	-			_		_		.2	1		0.11	5.55	6.44	80*
125 7.13 5.65 0.16 0.15 160 6.70 5.22 0.18 0.16 200 6.71 5.14 0.19 0.87 250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 0.82 400 6.43 3.23 0.66 500 5.57 2.54 0.93 1000 5.75 2.54 0.93 1000 5.75 2.54 0.93 1000 5.75 2.54 0.93 1000 5.75 2.54 0.93 1000 5.75 2.54 0.93 2000 4.59 2.13 1.05 2000 4.59 2.13 1.04 0200 4.59 1.13 1.00 5000 2.11 1.26 1.18 6300° 1.48 0.98 1.20 9000° 0.87 0.63 1.34 Calculated to EN ISO 11654-1997								11						
No. 0.10 0.12 0.10 200 6.71 5.14 0.19 250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 0.9 400 6.43 3.23 0.66 500 5.37 2.64 0.82 0.80 6300 5.06 2.49 0.82 0.80 1000 5.75 2.64 0.93 0.95 1250 5.58 2.46 0.96 0.5 1250 5.58 2.46 0.96 0.4 2000 4.59 2.13 1.05 1.00 2000 4.59 2.13 1.05 1.00 2000 2.67 1.50 1.13 1.00 5000* 2.11 1.26 1.18 0 6300* 1.48 0.98 1.20 0.4 0 9000* 1.74 1.12 1.34 0 125 0.00										0.15				
250 7.26 4.52 0.36 0.35 315 7.13 3.75 0.54 0.6 500 5.37 2.64 0.82 0.80 500 5.37 2.64 0.82 0.6 630 5.06 2.49 0.87 0.6 800 5.54 2.51 0.93 0.6 1000 5.75 2.54 0.93 0.95 1250 5.58 2.46 0.96 0.5 1200 4.59 2.13 1.05 1.00 2000 4.59 2.13 1.05 1.00 2000 2.67 1.50 1.13 1.00 5000 2.11 1.26 1.18 1.00 6300* 1.20 0.84 1.13 n/a 0000 0.87 0.63 1.34 0 Cacu 0.65(MH) Cacuulated to EN ISO 11654:1997			-					1						
315 7.13 3.75 0.54 400 6.43 3.23 0.66 500 5.37 2.64 0.82 630 5.06 2.49 0.87 800 5.54 2.51 0.93 1000 5.75 2.54 0.93 1000 5.76 2.54 0.93 1000 5.76 2.54 0.93 1000 5.76 2.54 0.93 1000 5.76 2.54 0.93 1000 5.76 2.54 0.93 1000 5.76 2.54 0.93 1000 5.76 2.54 0.93 1000 5.01 2.25 1.04 2000 4.59 2.13 1.05 1.30 1.74 1.12 1.05 4000 2.67 1.50 1.13 6300* 1.20 2.64 0.83 8000* 1.20 2.64 0.83 100000* 0.87 0.63 1.34 0.651(MH)	+							.9	C					
1230 3.38 2.48 0.39 1600 5.10 2.25 1.04 2000 4.59 2.13 1.05 2500 4.00 1.98 1.04 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 5000 2.11 1.26 1.18 6300* 1.20 0.84 1.13 n/a 6300* 1.20 0.84 1.33 1 0000* 0.87 0.63 1.34 1 0 0.65 (MH) Class C Eaculated to EN ISO 11654:1997 1								.8	ti o	0.35				
1230 3.38 2.48 0.39 1600 5.10 2.25 1.04 2000 4.59 2.13 1.05 2500 4.00 1.98 1.04 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 5000 2.11 1.26 1.18 6300* 1.20 0.84 1.13 n/a 6300* 1.20 0.84 1.33 1 0000* 0.87 0.63 1.34 1 0 0.65 (MH) Class C Eaculated to EN ISO 11654:1997 1									ficie					
1230 3.30 2.43 0.30 1600 5.10 2.25 1.04 2000 4.59 2.13 1.05 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 5000 2.11 1.26 1.18 6300* 1.20 0.84 1.13 6000* 1.20 0.84 1.13 0000* 0.87 0.63 1.34									leo	0.90				
1230 3.38 2.48 0.39 1600 5.10 2.25 1.04 2000 4.59 2.13 1.05 2500 4.00 1.98 1.04 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 5000 2.11 1.26 1.18 6300* 1.20 0.84 1.13 n/a 6300* 1.20 0.84 1.33 1 0000* 0.87 0.63 1.34 1 0 0.65 (MH) Class C Eaculated to EN ISO 11654:1997 1								.6	5 0	0.80				
1230 3.38 2.48 0.39 1600 5.10 2.25 1.04 2000 4.59 2.13 1.05 2500 4.00 1.98 1.04 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 5000 2.11 1.26 1.18 6300* 1.20 0.84 1.13 n/a 6300* 1.20 0.84 1.33 1 0000* 0.87 0.63 1.34 1 0 0.65 (MH) Class C Eaculated to EN ISO 11654:1997 1								.5	ptio					
1200 5.01 2.25 1.04 2000 4.59 2.13 1.05 1.00 2500 4.00 1.98 1.04 3.33 1.74 1.12 4000 2.67 1.50 1.13 1.00 100 160 250 400 630 1000 1600 2500 315 339 1.74 1.12 1.13 1.00 100 160 250 400 630 1000 1600 2500 315 500 800 125 2000 315 6300* 1.20 0.84 1.13 n/a 100 160 250 800 125 2000 315 6000* 1.20 0.84 1.33 n/a 100 160 250 800 125 2000 315 Class C Calculated to EN ISO 11654:1997								.4	sor	0.95				
1600 5.10 2.25 1.04 2000 4.59 2.13 1.05 1.00 2500 4.00 1.98 1.04 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 1.00 5000 2.11 1.26 1.18 1.00 6300* 1.48 0.98 1.20 8002* 1.30 1.20 8000* 0.87 0.63 1.34 Frequency, Hz Frequency, Hz Class C Calculated to EN ISO 11654:1997 Calculated to EN ISO 11654:1997 Calculated to EN ISO 11654:1997 Calculated to EN ISO 11654:1987 Calculated to EN ISO 11654:1987						1		3	Ab .	0.00				
2000 4.59 2.13 1.05 1.00 2000 4.00 1.98 1.04 3150 3.39 1.74 1.12 4000 2.67 1.50 1.13 1.00 5000 2.11 1.26 1.18 6300* 1.20 0.84 1.13 n/a 10000* 0.87 0.63 1.34								~ B						
2.00 1.00 <t< td=""><td></td><td></td><td></td><td></td><td></td><td>•</td><td></td><td>.2</td><td>C</td><td>1.00</td><td></td><td></td><td></td><td></td></t<>						•		.2	C	1.00				
4000 2.67 1.50 1.13 1.00 5000 2.11 1.26 1.18 1.20 1.20 1.20 2000 315 500 800 1250 2000 315 500 800 1250 2000 315 8000* 1.20 0.84 1.13 n/a 100 160 250 400 630 1000 1600 2500 315 8000* 1.20 0.84 1.13 n/a 100 125 200 315 500 800 1250 2000 315 70000* 0.87 0.63 1.34 100 160 250 100 160 250 100 160 2500 315 0.200 0.65 (MH) Class C Calculated to EN ISO 11654-1997 100 100 160 250 100 110 110 110 110 110 115 110 110 110 110 110 110 110	+ + + +			_				0.1	(1.04	1.98	4.00	2500
5000 2.11 1.26 1.18 6300* 1.48 0.98 1.20 200 315 500 800 1250 2000 315 8000* 1.20 0.84 1.13 n/a Frequency, Hz Frequency, Hz 0000* 0.87 0.63 1.34 Frequency, Hz Frequency, Hz Class C Calculated to EN ISO 11654-1997 Calculated to EN ISO 11654-1997 Frequency, Hz Frequency, Hz				_		_		0						3150
6300* 1.48 0.98 1.20 Frequency, Hz 8000* 1.20 0.84 1.13 n/a 10000* 0.87 0.63 1.34 Image: Class C Calculated to EN ISO 11654:1997	4000									1.00				
8000* 1.20 0.84 1.13 n/a 10000* 0.87 0.63 1.34	150 5000	2000 31	1250 20	0 800	15 500	200 3	125							
10000* 0.87 0.63 1.34			Hz	equency, H	Fre									
Ωω 0.65(MH) Class C Calculated to EN ISO 11654-1997										n/a	-			
Class C Calculated to EN ISO 11654-1997											1.34	0.63	0.87	10000*
NRC 0.80 Calculated to XFM C 423-01 * Denotes frequencies outside the range covered										-01	0.65(M NISO 11654: 0.80 ASTM C 423	CO Class C ulated to Ef RC Iculated to	Calco Calco Ni Ca	
by BS EN ISO 354:2003														201100
T1, empty room reverberation time														
T2, room reverberation time with sample										le				

P:\C22000s - Tech Services\C22750\22766 - Advanced Acoustics\SRL Corr Out\22766 - T01.docx
©SRL Technical Services Limited 11 April 2014 C/22766/T01

Advanced Acoustics is a registered company No. 07049694 - VAT # 980071035 Unit B Maunside, Greenlines Industrial Estate, Mansfield, Nottinghamshire, NG18 5GU