


Advanced Acoustics – SoundSense Isolation System – Wall Version



Overview

The Advanced Acoustics SoundSense Isolation System is a simple, effective, fool-proof and strong high performing sound reduction system designed to isolate walls. The system is simple to install and so installation costs are kept low. It is an effective system as it offers increased performance on traditional resilient bar systems. It is fool-proof because the system comprises of two parts as opposed to multi-part systems making installation even simpler. It is a strong system as it offers superior load bearing capabilities as opposed to some other resilient bar systems.



SoundSense is an acoustic isolation system for walls that completely de-couples the wall lining and so effectively giving a 'room within a room' concept that is often referred to by acoustic consultants. It dramatically reduces both airborne and impact noise transfer between adjacent rooms.

The system has been designed to be flexible, simple and easy to install. It is a 2 part system as opposed to some of the more complex multi-part systems often used where acoustic isolation/de-coupling is required. Designers wanting low-cost, space saving walls that provide superior nose control employ the Advanced Acoustics SoundSense Isolation System.

The SoundSense Isolation System is appropriate for all building types from residential properties to large commercial developments and is equally suited for both new build and refurbishment. It is also suitable for fitting onto timber and metal studs, concrete soffits and timber joists for ceilings.

The two part system consists of SoundSense Isolation Clip and SoundSense Isolation Bar. The damping clips ensure total isolation but also as they are fixed from both sides they ensure a much better load bearing capacity than most standard systems.

Traditional resilient bar systems provide acoustic isolation for plasterboard walls and ceilings by use of a vibration absorbing steel channel which is fixed onto timber studs and onto timber ceiling joists. Typically these systems are fixed along one edge allowing the other free edge to flex and so absorb sound or vibrations. Resilient bars attempt to create an acoustic break between floor joist and the plasterboard ceiling or the timber wall studding and the plasterboard. In order to operate correctly these steel channels need to be highly flexible; if they are rigid they will not dampen the



www.advancedacoustics-uk.com | info@advancedacoustics-uk.com | 01623 643609

vibrations caused by sound. This requirement for flexibility has a direct effect on their load bearing capabilities. Furthermore by being fixed on one side they are not completely isolated from the studwork or joists.

In comparison the SoundSense Isolation Clip is a rubber clip meaning the SoundSense Isolation Bar is not physically attached to the timber studwork, ceiling joists or masonry. This means that isolation is vastly improved. Also because the clip is fixed at the top and the bottom the system can withstand greater loads providing peace of mind for developers and dwellers.

Installation





The SoundSense Isolation system should be fixed at 90° to the wall studding using the SoundSense Isolation Clips. The spacing between channels shall be a maximum of 600mm. The spacing of the clips on the SoundSense Isolation Bar shall be a maximum of 900mm. The required number of clips can be simply slid onto the bar and moved into the required position. The SoundSense Isolation Bars can be cut to length using tin snips or a hacksaw. The bottom row of channel and clips should be a maximum of 75mm to the centre of the channel from the floor. The top row should be a within 150mm of the ceiling. If you are fixing the bar and clips to wood use 60mm coarse thread screws. If you are fixing to steel studs use 42mm self-tapping screws. If you are fixing direct to masonry use 60mm anchors and orientate the bar horizontally. In these images the bars have been fixed directly to the masonry.

Once the isolation bars and clips are securely fixed the next step is to install the first layer of acoustic plasterboard. The first layer of acoustic plasterboard should be 19mm thick and shall align seams between sheets on the centerline of the horizontal channels. Ensure a gap is left around the

linings to decouple the layer. Use the minimum number of


drywall screws to fix the first layer of plasterboard to the bar so as to help avoid hitting screw heads when fixing the second plasterboard layer. Make sure that no fixings connect the plasterboard lining to the joists, studding or masonry. For the first layer we recommend using 32mm self-drilling drywall screws.





www.advancedacoustics-uk.com | info@advancedacoustics-uk.com | 01623 643609







The second layer of plasterboard should be 12.5mm acoustic plasterboard fixed in a brick bond fashion avoiding overlapping joints with the first layer. This board should be fixed at 150mm centers at the board end and 250mm centers in the field. Again the correct length of self-tapping drywall screws should be used to avoid contact with the studwork, joists, concrete or masonry. If you incorporate 1 or 2 layers of Soundproofing Mat you will need to use 42mm screws. If you use using 20mm thick Soundproofing Mat you will need to use 65mm screws.



For the second layer of plasterboard ensure there is a gap left around the linings so the system is completely floating. The perimeter gap can be filled with our flexible acoustic sealant. All potential sound leaks such as gaps around outlets, window or door frames, pipe penetrations and the like are sealed with a flexible, non-hardening acoustic sealant.

NOTE: The SoundSense Isolation Bar and SoundSense Isolation must only be used in conjunction with each other and must not be mixed with another isolation system.



Specification

SoundSense Isolation Clips

Length - 98mm

Width – 25mm

Depth – 28mm

Weight – 59g each

SoundSense Isolation Bar

Length – 2400mm

Width – 65mm

Depth - 22mm

Weight – 380g / Linear Meter

Gauge – 0.5mm

<u>Total System thickness (excluding studding or masonry)</u>

With no Soundproofing Mat – 67mm

With 1 layer of 2mm Soundproofing Mat – 69mm

With 2 layer of 2mm Soundproofing Mat – 71mm

With 1 layer of 20mm Soundproofing Mat – 87mm