


Dimensions of Some Versions
May Vary From Above



FEATURES:

- High Quality and Reliable Switch
- Industry Standard 11mm x 30mm Cutout
- Illuminated and Signal Light Versions
- Multiple Terminal and Actuator Options
- PVC Cap for Dust and Water Protection

SPECIFICATIONS:

RATING: RATING OPTION C:
 15A 125VAC T55 [cULus]
 7.5A 250VAC T55 [cULus]
 16(4)A 250V- 1E4 T125/55 [ENEC]

RATING OPTION D (2 POS. FUNCTIONS):
 20A 125VAC T65 [cULus]
 1/4HP 125VAC T65 [cULus]
 3/4HP 250VAC T65 [cULus]
 20(8)A 250V- 1E4 T125 [ENEC]
 10(2)A 250V- 5E4 T85/55 [ENEC]
 16(4)A 250V- 1E4 T85/55 [ENEC]

RATING OPTION E (3 POS. FUNCTIONS):
 16A 125VAC T65 [cULus]
 16A 250VAC T65 [cULus]
 European Rating Pending

TEMPERATURE: -20°C to 65°C Min.
ELECTRICAL LIFE: 10,000 Cycles
CONTACT RESISTANCE: 35mΩ Max. at 50VAC
INSULATION RESISTANCE: 100MΩ Min. at 500VAC
DIELECTRIC STRENGTH: 1,500VAC for 1 Minute
INGRESS PROTECTION: IP54 with PVC Cap

MATERIALS:

Body: Polyamide 6/6, UL94 V-2
ACTUATOR: Polyamide 6/6, UL94 V-2
 Polycarbonate, UL94 V-2
CONTACTS: Silver Plated Copper