



Suitable For Underfloor Heating



Quick & Easy Installation



Easy Clean



Natural Look & Feel



PU Lacquer Dirt Resistant



R11* Slip Restraint



Clean Indoor Air



V-groove



Diamond Back



15 Year Residential Warranty



23



32

| | |
|----------------------|---|
| Construction | Heterogeneous Sheet Vinyl |
| Width | 2.0m & 4.0m |
| Standard Roll Length | 25m |
| Pattern Repeat | Refer to Vinyl Range Statement |
| Total Weight | 1800g/m ² |
| Wearlayer Thickness | 0.35mm |
| Total Thickness | 2.6mm |
| Backing | Diamond Back |
| Surface Protection | PU / Natural Feel |
| Fire Rating | ISO 9239-1 |
| Slip Resistance | DS-R11* (DIN 51130) |
| Acoustic Insulation | 18dB (ISO 717) |
| Thermal Insulation | 0.25W/mK |
| Underfloor Heating | Suitable |
| Chemicals Resistance | Very Good (EN ISO 26987) |
| Classification | Class 23 Domestic Heavy / Class 32 Commercial Medium |
| Warranty | 15 Year Residential Warranty |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards. |

* on selected items.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.