



Antistatic



Suitable For Underfloor Heating



PU Lacquer Dirt Resistant



100% Recyclable



R10 Slip Restraint



Power Bac Impact Resistant



7 Year Residential Warranty



floor score



Emissions dans l'air intérieur A+



100% Phthalate Free



Class 23 Domestic Heavy



Class 31 Commercial Light

Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 4.0m
Standard Roll Length	±30m
Total Weight	1750g/m ²
Wearlayer Thickness	0.25mm
Total Thickness	2.7mm
Surface Protection	PU Lacquer
Slip Resistance	R10 (DIN 51130)
Electrical Properties	Antistatic
Electrical Propensity	<2kV (EN 1815)
Fire Rating	CRF 8.1kW/m ² (ISO 9239-1)
Acoustic Insulation	ΔLw 18dB (ISO 717/2)
Dimensional Stability	≤0.40% (EN ISO 23999, EN 434)
Curling	≤8mm (EN ISO 23999)
Thermal Insulation	0.11W/m/K (EN 12524)
Indoor Air Quality	FloorScore®
Residual Indentation	≤0.35mm (EN ISO 24343-1, EN 433)
Underfloor Heating	Suitable
Colour Fastness	≥6 (ISO 105 B02)
Chemical Resistance	OK (ISO 26987, EN 423)
Abrasion Group	T (EN 660-2)
Classifications	Class 23 Domestic Heavy / Class 31 Commercial Light
Warranties	7 Year Residential Warranty
Environmental	100% Recyclable, 100% Phthalate Free
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.