



Stain Resistant



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Anti-Allergenic



Castor Chair Compatible



500 x 500mm



15 Year Commercial Warranty

ECONYL®
REGENERATION FOR LIFE

Construction	Structured loop pile
Yarn	100% Recycled Econyl Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Yarn Weight	480g/m ²
Total Weight	4040g/m ²
Pile Height	2.4mm
Total Thickness	5.7mm
Primary Backing	Non-woven PVC free
Secondary Backing	Bitumen reinforced with fiberglass PVC free
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	ISO 9239-1
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	24dB (ISO 140-8)
Acoustic Absorption	α _w 0.15 (ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Thermal Insulation	<0.17% ^{m²C} /W
Underfloor Heating	Suitable
Colour Fastness	5 - 6/8 on Grey Scale (ISO105-B02)
Classification	Class 33 Commercial Heavy
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	Low VOC, 100% Green Electricity, recycled fibre, PVC free ISO 14001, GUT Label, LEED® 100% In face fibre
Installation	Laying recommendation: Monolithic or Quarter Turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.