SAFETY DATA SHEE	Т
-------------------------	---

1.2

1.3

1.4

1.5

1.6

1.7

1.8

1.9

2.1

2.2

2.5

2.6

2.7

HONA Pure Bond

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards SDS Revision: 4.4 SDS Revision Date: 3/7/2023 **1. PRODUCT INDENTIFICATION** 1.1 Product Name: HONA Pure Bond Chemical Name: POLYURETHANE (METH) ACRYLATE PREPOLYMER RESIN BLEND Synonyms: NA Trade Names: none Product Use: PROFESSIONAL USE ONLY Manufacturer's Name: **MCCONNELL LABS, INC.** Manufacturer's Adress: 406 SW UMATILLA AVE, REDMOND, OR 97756 USA Emergency Phone: CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 696869) Business Phone / Fax: +1 541 526 1417 / +1 541 526 1418 2. HAZARD INDENTIFICATION Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as a DANGEROUS GOOD according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H): H224 - Extremely flammable liquid and vapor. H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P243 - Take precaustionary measures against static discharge. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF). Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES 2.3 Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression. EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated expsoure. INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of exposure but odor fatigue may occur. 2.4 Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure. Acute Health Effects: Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: The material may cause an allergic reaction for some sensitive individuals. Target Organs: Eyes, skin

3. COMPOSITION & INGREDIENT INFORMATION														
	EXPOSURE LIMITS IN AIR (mg/m3)													
					AC	GIH		NOHSC	2		OSHA			
					р	om		ppm			ppm			
						1	ES-	ES-	ES-					
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER	
ACETONE	67-64-1	AL3150000	200-662-2	60-100	500	750	250	1000	NF	1000	NA	2500		
	Flamm.Lig.2; Eye li	rrit. 2; STOT SI	E 3, H224, H31	9, H336	-	-	-			-	-			
Isopropylideneiphenyl	1565-94-2	NA	216-367-7	5-40	NA	NA	NF	NF	NF	NA	NA	NA		
bisoxyhydroxypropyl														
methacrylate					-	-	-			-	_			
BIS-HEA POLY(1,4-	73297-27-5	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA		
butanediol)-9/IPDI														
COPOLYMER					-	-	-			-	-			
Isobutyl Methacrylate	97-86-9	NA	202-613-0	0-3	NA	NA	NF	NF	NF	NA	NA	NA		
METHACRYLIC ACID	79-41-4	NA	201-204-4	0-3	150	200	150	200	NF	200	200	1700		
Flammable Liquid 3; Specific Target Organ Toxicity - Single Exposure 3; H226, H336														
HYDROXYCYCLOHEXYL	947-19-3	NA	213-426-9	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
PHENYLKETONE Accute Tox. Oral 5; Aquatic Acute 3; H225, H319, H402														
BIS-Trimethylbenzoyl	162881-26-7	NA	NA	0.1 - 5	NA	NA	NF	NF	NF	NA	NA	NA		
Phenylphosphine Oxide														

4. FIRST AID MEASURES

4.1	First Aid:					
	INGESTION:	If ingested, do not induce vomiting! If product has been swallowed, drink ple vomiting, continue to offer water or milk. Never give water or milk to an un Center or local emergency number. Provide an estimate of the time at whic substance that was swallowed.	conscious person. Contact the n	earest Poison Control		
	SKIN & EYES: INHALATION:	If product gets in the eyes, flush with copious amounts of lukewarm water f ensure thorough irrigation. Seek immediate medical attention. If problem p irritation occurs & product is on the skin, rinse thoroughly with lukewarm w area with plenty of soak and waster. Remove all contaminated clothing incl irritation, redness or swelling persists, consult a physician immediately. Remove victim to fresh air at once. If breathing stops, perform artificial resp	persists, seek immediate medical ater followed by a thorough was uding footwear and wash thorou	attention. If hing of the affected ghly before reuse. If		
4.2	Medical Conditi	ons Aggravated by Exposure:	HEALTH	1		
	Pre-existing der	matitis, other skin conditions and disorders of the target organs (eyes, skin)	FLAMMABILITY	3		
			PHYSICAL HAZARDS	1		
			PROTECTIVE EQUIPMENT	В		
			EYES SKIN			

5. FIREFIGHTING MEASURES

Upper Explosive Limit (UEL): NA

5.1 Flashpoint & Method:

- 20 °C (-4 °F) calculated

5.2 Autoignition Temperature:

NA

5.3 Flammability Limits: 5.4 Fire & Explosion Hazards:

This product is slightly flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)

Lower Explosive Limit (LEL): NA

5.5 Extinguishing Methods:

Water, Foam, CO2, Dry Chemical

5.6 Fire Fighting Procedures:

First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water before returnign to service.

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers shoiuld be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 °C (122 °F).

	8. EXPOSURE CONTROLS & PERSONAL PROTECTION							
8.1	Ventilation & Engineering Controls:	Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate deco	onta 💟 n	İ.				
		equipment is available (e.g., sink, safety shower, eye wash station).		l				
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or		ĺ				
		handling. In instances where vapors or sprays of this product are generated, and		l				
		respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134,		l				
		application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable		l				
		standards of Canadian Provinces, EC Member States or Australia.		l				
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling		ĺ				
		this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses		l				
		pose a special hazard; soft lenses may absorb and concentrate irritants.		l				
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in		ĺ				
		some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]),		l				
		wear nitrile or imprevious gloves.		l				
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., .		ĺ				
		1 gallon), eye wash stations and deluge showers should be available. Upon completion of		l				
		work activities involving large quantities of this product, wash any exposed areas						
		thoroughly with soap and water.						
P				•				

	9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	0.9				
9.2	Boiling Point:	57 °C (134 °F)				
9.3	Melting Point:	ND				
9.4	Evaporation Rate:	NA				
9.5	Vapor Pressure:	30.6 kPa @ 25°C				
9.6	Appearance & Color:	Clear liquid				
9.7	Odor Threashold:	NE				
9.8	Solubility:	Not soluble				
9.9	pH:	NA				
9.1	Viscosity:	approximately 300 cps				
9.11	Flash Point:	- 20 °C (-4 °F) calculated				
9.12	Other Information:	NA				

10. STABILITY & REACTIVITY

10.1	Stability:
	Relatively stable under ambient conditions when stored properly.
10.2	Hazardous Decomposition Products:
	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon
	and nitrogen).
10.3	Hazardous Polymerization:
	Will not occur.
10.4	Conditions to Avoid:
	Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.
10.5	Incompatable Substances:
	Strong oxidizers, peroxides, strong acids or alkalis.

11. TOXICOLOGICAL INFORMATION 11.1 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the produt which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity: See Section 2.5 11.3 Chronic Toxicity: See Section 2.6 11.4 Suspected Carcinogen: The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internail Agency for Research on Cancer or the American Conference of Government Industrial Hygenists. 11.5 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This products is not reported to cause teratogenic effects in humans. 11.6 Irritancy of Product: See Section 2.3 11.7 Biological Exposure Indicies: NE 11.8 Physician Recommendations: Treat syptomatically **12. ECOLOGICAL INFORMATION** 12.1 Environmental Stability: This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Butyl Acetate: K_{oc} = 1.82. Water Solubility: 120 parts H₂O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegredation. This compound's half life is 6.1 hours. 12.2 Effects on Plants & Animals: There is no specific data availble for this product on plant life. 12.3 Effects on Aquatic Life: There is no specific data availble for this product on aquatic life. **13. DISPOSAL CONSIDERATIONS** 13.1 Waste Disposal: Dispose inaccordance with local, state and Federal waste laws. 13.2 Special Considerations:

This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations.

	14. TRANSPORTATION INFORMATION		6 of 8
The b	asic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportat	$\langle \rangle$	
	ptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.	\checkmark	
	49 CFR (GRD):		-
	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) - UNTIL 12/31/2020	1	
	UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 0.5 L)		
14.2	IATA (AIR):	FLAMMABLE LIQUID	
	Ú ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L)	3	
	UN 1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 5.0 L)		
14.3	IMDG (OCN):		
	UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 5.0 L)		
14.4	TDGR (Canadian GND):		
	MARK PACKAGE "LIMITED QUANTITY" OR "QUANTITE LIMUTEE" OR "LTD QTY" OR "QUANT LTEE" (IP VOL ≤ 5.0 L)	•	
	UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 5.0 L)		
14.5	ADR/RID (EU):		
	UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 5.0 L)		
14.6	MEXICO (SCT):		
	UN1263 PINTURA, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 5.0 L)		
14.7	ADGR (AUS):		
	UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 5.0 L)		
			
	15. REGULATORY INFORMATION		
15.1	SARA Reporting:		
	NA		
15.2	SARA Threshold Planning Quantity:		
	NA		
15.3	TSCA Inventory Status:		
	All components of this product are listed in the TSCA Inventory or are exempt		
15.4	CERCLA Reportable Quantity (RQ):		
	BUTYL ACETATE: 5,0000 lbs (2,270 kg)		
15.5	Other Federal Requirements:		
	This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).		
15.6	Other Canadian Regulations:		
	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required		
	by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are on the		
	Priorities Substances List.		
15.7	State Regulatory Information:		
	Butyl Acetate is listed on the following state criteria list(s): Deleware Air Quality Management List (DE), Massachusetts Hazardou	s Substan	
	(MA), Minnesota Hazardous Substances List (MN), New Jersery Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), and	d Washington	
	Permissible Exposure Limits for Air Contaminants (WA).		
	No other ingredients in this producd, present in a concentration of 1.0% or greater, are listed on any of the following state criteri	a lists: California	
	Proposition 65 (CA), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Sub	stances List (MA),	,
	Michigan Critical Substances List (MI), Minnesota Hazardous Substances list, (MN), New Jersey Right-to-Know List (NJ), new Yord	Hazardous	
	Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Su	bstances List (WI)	
15.8	67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:		
	The primary cononents of this product are not listed in Annex 1 of EU Directive 67/548/EEC.		
	Butyl Acetate: Flammable (F). Harmful (Xi).		
	Risk Phrases (R): 11-36/37/38 - Highly Flammable. Irritating to eyes, skin and respiratory system. Safety Phrases (S): 2-23-29 -		
	Keep out of reach of Children. Do not breath gas, fumes, vapor or spray. Do not empty into drains. Keep away from sources of		
	ignition - No Smoking. Avoid contact with skin and eyes, rinse immediately with plenty of water and seek medical advice.		

16. OTHER INFORMATION

	16. OTHER INFORMATION						
-	16.1 Other Information:						
		TON. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective					
	gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally.						
	Keep away from heat and open flame. KEEP OUT						
16.2	Terms & Definitions:		Ì				
	Please see last page of this SDS.		1				
16.3	Disclaimer:						
	This Safety Data Sheet (SDS) is offered persuant to	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governement regulations must					
	be reviewed for applicability to this product. To the	e best of McConnell Labs' knowledge, the information contained herein is reliable and accurate as of					
	the date it was prepared; however, accuracy, suital	bility or completeness are not guaranteed and no warranties of any type, either expressed or					
	implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all						
	component properties must be considered. Data may be changed from time to time. Be sure to sonsult the latest edition.						
16.4	Prepared for:		ł				
	Home of Nail Art (HONA)						
	13614125, Wednesbury Street						
	Newport, NP190FG, Wales						