

AXIAL FANS

X-47ATR and X-48ATR

XPOWER's top-of-the-line axial fans feature powerful ventilation airflow up to 3600 CFM. Durable, lightweight, stackable ABS housing ensures easy transport and storage. Both units have a daisy chain function with circuit breaker. Ducting hose and adapter kit are available for confined spaces as well as for restoration jobs.

X-48ATR is a high temperature capable fan designed to withstand room temperatures up to 180° F for pest control applications such as bed bug extermination.

- Sealed motor for restoration applications
- Variable speed control
- Special grille design extends air to 60'
- High torque motor with low power draw
- 360° rotation for focused airflow





X-41ATR and X-42ATR

The X-41ATR and X-42ATR produce a maximum 3600 CFM using only 2.4A of power. Durable, lightweight, stackable ABS housing ensures easy transport and storage. Both units have a daisy chain function with circuit breaker. A ducting hose and adapter kit are available for confined space ventilation as we as other restoration uses.

X-42ATR is a high temperature capable fan designed to withstand room temperatures up to 180 F for pest control applications such as bed bug extermination.

- External rotor induction motor
- Variable speed control
- · Special grille design extends air to 60'
- · High torque motor with low 2.3a power draw
- · 360° rotation for focused airflow

X-34AR, X-34TR, X-34ASR & X-35AR

The X-34 and X-35 series compact axial fans are energy efficient, using only 1.6 AMP draw, yet producing up to 1700 CFM. Motors are sealed for the professional water damage industry. Unique variable speed control feature allows precise airflow control, while a special grille design extends the focused airflow up to 60 ft. The stand allows 360° fan rotation for multiple drying positons. The durable lightweight, stackable ABS (X-34) or PC (X-35) housing ensures easy transport and storage.

X-35AR is a high temperature capable fan designed specifically to withstand room temperature up to 180°F for pest control applications, such as bed bug extermination.

- · Sealed motors
- Variable Speed
- Low power draw
- 360° rotation for focused airflow
- · Lightweight and stackable for easy transport

Intertek

XPOWER MANUFACTURE, INC. • 220 CLARY AVENUE, SAN GABRIEL, CA 91776 • www.XPOWER.com PHONE: (626) 285-3301 • FAX: (626) 285-3302 • EMAIL: info@XPOWER.com

SPECIFICATIONS

| Model No | X-34AR | X-34ASR | X-34TR | X-35AR | X-41ATR | X-42ATR (High Temp) | X-47ATR | X-48ATR (High Temp) |
|-------------------------|------------------|------------------|------------------|------------------|-------------------|---------------------|-------------------|---------------------|
| Volts/Hertz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz |
| Motor | 1/4HP | 1/4HP | 1/4HP | 1/4HP | 1/3HP | 1/3HP | 1/3HP | 1/3HP |
| Power | 1.6A | 1.6A | 1.6A | 1.6A | 2.4A | 2.4A | 2.8A | 2.4A |
| Rated Airflow | 1720 CFM | 1720 CFM | 1720 CFM | 1720 CFM | 3600 CFM | 3600 CFM | 3600 CFM | 3600 CFM |
| Speeds | Variable | Variable | Variable | Variable | Variable | Variable | Variable | Variable |
| Cord Length | 10' / 18AWG | 10' / 18AWG | 10' / 18AWG | 10' / 18AWG | 20' / 14AWG | 20' / 14AWG | 20' / 14AWG | 20' / 14AWG |
| | 360° Rotation | 360° Rotation | 360° Rotation | 360° Rotation |
| Operating Position | 10" Height | 10" Height | 10" Height | 10" Height | 12.5" Height | 12.5" Height | 12.5" Height | 12.5" Height |
| | Rack Included) | Rack Included) | Rack Included) | Rack Included) |
| Daisy Chain | 1 | 1 | 1 | ✓ | 1 | ✓ | √ | ✓ |
| 3 Hour Timer | | | 1 | | √ | ✓ | ✓ | ✓ |
| Stackable | 1 | 1 | 1 | 1 | ✓ | ✓ | ✓ | ✓ |
| Unit Weight | 15.3lbs | 17.8lbs | 15.3lbs | 17.1lbs | 24.2lbs. | 25.2lbs | 22.2lbs | 26.6lbs |
| Unit Dimensions (LxWxH) | 18.6"x9.4"x19.2" | 18.6"x9.4"x19.2" | 18.6"x9.4"x19.2" | 18.6"x9.4"x19.2" | 21.9"x9.8"x22.5" | 21.9"x9.8"x22.5" | 21.9"X9.8"X22.5" | 21.9"x9.8"x22.5" |
| Box Weight | 20.2lbs | 21.7lbs | 19.4lbs | 20.2lbs | 31.5lbs | 31.2lbs | 28.7lbs | 31.6lbs |
| Box Dimensions (LxWxH) | 19.7"x17.7"x10" | 19.7"x17.7"x10" | 19.7"x17.7"x10" | 19.7"x17.7"x10" | 22.6"x23.2"x11.4" | 22.6"x23.2"x11.4" | 22.6"X23.2"X11.4" | 22.6"x23.2"x11.4" |
| Housing | ABS | ABS | ABS | ABS + PC | ABS | ABS + PC | ABS | ABS + PC |
| Safety Certification | ETL/CETL | ETL/CETL | ETL/CETL | ETL/CETL | ETL/CETL | ETL/CETL | ETL/CETL | ETL/CETL |
| Dual Thermal Protection | 1 | 1 | ✓ | 1 | 1 | ✓ | ✓ | 1 |
| Pallet Qty | 32 Units | 32 Units | 32 Units | 32 Units | 28 Units | 28 Units | 28 Units | 28 Units |

ACCESSORIES

| Ducting Hose (Sold Separately) | N/A | N/A | N/A | N/A | 16DH25 / 16DH15 - Yellow Polyester Ducting Hose Available in 25' & 15'x16" Ø Inside Diameter |
|--------------------------------|-----|-----|-----|-----|---|
| Adapter Kit (Sold Separately) | N/A | N/A | N/A | N/A | 16DHK - Adapter Kit that Connects Ducting Hose to Axial Fan |

Auxiliary Outlet with Circuit Breaker for Daisy Chain



External Rotor Induction Motor for Larger Torque That Produce High Efficient, Powerful & Quiet Airflow

Specially Designed Air Fin Guide for More Focused & Extended Airflow Range Up to 60 ft.

> Stand-Alone Design with Rubber Footing that Works Even without Rack





3-Hour Timer & Variable Speed Control Switch

Durable & ABS (X-41ATR) + PC (X-42ATR) Housing Design

Quick Release Knob for Easy Angle Adjustment

Wrap Around Cord Design

Fully Installed Rack / Stand Allowing 360° Angle Rotation



Adapter Kit (For X-41ATR & X-42ATR Only)



Stackable

Daisy Chain



Ducting Hose (For X-41ATR & X-42ATR Only)