

Wireless Keypad
KPW250
KPW5



KPW250

KPW5

The Best Wireless Keypads. Period.

Sleek, wireless design. Simple installation. Reliable performance. Built to deliver unbeatable operation in tough environments, LiftMaster®'s **KPW250** and **KPW5** are the ideal wireless security keypads for programming to one LiftMaster Gate Operator or Commercial Door Operator.

LiftMaster®

KPW250 and KPW5: Unrivalled Advantages for Easy Access

Universal Features:



KPW250

KPW5

Constant Pressure Override provides a simple, keypad-based method to manually operate a gate securely and safely until a service technician arrives*

Easy wireless installation saves time and the cost of running wires

Security+ 2.0® Technology virtually eliminates interference and offers extended range when the keypad is used to communicate with LiftMaster® Gate and Commercial Door Operators

Fully sealed electronics meet NEMA 4X water protection requirements and withstand tough outdoor environments

9V lithium battery provides extended life in harsh temperatures

10 unique temporary PINs can be set for 1-9 uses each

Easy single PIN removal while maintaining full access for other users

Ideal for solar or remote location applications

KPW250 UNIQUE FEATURES

- Programs to all LiftMaster Gate and Commercial Door Operators
 - LiftMaster Security+ 2.0
 - Security+® 315 MHz and 390 MHz
 - Linear® Multi-Code® 300 MHz
- Provides constant pressure override to open or close the gate when needed*
- Enables flexible setup for multiple users with 250 permanent PINs and 10 unique temporary PINs
- Withstands harsh environments with a zinc-alloy metal front cover

KPW5 UNIQUE FEATURES

- 5 permanent PINs and 10 unique temporary PINs make it ideal for residential gates
- Provides constant pressure override to open or close the gate when needed*
- Compatible with LiftMaster Security+ 2.0
- High-impact polycarbonate front cover is perfect for residential gate access

ADDITIONAL APPLICATIONS

Use alone or with Universal Receiver (850LM/860LM)
for expanded functionality



Commercial Door Operators



Community Pool Gates
Requires Universal Receiver



Entrances with Electronic Locks
Requires Universal Receiver



Small, Gated Cul-de-Sacs



Backup Access at Gate House

ADD TO YOUR SYSTEM



Gooseneck Pedestal
(PED42)

42 in. pad-mount pedestal, 2 x 2 in. square pipe with a black powder-coated finish, 11-gauge steel.



Gooseneck Pedestal
(PED64)

64 in. in-ground mount pedestal, 2 x 2 in. square pipe with a black powder-coated finish, 11-gauge steel.





Universal Receiver
(850LM/860LM)

Security+ 2.0® Technology virtually eliminates radio interference. 3 channels for expanded capacity can store up to 90 remote controls. Compatible with most gate and commercial door operators. 860LM has weather-tight enclosure.

Wireless Keypad

KPW250

KPW5

		
FEATURE	KPW250	KPW5
Code and Radio Frequency	<ul style="list-style-type: none"> LiftMaster® Security+ 2.0® (default) <ul style="list-style-type: none"> – Delivered on tri-band 310/315/390 MHz LiftMaster Security+® 315 MHz LiftMaster Security+ 390 MHz Linear® Multi-Code® 300 MHz 	<ul style="list-style-type: none"> LiftMaster Security+ 2.0 <ul style="list-style-type: none"> – Delivered on tri-band 310/315/390 MHz
PIN Capacity	<ul style="list-style-type: none"> Up to 250 permanent 4-digit PINs Up to 10 unique temporary PINs 	<ul style="list-style-type: none"> Up to 5 permanent 4-digit PINs Up to 10 unique temporary PINs
Power	9V lithium battery with battery life up to 5 years (based on 25 activations per day)	
Operating Temperature	–4°F to 140°F (–20°C to 60°C)	
Storage and Shipping Temperature Range	–40°F to 140°F (–40°C to 60°C)	
Operating Humidity	5% to 95% (non-condensing)	
Weatherization	Electronics meet NEMA 4X water protection requirements; housings meet or exceed NEMA 3R	
Enclosure	Zinc-alloy metal front cover; high-impact polycarbonate back housing	High-impact polycarbonate front cover and back housing
Lockable Housing	Restricts access to the reset button	
Memory	Non-volatile (codes are saved when battery is replaced)	
Mounting	Compatible for surface mount or standard pedestal mount (4 x 4 in.)	
Operating Range	Up to 500 ft. (open field)	
Dimensions	4.3" W x 6" H x 1.75" D	
Shipping Weight	1.2 lbs.	0.73 lbs.
Warranty	1 Year limited	



Learn more at LiftMaster.com/AccessControl

Sales Support: 800.282.6225

Technical Support Center: 800.528.2806

LiftMasterDealer.CustHelp.com/App/Ask

© 2016 LiftMaster All Rights Reserved
 845 Larch Ave., Elmhurst, IL 60126
LiftMaster.com
 Multi-Code is a registered trademark
 of Nortek Security & Control LLC.
 LMTEBROKPW 8/16

CGI IS AN ISO9001 REGISTERED COMPANY



IC/FCC
 Certified

CGI reserves the right to make design or specification changes without notice.

LiftMaster®