

# SL3000UL AC HIGH-TRAFFIC COMMERCIAL SLIDE GATE OPERATOR

The first choice for heavy-traffic applications.



**PRODUCT HIGHLIGHT**  
CONTINUOUS-DUTY,  
High-Temperature Motor

## RELIABLE

**LEGACY ELITE HEAVY-DUTY COMMERCIAL GEAR-DRIVEN TRANSMISSION** PROVIDES UNSURPASSED RELIABILITY.

**LIMIT SWITCH DESIGN** PROVIDES PRECISION LIMIT ACCURACY AND RELIABILITY.

**SURGE SUPPRESSION** PROVIDES INDUSTRIAL SURGE AND LIGHTNING PROTECTION AGAINST STRIKES UP TO 50 FEET AWAY.

**WARRANTY** 5 YEARS COMMERCIAL, 7 YEARS RESIDENTIAL.

## SMART

**myQ® TECHNOLOGY** ENABLES YOU TO SECURELY CONTROL AND MONITOR YOUR GATE OPERATOR FROM ANYWHERE.\*

**WIRELESS DUAL-GATE COMMUNICATION** SYNCHRONIZES GATE OPENING/CLOSING AND ELIMINATES EXPENSIVE DRIVEWAY TRENCHING COSTS.

## SAFE AND SECURE

**SECURITY+ 2.0®** SAFEGUARDS ACCESS WITH AN ENCRYPTED TRI-BAND SIGNAL TO VIRTUALLY ELIMINATE INTERFERENCE AND OFFER EXTENDED RANGE.

**INHERENT REVERSING SENSOR** DETECTS OBSTRUCTIONS AND REVERSES GATE WHEN CLOSING OR STOPS/REVERSES THE GATE WHEN OPENING.

**PRE-MOTION WARNING ALARM** ACTIVATES ON-BOARD ALARM 3 SECONDS PRIOR TO GATE MOTION.

**MANUAL DISCONNECT** WHEN UNLOCKED ALLOWS GATE TO BE OPERATED MANUALLY.

**QUICK CLOSE AND ANTI-TAILGATE** QUICKLY SECURE PROPERTY, PREVENTING UNAUTHORIZED ACCESS.

**UL® LISTED** GATE OPERATORS WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICES.

\*Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

## INCLUDED ACCESSORIES:

**MONITORED RETRO-REFLECTIVE PHOTO EYE**  
Enhanced retro-reflective photo eye now with heater and wider beam, engineered to stay aligned; max. range: 50 ft.



LMRRUL

**MONITORED SMALL PROFILE RESISTIVE EDGE**  
Pressure-sensitive edge stops and/or reverses gate when obstructed.



S505AL

## SAFETY ADD-ONS:

**MONITORED THROUGH-BEAM PHOTO EYES**  
Enhanced through-beam now with wider beam and heater for high performance in most environments; max. range: 90 ft.



LMTBUL

**MONITORED WIRELESS EDGE KIT**  
Low-energy Bluetooth® connection between a LiftMaster Monitored Resistive Edge and the gate operator; max. range: 130 ft.\*\*



LMWEKITU

**MONITORED SAFETY ENTRAPMENT EDGES**  
Full line of Small, Large and Wraparound Profile Edges that sense obstructions.



EDGES

## TOTAL SOLUTION ACCESSORIES:

**TELEPHONE ENTRY FOR COMMERCIAL APPLICATIONS AND GATED COMMUNITIES**  
Mid-capacity telephone entry access control system with Versa XS 4.0 software.



EL2000SS

**PLUG-IN LOOP DETECTOR**  
Prevents the gate from closing on a vehicle in the path; power efficient for maximum cycles on Battery Backup.



LOOPDETLM

\*\*Wireless kit for up to 4 transmitters and 2 resistive edges per transmitter.

# MASTERFUL ENGINEERING.

## MECHANICS



- **Continuous-Duty Motor with Class H Insulation** Is Rated for High-Cycle, High-Temperature Applications (Available in 1/2 and 1 HP)
- **Operator Duty Rating:** Continuous Duty
- **Wormgear Reduction:** Commercial Oil-Bath Gearbox Providing 30:1 Wormgear Reduction
- **Chain:** #41 Black Oxide (25 ft. Supplied)

## POWER



- **115V** Single-Phase
- **Accessory Power:** 24VDC 500mA Output
- 2 Auxiliary Outlets
- Optional Kit (3PHCONV) to Convert an Input Voltage of 208/240/480/575VAC to an Output Voltage of 115VAC

## COMMERCIAL-GRADE DESIGN



- **Chassis:** Constructed with 1/4 in. Gold Zinc-Plated Steel for Rust Prevention
- **Cover:** High-Density, UV-Resistant, 1-Piece Polyethylene Plastic for Excellent Heat and Corrosion Resistance
- **UL® Usage Classification:** I, II, III and IV
- **Operator Weight:** 140 lbs.




26.51"

18.14"

20.39"

[SL3000101UL AND SL3000501UL HAVE THE SAME DIMENSIONS]

## CAPACITIES



## TEMPERATURE SPECIFICATIONS



### WITHOUT HEATER

-4°F (-20°C) to 140°F (60°C)

### WITH OPTIONAL HEATER (HTRNB)

-40°F (-40°C) to 140°F (60°C)

## GATE TRAVEL SPEED

12" per second

## STANDARD FEATURES.

### EXTERNAL ALARM RESET BUTTON

- Instantly Resets the Built-In Safety Alarm Siren

### MECHANICAL LIMIT SYSTEM

- Maintains Accurate Gate Position Throughout Gate Travel, Even After Using Manual Disconnect

### MONITORED SAFETY INPUTS

- 3 Main Board, 3 Expansion Board

### SECURITY+ 2.0® ON-BOARD

#### RADIO RECEIVER

- Tri-Band 310/315/390 MHz Frequency
- Up to 50 Remote Controls (Unlimited with 811LM/813LM)

### LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

### PROGRAMMABLE AUXILIARY RELAYS

- Make Adding Additional Features Easy

### HOMELINK® COMPATIBLE

- Version 4.0 or Higher\*

## SUPPORT.



For Support Tools and Training Videos, Visit [LiftMasterTraining.com](http://LiftMasterTraining.com)

For More Information on Gate Operators, Visit [LiftMaster.com/UL325Gates](http://LiftMaster.com/UL325Gates)

To Find the Right Perimeter Access Solution for You, Visit [LiftMaster.com/Solution-Generator](http://LiftMaster.com/Solution-Generator)



Sales Support: 800.282.6225

Technical Support Center: 800.528.2806

To Order: 800.323.2276



\*May require an external adapter depending on the model and year of your vehicle. Visit [HomeLink.com](http://HomeLink.com) for additional information.