

# TITAN Linear Actuator

Elegant, modular design meets quiet operation

Quiet, powerful, and field-repairable with multiple controller and power options.

## Features:



### Powerful:

Move gate leaf up to 1,000 lbs and 20 ft



### Design:

Superior arm design keeps out dust and snow



### Easy maintenance:

Modular, field replaceable components for easy maintenance



### Noise reduction:

Soft-start and soft-stop for smooth gate operation



### Convenience:

Easy access to limit switch adjustment



### Protected:

Locking manual release prevents unauthorized access and allows operation during power outage



### Gate types:

Single or dual gate applications



### Technology:

Nice BlueBUS 2-wire system self-identifies monitored photo eyes

# TITAN Linear Actuator

## Residential, Farm, Ranch Applications



powered by  
**936, 1050**

### Technical Specifications

Model	TITAN12L	TITAN12L1	TITANKIT 12L1
<b>Operator Kit</b>	Single: CBOX936 and 912L-1 Twin: CBOX936, 912L-1 and 912L-2	Single: CBOX1050 and 912L-1 Twin: CBOX1050, 912L-1 and 912L-2	Single: CBOX1050 or MB1050, and 912L-1 Dual: CBOX1050 or MB1050, 912L-1 and 912L-2
<b>Duty Cycle</b>	Continuous for AC; Varies based on solar charging capacity*		
<b>Drive</b>	Electromechanical		
<b>Gate Weight/Length Max</b>	up to 600 lb for a 20 ft leaf (272 kg for 6 m) up to 1000 lb for a 8 ft leaf (453 kg for 2.4 m)		
<b>Open/Close Time (to 90°)</b>	14 - 16 seconds Slowdown positions adjustable	14 - 16 seconds Open/Close speed set independently	
<b>Temperature Rating</b>	-4° TO 122° F (-20° TO 50° C)		
<b>Operating Voltage</b>	12VDC		
<b>Input Voltage</b>	12VDC	12VDC or 24VDC	
<b>Idle Current</b>	17mA		
<b>Accessory Power</b>	Regulated 12V/24V - 300mA (1 location each) Fused power - 3A (3 locations)	V+/24V/12V, 0.3A each location	
<b>Included Accessories</b>	OXIBD bi-directional receiver, one set of BlueBUS through beam photo eyes, Pivot Bolt	OXIBD bi-directional receiver, one set of EMX reflective photo eyes, Era One 2 Channel Mono Transmitter, Pivot Bolt	
<b>Communication</b>	BlueBUS, BUST4, USB port, OXI	BlueBUS, BUST4, OXI	
<b>User Controls</b>	936US Controller	1050US Controller	
<b>Relays</b>	2 non-programmable relays	3 programmable relays	
<b>Actuator Dimensions</b>	Total Length: 42.5 retracted - 69.3 extended inches (108 - 176 cm) Pin-to-Pin: 40.5 retracted - 67.3 extended inches (103 - 171 cm)		
<b>Enclosure</b>	CBOX: 18w x 18h x 8d inch (46w x 46h x 20.3d cm)	CBOX: 18w x 18h x 8d inch (46w x 46h x 20.3d cm) MB1050: 14.25w x 15.125h x 9d inch (36.2w x 38.4h x 22.9d cm)	
<b>Finish</b>	CBOX: Black powder coat steel		CBOX: Black powder coat steel MB1050: Black plastic
<b>ETL Listed (UL 325)</b>	Usage Class I, II		
<b>Warranty</b>	3 year w/product registration		

\* Actual battery backed up cycles will depend on gate resistance to travel, cycle length, battery health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.

Note: Battery required but not included for solar models.

### Optional Accessories - See website for complete list



EPMB/A  
EPMOB/A  
EPLOB/A  
Photo Eye Kits



EDSWG  
Keypad



Oview  
Programmer



Inti 2-Channel  
Transmitter



Era One  
2 or 4 Channel  
Transmitter



Solar Panels



Battery Charger



ASO Edge Sensors

Contact Nice for an operator/parts distributor near you.  
phone 253-867-3700 | 800-321-9947  
hysecurity.com | sales@hysecurity.com

Nice



D0813 101420