

## INCLUDED COMPONENTS:

- Lens Station IOLS-RF
- Instruction Manual
- USB Cable
- Canon RF Mount Body Cap

## PRODUCT SPECIFICATIONS

- Interface: USB 2.0 / Bus Power (5.0V±5% / 500mA)
- Diameter x Height: 3.07" x 0.99" (78.1mm x 25mm)
- Weight: 2.3oz (64.2g)
- Operating Environment: Temperature 32°F ~ 104°F (0°C ~ 40°C) Humidity : 30~70% (No Condensation)

**ROKINON®**

Toll Free: 800.441.1100  
Phone: 212.947.7100  
support@rokinon.com

ROKINON® is owned and operated solely by Elite Brands Inc.  
©2020, Elite Brands Inc., ROKINON Division, New York, NY 10005  
rokinon.com  
facebook.com/rokinonlenses

**The product exterior, specifications, and contents of this manual are subject to change without notice.**

FC CE RCM

Class B equipment: Korean Class B ITE  
This equipment has been registered with  
electromagnetic compatibility for household  
purposes and can be used in residential areas.

Thank you for purchasing the ROKINON Lens Station model IOLS-RF designed exclusively for ROKINON AF Canon RF Mount lenses. It allows you to connect ROKINON AF Canon RF Mount lenses to your computer to update firmware, calibrate, and customize focus, and aperture parameters with the use of ROKINON Lens Manager Software.

## CAUTIONS

**To prevent damage please fully familiarize yourself with the following:**

- Only ROKINON AF Canon RF Mount lenses should be connected to a Rokinon IOLS-RF Lens Station.
- Do not connect any other ROKINON lens types, mount types or lens brands.
- The Lens Station is not compatible with any mount adapters.
- When attaching the Lens Station, position the front of the lens face down with lens cap on (mount facing up) on a stable surface.
- In the case of a large lens, please carefully position and hold it in a manner that will prevent it from falling over.
- Only use the supplied USB cable. Using a different cable can cause problems.

## USER GUIDE

### 1) Install the ROKINON Lens Manger Instruction Manual and Software onto your computer.

- Please go to [rokinon.com/downloads](http://rokinon.com/downloads) and click on “Lens Station Software”.
- Depending on the operating system of your computer click on and download either “Lens Manager for Windows” or “Lens Manager for Mac”.

### Lens Manager System recommendations:

**Windows:** Windows 7 or above • 1+ GB RAM • 1+ GB HDD space • 1024 x 768 or higher resolution • USB 2.0 Port

**Mac:** Mac OS X Ver.10.10 or above • 1+ GB RAM • 1+ GB HDD space • 1024 x 768 or higher resolution • USB 2.0 Port

### 2) Attach the lens.

- Remove the Lens Station's body cap.
- Remove the rear lens cap of your ROKINON AF Canon RF lens.
- Position the lens with its front lens cap on and its front facing down (mount facing up) on a stable surface.
- Align the white index mark (dot) on the lens with the red index mark (dot) of the Lens Station.
- Do not press the lens release button on the Lens Station when mounting the lens.
- Rotate the lens station in the direction labeled “close” on the rear of the Lens Station until it “clicks” and locks in place.

### 3) Connect the Lens Station to your computer.

- Use the supplied USB cable to connect the Lens Station.
- Read and familiarize yourself with the Instruction Manual.
- Start Lens Manager and update the firmware or customize the features of your ROKINON AF Canon RF lens.
- Close Lens Manager when completed.

### 4) Detach the lens.

- Remove the USB cable from the Lens Station.
- While holding down the lens release button on the Lens Station, rotate the Lens Station in the direction labeled “open” on the rear of the Lens Station until it stops. Separate the Lens Station from the lens.
- Attach the rear lens cap of your ROKINON AF Canon RF lens.
- Attach the Lens Station's body cap.

## PARTS

