



85mm F1.4 II Auto Focus SONY E MOUNT Instruction Manual

Thank you for purchasing the Rokinon AF 85mm F1.4 Series II Full Frame Telephoto Prime Lens. This lens is specifically designed to provide optimal image and video quality on Full Frame and APS-C Sony E mount cameras.

Before Using

- Please read this instruction manual and familiarize yourself with the functions of the lens, the operating method, and cautions for handling the product correctly prior to use. Also, refer to the instruction manual of the camera you are using with the lens.
- The supported functions of this product may vary by the camera model.
- For detailed information regarding compatibility, visit www.rokinon.com

Cautions

To maintain your safety and prevent damage to the lens, please fully familiarize yourself with the following:

- Do not look at the sun or other strong light through the lens or camera. Doing so may cause blindness.
- Do not store the lens without a lens cap in a location with direct sunlight, such as inside a vehicle. Direct sunlight passing through the lens may be concentrated, causing a fire.
- Keep the lens out of the reach of children. Failure to do so may cause an accident or personal injury.
- In order to use the lens safely, attach or detach the lens while the camera is turned off.
- Be careful not to touch or contaminate the contact point on the mount. If electronic signals are not transmitted between the camera and the lens smoothly, a malfunction may occur.
- Do not apply excessive force to the lens when attached to the camera. Doing so may cause damage to the lens and/or camera mounts.
- It is recommended to use a strong tripod. If a weak tripod is used, the tripod may fall, damaging the camera and/or the lens.
- If the lens is placed in a hot location, damage or distortion may occur, resulting in performance problems.

- Avoid using the lens in a location with drastic temperature changes. In particular, if you move a lens that has been chilled in a cold location to a warm location, moisture in the air may be concentrated outside or inside the lens, causing a failure or the production of mold. In such a case, keep the lens in a plastic bag or an exclusive camera bag and take it out when the temperature of the lens becomes similar to the peripheral temperature.

- If the lens is wet or if you use the lens with wet hands, product failure, fire, or electric shock may occur.

- Avoid direct sunlight, and do not store the lens near naphthalene or mothballs.

- Take care not to get the lens wet with water or other liquids, and store the lens in a dry place with ventilation.

Cleaning

- Before cleaning, it is extremely important to dust off the lens surface using a lens blower or a soft brush to remove any foreign particles or grit that could scratch the lens.

- For stubborn spots, use only one or two small drops of a reputable lens cleaner on a microfiber cloth, and gently wipe the lens in a circular motion.

DO NOT USE AN ORGANIC SOLVENT SUCH AS PAINT THINNER, ALCOHOL, OR BENZENE.

Attaching/Detaching the Lens

- Align the index mark on the lens barrel with the index mark on the lens mount of the camera.

- Do not press the lens release button on the camera when mounting the lens.

- Insert the lens into the camera mount and rotate it clockwise until it "clicks" and locks into place. Do not insert the lens at an angle.

- Remove the front lens cap when you are ready to shoot.

- To detach the lens, first attach the front lens cap.

- While holding down the lens release button on the camera body, rotate the lens counterclockwise until it stops, and separate the lens from the body.

- Attach the rear lens cap.

Lens Hood

- The hood blocks unnecessary light and protects the front surface of the lens from rain, snow, and dust.

- Align the mount position index indicated on the hood with the hood index (white) indicated on the lens, rotate the hood clockwise until a clicking sound occurs. The hood is now fixed.

- You can store the hood by mounting it on the lens in the opposite direction.

- Caution: Improper mounting of the hood hides the lens angle and causes vignetting.

Mounting the Filter

- A filter can be mounted on the filter mounting screw at the front of the lens.

- If two or more filters are mounted at the same time, vignetting may occur.

- Check if the filter size is compatible with the lens (refer to "Product specifications") and then mount it at the front of the lens.


Focus Hold Button

- This button can fix the focus when the AF mode is selected as the camera focusing method.

- The user can also assign other desired functions to the focus hold button through the menu setting on the camera body.

Custom Switch

- Use the custom switch to set the focus ring to control functions such as aperture adjustment.



- - MODE 1: Works as a focus adjustment function (when the focusing mode of the camera is set to MF or DMF)

- - MODE 2: Works as an aperture adjustment function (when the focusing mode of the camera is set to AF)

Product Specifications

Model Name	AF 85MM F1.4 SERIES II	
Aperture Range	F1.4 ~ 16	
Lens Optical	Construction	11 Elements in 8 Groups
	Special Lens	HR 4, ED 1
Coating	UMC	
Minimum Focusing Distance	0.85m (2.79ft)	
Magnification Ratio	X 0.12	
Diaphragm Blades	9	
Filter Size	72.0	
Maximum Diameter	83.4	
Mount	Sony FE	
Angle of view	Full Frame	28.9°
	APS-C	19.1°
Length	99.5mm	
Weight	509g	
Weight (With Lens Cap and Hood)	592g	
Weather Sealing	YES	
Custom Switch	YES	
AF Motor	Linear STM	

- The minimum focus is the distance from the image sensor to the object.
- The product specifications and exterior are subject to change without notice.
- The supported functions of this product may vary according to the camera brand and model.

Included Components

- Instruction Manual / Warranty
- Front Lens Cap
- Soft Lens Pouch
- Rear Lens Cap

Parts



- 1) Hood Locking Tube
- 2) Focus Ring
- 3) Mount
- 4) Lens Mount Index
- 5) Lens Signal Contact
- 6) Custom Switch
- 7) Focus Hold Button

※ The focus ring (②) can be used for different functions, such as aperture adjustment, depending on the position of the custom switch(⑥).

Notes

Contacts

Elite Brands Inc.
ROKINON Division
New York, NY 10005
Toll Free: 800.441.1100
Phone: 212.947.7100
support@rokinon.com

rokinon.com
facebook.com/rokinonlenses
instagram.com/rokinon

ROKINON® is a registered trademark of Elite Brands Inc
©2022, Elite Brands Inc., New York, NY 10005

IMPORTANT!
BEFORE SENDING YOUR ROKINON LENS OR ACCESSORY PLEASE CALL 1-800-441-1100 / (212) 947-7100
FOR TECHNICAL SUPPORT TO OBTAIN A WARRANTY AUTHORIZATION #

1. If the product on the right is determined to be defective a warranty authorization number will be provided.
2. Please include a copy of this document with all information filled in and dated proof of purchase.
3. Pack the equipment carefully with sufficient cushioning material and ship it prepaid and insured for its full value to:
ELITE BRANDS INC., Attn: Service Dept., 40 Wall Street, 61st Floor, New York, NY 10005

ROKINON U.S.A. LIMITED ONE YEAR WARRANTY

Your ROKINON product of the model and serial number on the right is warranted by Elite Brands Inc. against defective workmanship or materials for one full year from the date of purchase.

Elite Brands Inc. will at its option, either repair or replace equipment which is returned prepaid and insured to the address above. The product must be accompanied by the original sales slip showing proof of date of purchase and a copy of the Certificate of Quality with all of the required information filled in. On examination if the product has been damaged in transit, abused or is out of warranty, we will contact you with an estimate of the cost of service.

This warranty does not apply to equipment or accessories not manufactured or imported by Elite Brands Inc., or if the equipment is out of warranty, or has been damaged in transit, by accident, abuse (including, but not limited to, sand, dirt, water, liquid, impact, etc.), or failure to follow operating or maintenance instructions, or if the equipment has been modified or serviced by anyone other than Elite Brands Inc. This warranty only covers manufacturer defects as deemed by Elite Brands Inc.

SOME STATES DO NOT ALLOW CERTAIN CONDITIONS ON THE REPAIR OF WARRANTED PRODUCTS, SO THE ABOVE MAY NOT APPLY TO YOU.

This U.S.A. Limited One Year Warranty applies only to ROKINON lenses and accessories imported to the U.S.A. by Elite Brands Inc. and sold by an authorized Rokinson dealer. Elite Brands Inc. may, at its sole discretion, refuse to honor the warranty of any unauthorized product that is presented for repair.

THE FOREGOING WARRANTY IS ELITE BRAND INC.'S ONLY WARRANTY WITH RESPECT TO THE PRODUCT AND ELITE BRANDS INC. MAKES NO OTHER WARRANTY WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL ELITE BRANDS INC. OR ROKINON INC. BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF SUCH DAMAGES RESULT FROM NEGLIGENCE OR OTHER FAULT.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you.

This warranty gives you specific legal rights and you may also HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. ADDRESS ALL INQUIRIES CONCERNING THE ABOVE TO: ELITE BRANDS INC., ATTN: WARRANTY SERVICE 40 Wall Street, 61st Floor, New York, NY 10005 USA.
Email: support@rokinon.com Phone: (212) 947 7100

Date of Purchase _____ Purchased From _____
Name _____ Address _____
Phone # _____ Email Address _____

ROKINON®
Technology by Samyang Optics

Certificate of Quality

Thank you for Purchasing a Rokinson product. Rokinson lenses and accessories are renowned worldwide to deliver the performance required and exceptional value appreciated by both professional and beginner photographer/videographers. This certificate assures that the Rokinson product model and serial number below were manufactured by Samyang Optics in South Korea and incorporates their latest technology, attention to quality and detail.

Director Taeyoung Kang
Quality Control Team

Rokinson Optics Distributed by Elite Brands Inc.

40 Wall Street, 61st Floor
New York, NY 10005 USA
Web: www.rokinon.com
Email: Support@rokinon.com
Phone: (212) 947-7100 / (800) 441-1100