Ceiling Speaker Overview

	C806	C7V6	C808	C7V8	MC8026	MC7V26	MC8028	MC7V28
				0				
Driver design	2-way co-axial	2-way co-axial	2-way co-axial	2-way co-axial				
Driver Size	6.5" woofer/ 1" tweeter	6.5" woofer/ 1" tweeter	8" woofer/ 1" tweeter	8" woofer/ 1" tweeter	6.5" woofer/ 1" tweeter	6.5" woofer/ 1" tweeter	8" woofer/ 1" tweeter	8" woofer/ 1" tweeter
Connection	Wired	Wired	Wired	Wired	Wired	Wired	Wired	Wired
Amplifier	No, must be connected to amplifier	No, must be connected to amplifier	No, must be connected to amplifier	No, must be connected to amplifier	No, must be connected to amplifier	No, must be connected to amplifier	No, must be connected to amplifier	No, must be connected to amplifier
Power handling	120W RMS / 250W Peak	120W RMS / 250W Peak	150W RMS / 250W Peak	150W RMS / 250W Peak	120W RMS / 250W Peak	40W RMS / 80W Peak	150W RMS / 250W Peak	50W RMS / 100W Peak
Response Frequency	65Hz – 20 kHz	65Hz – 20 kHz	55Hz-20 kHz	55Hz-20 kHz	65Hz – 20 kHz	65Hz – 20 kHz	55Hz-20 kHz	55Hz-20 kHz
Impedance	8Ω	70V/100V 25W output	8Ω	70V/100V 35W output	8Ω	8Ω or 70V/100V 30W output	8Ω	8Ω or 70V/100V 35W output
Colour	White	White	White	White	White	White	White	White
Size diameter cm	22,9	22,9	27,3	27,3	23,5	23,5	28,3	28,3
Cut out dimensions WxD mm	193 x 94	193 x 94	240 x 114	240 x 114	203 x 94	203 x 94	254 x 110	254 x 110
Extra information	- Comes as a pair - Easy mount	Comes as a pairEasy mountMagnetic grill	- Comes as a pair - Easy mount - Magnetic grill	- Comes as a pair - Easy mount - Magnetic grill	- Comes as a pair - Easy mount - Magnetic grill			