



# SKID GARD NON-SKID TEXTURE ADDITIVE 44 and 45 Data Sheet

#### **CHARACTERISTICS**

DYCO<sup>®</sup> SKID GARD<sup>™</sup> is a non-skid additive specially formulated for easy mixing and application in all types of floor coatings. SKID GARD gives a tough, skid resistant texture finish for both interior and exterior surfaces.

#### **RECOMMENDED USES**

Interior and exterior concrete surfaces:

- Driveways
- Garages
- Walkways
- Patios
- Pool Decks
- Docks
- Steps
- Ramps

#### FOR ADDITIONAL INFORMATION

See MSDS or call toll-free 1-800-282-7901.

# **TECHNICAL DATA**

Finish/Sheen.....Flat Color......White VOC <sup>(less exempt solvents)</sup> .....0 g/L.

# COVERAGE

0.2lb. per gallon. 1lb. per 5 gallon.

#### **AVAILABLE GRADES**

- 44 Fine
- 45 Coarse

## **PHYSICAL PROPERTIES**

Flash Point: None



# DYC4X



SKID GARD NON-SKID TEXTURE ADDITIVE 44 and 45 Precautions & Application Guide

**FOR USE ON:** Concrete surfaces usually found in driveways, garages, walkways, patios, pool decks, docks, steps and ramps.

**PRECAUTION:** Wear protective clothing and eyewear during application of this product. Do not transport on passenger seats or inside passenger compartment of any vehicle. Store product in cargo area of vehicle, and secure with protective cloths to prevent accidental spill damage. Do not store at temperatures above 100 °F (37 °C). Do not use in drinking water or food systems.

**APPLICATION:** Mix SKID GARD into stain or paint. Add one (1) 3.2 OZ SKID GARD per gallon of floor coating. Use medium nap roller, brush or airless sprayer and follow manufacturer's directions for application. If two (2) coats are applied, SKID GARD may be used in both coats and will not change the color or property of the floor coating.

#### **CAUTION!**

HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

**WARNING!** Fine powder / dust may cause eye, skin or respirator irritation. Use adequate ventilation.

## VOC/VOS: 0 g/L

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to Sun Paints & Coating quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or consequential damages is hereby excluded.

