



## Duralux Marine Enamel CAMO Duckboat Drab - M691

### ICP Building Solutions Group

Version No: 1.1  
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 10/13/2021  
Print Date: 10/19/2021  
S.GHS.USA.EN

#### SECTION 1 Identification

##### Product Identifier

Product name	Duralux Marine Enamel CAMO Duckboat Drab - M691
Synonyms	Not Available
Proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base
Other means of identification	Not Available

##### Recommended use of the chemical and restrictions on use

Relevant identified uses	Marine Enamel
--------------------------	---------------

##### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group
Address	150 Dascomb Road Andover MA 01810 United States
Telephone	978-623-9980
Fax	Not Available
Website	<a href="http://www.icpgroup.com">www.icpgroup.com</a>
Email	sds@icpgroup.com

##### Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

#### SECTION 2 Hazard(s) identification

##### Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Flammable Liquids Category 3, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Skin Corrosion/Irritation Category 2, Carcinogenicity Category 1A, Reproductive Toxicity Category 2, Sensitisation (Skin) Category 1, Aspiration Hazard Category 1
----------------	---

##### Label elements

Hazard pictogram(s)	
---------------------	--

Signal word	Danger
-------------	--------

##### Hazard statement(s)

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.

## Duralux Marine Enamel CAMO Duckboat Drab - M691

H336	May cause drowsiness or dizziness.
H315	Causes skin irritation.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H317	May cause an allergic skin reaction.
H304	May be fatal if swallowed and enters airways.

**Hazard(s) not otherwise classified**

Not Applicable

**Precautionary statement(s) General**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

**Precautionary statement(s) Prevention**

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof (electrical/ventilating/lighting) equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fumes/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement(s) Response**

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P308+P313	IF Exposed or concerned: Get medical advice/attention.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse SKIN with water (or shower)
P333+P313	IF SKIN irritation or rash occurs: Get medical advice/attention
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+P313	IF Eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.

**Precautionary statement(s) Storage**

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
100-41-4	.1-1	<u>ethylbenzene</u>
64741-91-9.	5-10	<u>C14-20 aliphatics (&lt;=2% aromatics)</u>
64742-47-8	10-30	<u>distillates, petroleum, light, hydrotreated</u>
13463-67-7*	1-5	<u>Titanium Dioxide TiO2</u>
51274-00-1	1-5	<u>C.I. Pigment Yellow 42</u>
22464-99-9	.1-1	<u>zirconium 2-ethylhexanoate</u>
96-29-7	.1-1	<u>methyl ethyl ketoxime</u>
1333-86-4	.1-1	<u>carbon black</u>

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### SECTION 4 First-aid measures

#### Description of first aid measures

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For petroleum distillates

- In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption - decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- Positive pressure ventilation may be necessary.
- Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- After the initial episode, individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment. Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
- Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

BP America Product Safety & Toxicology Department

For acute or short term repeated exposures to iron and its derivatives:

- ▶ Always treat symptoms rather than history.
- ▶ In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- ▶ Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- ▶ Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- ▶ Iron intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- ▶ Serum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater than 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex) are the usual means of decontamination.
- ▶ Activated charcoal does not effectively bind iron.
- ▶ Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.
- ▶ Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]

### SECTION 5 Fire-fighting measures

#### Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.

#### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

#### Special protective equipment and precautions for fire-fighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are flammable.</li> <li>▶ Moderate fire hazard when exposed to heat or flame.</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) carbon monoxide (CO) metal oxides</p>

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

other pyrolysis products typical of burning organic material.

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

<b>Safe handling</b>	<p>The conductivity of this material may make it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of overexposure occurs.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ Store away from incompatible materials in a cool, dry, well-ventilated area.</li> </ul>

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul>

## SECTION 8 Exposure controls / personal protection

### Control parameters

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m <sup>3</sup>	545 mg/m <sup>3</sup> / 125 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	(); A3; BEI
US OSHA Permissible Exposure Limits (PELs) Table Z-1	C14-20 aliphatics (<=2% aromatics)	Oil mist, mineral	5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	C14-20 aliphatics (<=2% aromatics)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m <sup>3</sup>	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-1	distillates, petroleum, light, hydrotreated	Oil mist, mineral	5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	distillates, petroleum, light, hydrotreated	Mineral oil, excluding metal working fluids - Poorly and mildly refined	Not Available	Not Available	Not Available	A2
US ACGIH Threshold Limit Values (TLV)	distillates, petroleum, light, hydrotreated	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m <sup>3</sup>	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide TiO <sub>2</sub>	Inert or Nuisance Dust: Respirable fraction	5 mg/m <sup>3</sup> / 15 mppcf	Not Available	Not Available	Not Available

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide TiO2	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide TiO2	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide TiO2	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	Titanium Dioxide TiO2	Titanium dioxide	10 mg/m3	Not Available	Not Available	(A4)
US OSHA Permissible Exposure Limits (PELs) Table Z-3	C.I. Pigment Yellow 42	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	C.I. Pigment Yellow 42	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	C.I. Pigment Yellow 42	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	C.I. Pigment Yellow 42	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	C.I. Pigment Yellow 42	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-3	zirconium 2-ethylhexanoate	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	zirconium 2-ethylhexanoate	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	zirconium 2-ethylhexanoate	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	zirconium 2-ethylhexanoate	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	zirconium 2-ethylhexanoate	Zirconium compounds (as Zr)	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	zirconium 2-ethylhexanoate	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US NIOSH Recommended Exposure Limits (RELs)	zirconium 2-ethylhexanoate	Zirconium compounds (as Zr)	5 mg/m3	10 mg/m3	Not Available	[*Note: The REL applies to all zirconium compounds (as Zr) except Zirconium tetrachloride.]
US ACGIH Threshold Limit Values (TLV)	zirconium 2-ethylhexanoate	Zirconium and compounds, as Zr	5 mg/m3	10 mg/m3	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black (Inhalable particulate matter)	3 mg/m3	Not Available	Not Available	A3

## Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
ethylbenzene	Not Available	Not Available	Not Available
C14-20 aliphatics (<=2% aromatics)	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3
distillates, petroleum, light, hydrotreated	140 mg/m3	1,500 mg/m3	8,900 mg/m3
Titanium Dioxide TiO2	30 mg/m3	330 mg/m3	2,000 mg/m3
methyl ethyl ketoxime	30 ppm	56 ppm	250 ppm
carbon black	9 mg/m3	99 mg/m3	590 mg/m3

Ingredient	Original IDLH	Revised IDLH
ethylbenzene	800 ppm	Not Available
C14-20 aliphatics (<=2% aromatics)	2,500 mg/m3	Not Available
distillates, petroleum, light, hydrotreated	2,500 mg/m3	Not Available
Titanium Dioxide TiO2	5,000 mg/m3	Not Available
C.I. Pigment Yellow 42	Not Available	Not Available


## Duralux Marine Enamel CAMO Duckboat Drab - M691

Ingredient	Original IDLH	Revised IDLH
zirconium 2-ethylhexanoate	25 mg/m <sup>3</sup>	Not Available
methyl ethyl ketoxime	Not Available	Not Available
carbon black	1,750 mg/m <sup>3</sup>	Not Available

## Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
methyl ethyl ketoxime	D	> 0.1 to ≤ 1 ppm
<b>Notes:</b>	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

## Exposure controls

<b>Appropriate engineering controls</b>	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>▶ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.</li> <li>▶ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.</li> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> </ul>

## Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

<b>Appearance</b>	Not Available		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available

## Duralux Marine Enamel CAMO Duckboat Drab - M691

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	40.56	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## SECTION 11 Toxicological information

## Information on toxicological effects

Inhaled	<p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p>
Ingestion	<p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>The material has <b>NOT</b> been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.</p> <p>Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.</p>
Skin Contact	<p>This material can cause inflammation of the skin on contact in some persons.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.</p>
Eye	<p>This material can cause eye irritation and damage in some persons.</p> <p>Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.</p>
Chronic	<p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>There is sufficient evidence to suggest that this material directly causes cancer in humans.</p> <p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.</p> <p>Chronic excessive intake of iron have been associated with damage to the liver and pancreas. People with a genetic disposition to poor control over iron are at an increased risk.</p> <p>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]</p>

## Duralux Marine Enamel CAMO Duckboat Drab - M691

Duralux Marine Enamel CAMO Duckboat Drab - M691	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
ethylbenzene	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	Eye (rabbit): 500 mg - SEVERE
	Inhalation(Rat) LC50; 17.2 mg/14h <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral(Rat) LD50; ~3523 mg/kg <sup>[2]</sup>	Skin (rabbit): 15 mg/24h mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
C14-20 aliphatics (<=2% aromatics)	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye : Not irritating (OECD 405) *
	Inhalation(Rat) LC50; 4.6 mg/14h <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral(Rat) LD50; 7400 mg/kg <sup>[2]</sup>	Skin : Not irritating (OECD 404)*
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
distillates, petroleum, light, hydrotreated	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation(Rat) LC50; >4.3 mg/14h <sup>[1]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>
	Oral(Rat) LD50; >5000 mg/kg <sup>[2]</sup>	
Titanium Dioxide TiO2	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (hamster) LD50: >=10000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation(Rat) LC50; >2.28 mg/14h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral(Rat) LD50; >=2000 mg/kg <sup>[1]</sup>	
C.I. Pigment Yellow 42	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral(Rat) LD50; >5000 mg/kg <sup>[2]</sup>	Not Available
zirconium 2-ethylhexanoate	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
	Inhalation(Rat) LC50; >4.3 mg/14h <sup>[1]</sup>	
	Oral(Rat) LD50; 2043 mg/kg <sup>[1]</sup>	
methyl ethyl ketoxime	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >184<1840 mg/kg <sup>[1]</sup>	Eye (rabbit): 0.1 ml - SEVERE
	Inhalation(Rat) LC50; >4.83 mg/14h <sup>[1]</sup>	
	Oral(Rat) LD50; >900 mg/kg <sup>[1]</sup>	
carbon black	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral(Rat) LD50; >8000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

<b>ETHYLBENZENE</b>	<p>Liver changes, uterual tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>Ethylbenzene is readily absorbed when inhaled, swallowed or in contact with the skin. It is distributed throughout the body, and passed out through urine.</p> <p><b>NOTE:</b> Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.</p>
<b>C14-20 ALIPHATICS (&lt;=2% AROMATICS)</b>	*Exxsol D 100 SDS



## Duralux Marine Enamel CAMO Duckboat Drab - M691

<b>C.I. PIGMENT YELLOW 42</b>	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
<b>ZIRCONIUM 2-ETHYLHEXANOATE</b>	For aliphatic fatty acids (and salts) Acute oral (gavage) toxicity: The acute oral LD50 values in rats for both were greater than >2000 mg/kg bw Clinical signs were generally associated with poor condition following administration of high doses (salivation, diarrhoea, staining, piloerection and lethargy). There were no adverse effects on body weight in any study. In some studies, excess test substance and/or irritation in the gastrointestinal tract was observed at necropsy. Skin and eye irritation potential, with a few stated exceptions, is chain length dependent and decreases with increasing chain length. According to several OECD test regimes the animal skin irritation studies indicate that the C6-10 aliphatic acids are severely irritating or corrosive, while the C12 aliphatic acid is irritating, and the C14-22 aliphatic acids generally are not irritating or mildly irritating. Human skin irritation studies using more realistic exposures (30-minute, 1-hour or 24-hours) indicate that the aliphatic acids have sufficient, good or very good skin compatibility. Animal eye irritation studies indicate that among the aliphatic acids, the C8-12 aliphatic acids are irritating to the eye while the C14-22 aliphatic acids are not irritating. Fatty acid salts of low acute toxicity. Their potential to irritate the skin and eyes is dependent on chain length.
<b>METHYL ETHYL KETOXIME</b>	Mammalian lymphocyte mutagen *Huls Canada ** Merck For methyl ethyl ketoxime (MEKO): At medium to high concentrations, MEKO increased the rate of liver tumours in animal testing. This seems to be due to the breakdown of MEKO into a cancer-causing substance, and occurred more often in males.
<b>CARBON BLACK</b>	Inhalation (rat) TCLo: 50 mg/m <sup>3</sup> /6h/90D-I Nil reported
<b>Duralux Marine Enamel CAMO Duckboat Drab - M691 &amp; METHYL ETHYL KETOXIME</b>	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.
<b>Duralux Marine Enamel CAMO Duckboat Drab - M691 &amp; C14-20 ALIPHATICS (&lt;=2% AROMATICS) &amp; DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED</b>	Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species.
<b>Duralux Marine Enamel CAMO Duckboat Drab - M691 &amp; DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED</b>	Kerosene may produce varying ranges of skin irritation, and a reversible eye irritation (if eyes are washed). Skin may be cracked or flaky and/or leathery, with crusts and/or hair loss.
<b>ETHYLBENZENE &amp; CARBON BLACK</b>	<b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
<b>DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED &amp; C.I. PIGMENT YELLOW 42 &amp; ZIRCONIUM 2-ETHYLHEXANOATE &amp; CARBON BLACK</b>	No significant acute toxicological data identified in literature search.

<b>Acute Toxicity</b>	✗	<b>Carcinogenicity</b>	✓
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	✓
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✓
<b>Respiratory or Skin sensitisation</b>	✓	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✓

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

<b>Duralux Marine Enamel CAMO Duckboat Drab - M691</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	Not Available	Not Available	Not Available	Not Available	Not Available
<b>ethylbenzene</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	EC50	72h	Algae or other aquatic plants	4.6mg/l	1
	LC50	96h	Fish	3.381-4.075mg/L	4
	EC50	48h	Crustacea	1.37-4.4mg/l	4
	NOEC(ECx)	720h	Fish	0.381mg/L	4
	EC50	96h	Algae or other aquatic plants	3.6mg/l	2
<b>C14-20 aliphatics (&lt;=2% aromatics)</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	72h	Algae or other aquatic plants	<0.03mg/l	1
	NOEC(ECx)	3072h	Fish	1mg/l	1

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

distillates, petroleum, light, hydrotreated	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	3072h	Fish	1mg/l	1

Titanium Dioxide TiO2	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	3.75-7.58mg/l	4
	BCF	1008h	Fish	<1.1-9.6	7
	EC50	48h	Crustacea	1.9mg/l	2
	LC50	96h	Fish	1.85-3.06mg/l	4
	NOEC(ECx)	504h	Crustacea	0.02mg/l	4
	EC50	96h	Algae or other aquatic plants	179.05mg/l	2

C.I. Pigment Yellow 42	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Fish	0.52mg/l	2
	EC50	72h	Algae or other aquatic plants	18mg/l	2
	LC50	96h	Fish	0.05mg/l	2

zirconium 2-ethylhexanoate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	>0.17mg/l	2
	EC50	72h	Algae or other aquatic plants	49.3mg/l	2
	EC50	48h	Crustacea	>0.17mg/l	2
	LC50	96h	Fish	>100mg/l	2

methyl ethyl ketoxime	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	0.5-0.6	7
	NOEC(ECx)	72h	Algae or other aquatic plants	~1.02mg/l	2
	EC50	72h	Algae or other aquatic plants	~6.09mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	~201mg/l	2

carbon black	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>0.2mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	33.076-41.968mg/l	4
	NOEC(ECx)	24h	Crustacea	3200mg/l	1

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

When spilled this product may act as a typical oil, causing a film, sheen, emulsion or sludge at or beneath the surface of the body of water. The oil film on water surface may physically affect the aquatic organisms, due to the interruption of the oxygen transfer between the air and the water

Oils of any kind can cause:

- ▶ drowning of water-fowl due to lack of buoyancy, loss of insulating capacity of feathers, starvation and vulnerability to predators due to lack of mobility
- ▶ lethal effects on fish by coating gill surfaces, preventing respiration
- ▶ asphyxiation of benthic life forms when floating masses become engaged with surface debris and settle on the bottom and
- ▶ adverse aesthetic effects of fouled shoreline and beaches

In case of accidental releases on the soil, a fine film is formed on the soil, which prevents the plant respiration process and the soil particle saturation.

For petroleum distillates:

Environmental fate:

When petroleum substances are released into the environment, four major fate processes will take place: dissolution in water, volatilization, biodegradation and adsorption. These processes will cause changes in the composition of these UVCB substances.

**DO NOT discharge into sewer or waterways.**

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
Titanium Dioxide TiO2	HIGH	HIGH
methyl ethyl ketoxime	LOW	LOW

#### Bioaccumulative potential

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

Ingredient	Bioaccumulation
ethylbenzene	LOW (BCF = 79.43)
C14-20 aliphatics (<=2% aromatics)	LOW (BCF = 159)
distillates, petroleum, light, hydrotreated	LOW (BCF = 159)
Titanium Dioxide TiO2	LOW (BCF = 10)
methyl ethyl ketoxime	LOW (BCF = 5.8)

## Mobility in soil

Ingredient	Mobility
ethylbenzene	LOW (KOC = 517.8)
Titanium Dioxide TiO2	LOW (KOC = 23.74)
methyl ethyl ketoxime	LOW (KOC = 130.8)


## SECTION 13 Disposal considerations

## Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> </ul>
------------------------------	---

## SECTION 14 Transport information

## Labels Required

	
Marine Pollutant	NO

## Land transport (DOT)

UN number	1263	
UN proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base	
Transport hazard class(es)	Class	3
	Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Hazard Label	3
	Special provisions	367, B1, B52, B131, IB3, T2, TP1, TP29

## Air transport (ICAO-IATA / DGR)

UN number	1263	
UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	
Transport hazard class(es)	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	366
	Cargo Only Maximum Qty / Pack	220 L
	Passenger and Cargo Packing Instructions	355

## Duralux Marine Enamel CAMO Duckboat Drab - M691

Passenger and Cargo Maximum Qty / Pack	60 L
Passenger and Cargo Limited Quantity Packing Instructions	Y344
Passenger and Cargo Limited Maximum Qty / Pack	10 L

## Sea transport (IMDG-Code / GGVSee)

<b>UN number</b>	1263	
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
<b>Transport hazard class(es)</b>	IMDG Class	3
	IMDG Subrisk	Not Applicable
<b>Packing group</b>	III	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	EMS Number	F-E , S-E
	Special provisions	163 223 367 955
	Limited Quantities	5 L

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethylbenzene	Not Available
C14-20 aliphatics (<=2% aromatics)	Not Available
distillates, petroleum, light, hydrotreated	Not Available
Titanium Dioxide TiO2	Not Available
C.I. Pigment Yellow 42	Not Available
zirconium 2-ethylhexanoate	Not Available
methyl ethyl ketoxime	Not Available
carbon black	Not Available

## Transport in bulk in accordance with the ICG Code

Product name	Ship Type
ethylbenzene	Not Available
C14-20 aliphatics (<=2% aromatics)	Not Available
distillates, petroleum, light, hydrotreated	Not Available
Titanium Dioxide TiO2	Not Available
C.I. Pigment Yellow 42	Not Available
zirconium 2-ethylhexanoate	Not Available
methyl ethyl ketoxime	Not Available
carbon black	Not Available

## SECTION 15 Regulatory information

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## ethylbenzene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Carcinogens

US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US CWA (Clean Water Act) - List of Hazardous Substances

US CWA (Clean Water Act) - Priority Pollutants

US CWA (Clean Water Act) - Toxic Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

**C14-20 aliphatics (<=2% aromatics) is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 US ACGIH Threshold Limit Values (TLV)  
 US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**distillates, petroleum, light, hydrotreated is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans  
 US - California Proposition 65 - Carcinogens  
 US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List  
 US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**Titanium Dioxide TiO2 is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)  
 US - California Proposition 65 - Carcinogens  
 US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List  
 US - Massachusetts - Right To Know Listed Chemicals  
 US ACGIH Threshold Limit Values (TLV)  
 US ACGIH Threshold Limit Values (TLV) - Carcinogens

US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule  
 US NIOSH Carcinogen List  
 US NIOSH Recommended Exposure Limits (RELs)  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1  
 US OSHA Permissible Exposure Limits (PELs) Table Z-3  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**C.I. Pigment Yellow 42 is found on the following regulatory lists**

US NIOSH Recommended Exposure Limits (RELs)  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1  
 US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**zirconium 2-ethylhexanoate is found on the following regulatory lists**

US ACGIH Threshold Limit Values (TLV)  
 US ACGIH Threshold Limit Values (TLV) - Carcinogens  
 US NIOSH Recommended Exposure Limits (RELs)  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**methyl ethyl ketoxime is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List  
 US AIHA Workplace Environmental Exposure Levels (WEELs)  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances  
 US TSCA Section 4/12 (b) - Sunset Dates/Status

**carbon black is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)  
 US - California Proposition 65 - Carcinogens  
 US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List  
 US - Massachusetts - Right To Know Listed Chemicals  
 US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US NIOSH Carcinogen List  
 US NIOSH Recommended Exposure Limits (RELs)  
 US OSHA Permissible Exposure Limits (PELs) Table Z-1  
 US OSHA Permissible Exposure Limits (PELs) Table Z-3  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**Federal Regulations****Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312 hazard categories**

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No

Continued...

## Duralux Marine Enamel CAMO Duckboat Drab - M691

Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	Yes
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	Yes
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

## US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylbenzene	1000	454

## State Regulations

## US. California Proposition 65

**WARNING:** This product can expose you to chemicals including ethylbenzene, distillates, petroleum, light, hydrotreated, Titanium Dioxide TiO2, carbon black, which are known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylbenzene; C14-20 aliphatics (<=2% aromatics); distillates, petroleum, light, hydrotreated; titanium dioxide tiO2; c.i. pigment yellow 42; zirconium 2-ethylhexanoate; methyl ethyl ketoxime; carbon black) aromatics);=" distillates,=" petroleum,=" light,=" hydrotreated;=" titanium=" dioxide=" tiO2;=" c.i.=" pigment=" yellow=" 42;=" zirconium=" 2-ethylhexanoate;=" methyl=" ethyl=" ketoxime;=" carbon=">
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (zirconium 2-ethylhexanoate)
Vietnam - NCI	Yes
Russia - FBEPH	No (C.I. Pigment Yellow 42)
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

## SECTION 16 Other information

Revision Date	10/13/2021
Initial Date	10/14/2021

## CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

## Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit

Continued...

**Duralux Marine Enamel CAMO Duckboat Drab - M691**

TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
ES: Exposure Standard  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index  
AIIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDSL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European INventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCS: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory  
INSQ: Inventario Nacional de Sustancias Químicas  
NCI: National Chemical Inventory  
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.