



WIRELESS SECURITY SYSTEMS





Control Panels



ALAAJA-003

AJAX Hub Plus White

- Ethernet, Wi-Fi, 2 SIM cards (2G/3G)
- Up to 150 devices
- Up to 50 cameras or DVRs
- Up to 5 radio signal range extenders
- Up to 99 users
- Up to 25 security groups
- Up to 64 automation scenarios



ALAAJA-085

AJAX Hub 2 White 4G

- Ethernet and 2 SIM cards (2G/3G/4G)
- Up to 100 devices
- Up to 25 cameras or DVRs
- Up to 5 radio signal range extenders
- Up to 50 users
- Up to 9 security groups
- Up to 32 automation scenarios
- supporting photo verification of alarms



ALAAJA-035

AJAX Hub 2 Plus Black

- Ethernet, Wi-Fi, 2 SIM cards (2G/3G/4G)
- Up to 200 devices
- Up to 100 cameras or DVRs
- Up to 5 radio signal range extenders
- Up to 200 users
- Up to 25 security groups
- Up to 64 automation scenarios
- supporting photo verification of alarms





Range Extenders



ALAAJA-004

AJAX Rex Plus White

- Enviroment: Indoors
- Supports all Ajax Hubs
- Doesn't support MotionCam
- Max Number of Connected ReX per Hub Hub 1, Hub Plus/Hub 2/Hub 2 Plus - 5
- Power supply 110 240 VAC
- Built-in back-up battery: Li-Ion 2 Ah
- Battery backup up to 35 hours
- Operating frequencies 868.0 868.6 MHz
- Self-adjusting RF output power up 25mW



ALAAJA-063

AJAX Rex Plus 2 White

- Enviroment: Indoors
- Compatibility Hub 2 and Hub 2 Plus
- Supports MotionCam
- Max Number of Connected ReX per Hub: 5
- Power supply 110 240 VAC
- 12V option when using PSU module
- Built-in back-up battery: Li-lon 2 Ah
- Two-way communication between devices
- Operating frequencies 868.0 868.6 MHz
- Self-adjusting RF output power up to 25mW





Opening Detectors



ALAAJA-017

AJAX DoorProtect White

- · Door contact detector
- Activation threshold: Small Magnet -1cm
- · Operating frequencies 868.0 868.6 MHz
- Battery life: up to 5 years



ALAAJA-016

AJAX DoorProtect Plus White

- · Combined door
- · Built-in accelerometer for shock and tilt detection
- Ignores chattering and single shocks to avoid false alarms
- Additional NC input for connecting a third-party detector
- Activation threshold: Small Magnet -1cm
- Operating frequencies 868.0 868.6 MHz
- Battery life: up to 5 years

Glass Break Detectors



ALAAJA-020

AJAX GlassProtect White

- Sensing element: Electret microphone
- Break detection distance: Up to 9 m
- Microphone coverage angle: 180°
- Operating frequencies: 868.0 868.6 MHz
- Battery life: up to 7 years



ALAAJA-015

AJAX CombiProtect White

- Combined motion and glass break detector
- Motion detection distance: up to 12m
- Break detection distance: up to 9m
- Break detection angle: 180°
- Detection angles: Horizontal 88.5°, Vertical 80°
- · Recommended installation height: 2.4 m
- Pet immunity: Weight up to 20 kg, Height up to 50 cm
- Operating frequencies: 868.0 868.6 MHz
- Battery life: up to 5 years





Motion Detectors - Indoor



ALAAJA-005

AJAX MotionProtect White

- Sensing element: PIR sensor
- Motion detection distance: up to 12m
- Detection angles: Horizontal 88.5°, Vertical 80°
- Recommended installation height: 2.4 m
- Pet immunity: Weight up to 20 kg, Height up to 50 cm
- Operating frequencies 868.0 868.6MHz
- Battery life: up to 5 years



ALAAJA-015

AJAX CombiProtect White

- Combined motion and glass break detector
- Motion detection distance: up to 12m
- Break detection distance: up to 9m
- Break detection angle: 180°
- Detection angles: Horizontal 88.5°, Vertical 80°
- Recommended installation height: 2.4 m
- Pet immunity: Weight up to 20 kg, Height up to 50 cm
- Operating frequencies: 868.0 868.6 MHz
- Battery life: up to 5 years



ALAAJA-007

AJAX MotionCam Curtain White

- Compatible only with Hub 2, Hub 2 Plus
- Photo by scenario functions only
- Motion detection distance: up to 12 m
- Pet immunity: Weight up to 20 kg, Height up to 50 cm
- \bullet $\,\,$ Detection angles: Horizontal 88.5°, Vertical 80° $\,\,$
- Camera view angle: 90°
- Photo quality: up to 640 × 480
- Recommended installation height: 2.4 m
- Battery life: up to 4 years (up to 2.5 years if "Delay when entering" setting is activated)



ALAAJA-006

AJAX MotionProtect Plus White

- Sensing element: PIR sensor & microwave sensor (2.4GHz)
- Motion detection distance: up to 12m
- Detection angles: Horizontal 88.5°, Vertical 80°
- · Recommended installation height: 2.4 m
- Pet immunity: Weight up to 20 kg, Height up to 50 cm
- Operating frequencies 868.0 868.6MHz
- Battery life: up to 5 years



ALAAJA-008

AJAX MotionProtect Curtain White

- Two PIR sensors
- Motion detection distance 6 to 15 meters (depending on the device settings)
- Detection angles: Horizontally 6°, Vertically 90°
- Recommended installation height 2.4 m
- Operating frequencies: 868.0 868.6 MHz
- Battery life up to 3 years
- Protection class IP54



ALAAJA-091

AJAX MotionCam (Phod) White

- Compatible only with Hub 2, Hub 2 Plus
- · Photo by scenario functions and Photo on demand (Phod)
- Motion detection distance: up to 12 m
- Pet immunity: Weight up to 20 kg, Height up to 50 cm
- Detection angles: Horizontal 88.5°, Vertical 80°
- Camera view angle: 90°
 - Photo quality: up to 640 × 480
- Recommended installation height: 2.4 m
- Battery life: up to 4 years (up to 2.5 years if "Delay when entering" setting is activated)



AJAX MotionProtect White

- Two PIR sensors
- · Intelligent anti-masking system
- Recommended installation height: 0.8 1.3 m
- Detection angle: Horizontal 90°
- Motion detection distance: Adjustable, 3 15 m
- Pet immunity: Height up to 80 cm
- Battery life: up to 5 years



ALAAJA-053

AJAX MotionCam Outdoor White

- Compatibility: Hub 2, Hub 2 Plus
- Recommended installation height: 0,8 1,3 m
- 2 × PIR sensor
- Motion detection distance: Adjustable, from 3 to 15 m
- Pet immunity: Up to 80 cm tall
- Detection angle: Horizontal 88,5° Vertical 80°
- · Photo by scenario functions only
- Camera's angle: Horizontal 105° Vertical 102°
- Photo resolution: 320 × 176 pixels (by default); 640 × 352 pixels
- Shooting series up to 5 photos
- Infrared light for shooting in the dark: Available
- Battery life: Up to 3 years



ALAAJA-051

AJAX DualCurtain Outdoor White

- · Compatibility: Hub Plus, Hub 2, Hub 2 Plus, ReX
- IR sensor, 2 on each side
- Motion detection distance: 4 to 15 meters (on each side, depends on settings)
- · Battery life: Up to 4 years



ALAAJA-088

AJAX MotionCam Outdoor (Phod) White

- Compatibility: Hub 2, Hub 2 Plus
- Recommended installation height: 0,8 1,3 m
- 2 × PIR sensor
- Motion detection distance: Adjustable, from 3 to 15 m
- Pet immunity: Up to 80 cm tall
- Detection angle: Horizontal 88,5° Vertical 80°
- Photo by scenario functions and Photo on demand (Phod)
- Camera's angle: Horizontal 105° Vertical 102°
- Photo resolution: 320×176 pixels (by default); 640×352 pixels
- Shooting series up to 5 photos
- Infrared light for shooting in the dark: Available
- Battery life: Up to 3 years





Controls and Panic Buttons



ALAAJA-013

AJAX Keypad White

- Numeric touch keypad
- Clear button
- · Function button
- Arming button
- · Disarming button
- Night mode button
- Tamper button
- Duress code



ALAAJA-037

AJAX Keypad Plus White

- · Numeric touch keypad
- · Clear button
- · Function button
- · Arming button
- Disarming button
- Night mode button
- Tamper button
- Duress codeContactless access



ALAAJA-039

AJAX Contactless Cards White

- · Compatible with KeyPad Plus
- Operating frequency 13.56 MHz
- Encryption
- Authentication
- Protection from signal interception
- Possibility to assign the user
- Pack of 10





ALAAJA-012

AJAX SpaceControl White

- Four button key fob
- Command delivery indication
- Operating frequencies 868.0 868.6 MHz





Controls and Panic Buttons



ALAAJA-014

AJAX Button White

- · Command delivery confirmation
- Encryption with a modified AES algorithm
- Code hopping frequency
- Two modes: panic/control button
- Protected from accidental activation
- Operates with all Ajax Hubs and range extenders
- Operating frequencies 868.0 868.6 MHz
- Battery life of up to 5 years



ALAAJA-043

AJAX DoubleButton White

- Two buttons
- · LED indicating command delivery
- Protection against accidental press
- Radio frequency band 868.0 868.6 MHz
- Compatible only with hubs and range extenders on OS Malevich 2.10 and higher
- Battery life of up to 5 years
- Protection class IP55

Call for backup in one click in case of emergency 9:41 Tuesday, June 6 Ajax Multi-Planic button is pressed:

Sirens



AJAX HomeSiren White



ALAAJA-011

AJAX StreetSiren White



Integration Modules



ALAAJA-028

AJAX Multi Transmitter White

- 18 Wired zones for connecting third-party detectors
- NO, NC (without R), EOL (NC with R), EOL (NO with R)
- Remote setup of connected detectors in the app
- Power supply for connected detectors: 12 VDC, 1A
- Operating frequencies 868.0 868.6 MHz
- Power supply: 110 255 VAC
- Battery backup: 4 or 7 Ah capacity (not included)



ALAAJA-025

AJAX Transmitter

- Power supply output: 3.3 VDC
- Battery life: up to 5 years
- Operating frequencies 868.0 868.6 MHz



ALAAJA-068

AJAX vhfBridge White

- · Number of potential outputs: 8
- Output types: Positive trip and negative trip (depends on the settings)
- Transmission types: Pulse and bistable (depends on the settings)
- · Compatible with Ajax central units:
- Operates with Hub 2, Hub Plus, Hub 2 Plus
- Primary power supply: 100–240 V, 50/60 Hz
- VHF transmitter power: 12 V DC, 2 A
- Connection with a hub at a distance of up to 1800 meters
- The maximum battery size installed in the casing: 150×64×94mm
- · Backup battery is not included







AJAX Relay

- Power supply: 7 24 VDC
- Maximum load current: 5A at 36 VDC, 13A at 230 VAC
- Relay: NO/NC
- Operating frequencies 868.0 868.6 MHz



ALAAJA-026

AJAX WallSwitch

- Installation method: into wall plate
- Maximum load current: 13A
- Relay: NO/NC
- Operates with all Ajax Hub and range extenders
- Operating frequencies 868.0 868.6 MHz
- Power supply: 110 230 VAC







AJAX FireProtect White

- Smoke-sensitive element: Photoelectric sensor
- Temperature-sensitive element: Thermocouple
- Volume of built-in siren: 85 dB
- · Battery life: up to 4 years



ALAAJA-018

AJAX FireProtect Plus White

- · Smoke-sensitive element: Photoelectric sensor
- Temperature-sensitive element:Thermocouple
- Carbon monoxide detector
- Volume of built-in siren: 85 dB
- Battery life: up to 4 years

Water Leak Prevention



ALAAJA-021

AJAX LeaksProtect White

- Installation: Indoors
- Operating frequencies 868.0 868.6 MHz
- Battery life: up to 5 years
- Protection class: IP65







AJAX Socket White

- Maximum load current: 11 A (continuous) or 13 A (up to 5 sec)
- Executes scenarios
- · Relay: NO/NC
- Pulse duration: 0.5 255 sec
- Operating frequencies 868.0 868.6 MHz
- Operating voltage: 110 230 VAC
- Output power: up to 2.5 kW

Accessories



ALAAJA-029

AJAX Motion Protect Outdoor Hood White

- Smoke-sensitive element: Photoelectric sensor
- Temperature-sensitive element: Thermocouple
- Volume of built-in siren: 85 dB
- Battery life: up to 4 years





ALAAJA-045

AJAX Holder White

- · Surface mount holder
- Compatible with Button and DoubleButton

ALAAJA-090

AJAX Smart Universal bracket

- Compatible with MotionProtect Outdoor and MotionCam Outdoor
- Adjusted within a 180-degree angle from the mounting surface
- · Powder-coated stainless steel for added weather durability
- Supplied with stainless steel nuts and bolts required for mounting the MotionProtect Outdoor or the MotionCam Outdoor









AJAX 12V PSU For Hub/Hub Plus/Rex

- Input voltage: 8 20 VDC
- Output voltage: 4.65 VDC ± 3%
- Switch on voltage: 8 VDC ± 2.5%
- Switch off voltage: 6.9 7.5 VDC (depending on load)
- Max input current: < 1A
- Max output current: 1.5A
- DC jack: 5.5 × 2.1 mm

ALAAJA-031

AJAX 6V PSU For Hubs 2

- Input voltage 4.2-10 V
- Output voltage 4.8 V ± 5%
- Switch-on voltage 4.2 V ± 2.5%
- Switch-off voltage 3-3.4 V (depending on the load)
- Maximum input current 2.2 A at 4.2 V;
 0.8 A at 10 V
- Maximum output current 1.5 A
- Plug: 5.5 x 2.1 mm



ALAAJA-082

AJAX 12 PSU For Hubs 2 / Hub 2 Plus

- Input voltage: 4.2-16 V
- Output voltage: 4.8 V ± 5%
- Switch-on voltage: 4.2 V ± 2.5%
- Switch-off voltage: 3-3.4 V (depending on the load)
- Maximum input current: 2.2 A at 4.2 V; 0.5 A at 16 V
- Maximum output current: 1.5 A
- DC Jack: 5.5 × 2.1 mm





