

SHELLY BEACH

PROVISION ISR

IP SURVEILLANCE



















H.265 Stand Alone NVR 4CH 5MP at 25fps

Video Input 4 Channel Conventional Connection (1 x RJ-45 Network)

Support

Video Output HDMI: 1920x1080 (1080P), VGA: 1280x1024, 1024x768

Bandwidth Incoming 32Mbps
Bandwidth Outgoing 32Mbps
Decoding Support H.265/H.264

Recording Real-Time 4CH 5MP **FPS** 100 (PAL) / 120 (NTSC)

Resolution 2592x1944

Playback 4 Channels Simultaneously

Analytics support Camera Tampering, Line Crossing, Sterile Area,

Object Monitoring

Alarm Input IP Camera inputs only
Alarm Output IP Camera outputs only
Storage 1 x SATA (Up to 6TB)

USB Port2 x USB2.0NetworkRJ-45: 100MbpsAudio InputIP Camera inputs



NVR5-4100X+(MM)

SURNIP-PRO4001

























H.265 Stand Alone NVR 4CH 5MP at 25fps with PoE

Video Input 4 Channel PoE / Conventional Connection

(4x RJ-45 + 1 x RJ-45 Network)

Video Output HDMI: 1920x1080 (1080P), VGA: 1280x1024, 1024x768

Bandwidth Incoming 32Mbps
Bandwidth Outgoing 32Mbps
Decoding Support H.265/H.264
Recording Real-Time 4CH 5MP

FPS 100 (PAL) / 120 (NTSC)

Resolution 2592x1944

Playback 4 Channels Simultaneously

Analytics support Camera Tampering, Line Crossing, Sterile Area,

Object Monitoring

Alarm Input IP Camera inputs only
Alarm Output IP Camera outputs only
Storage 1 x SATA (Up to 6TB)

USB Port 2 x USB2.0

Network RJ-45: 100Mbps

Audio Input IP Camera inputs



NVR5-4100PX+(MM)





































H.265 Stand Alone NVR 8CH 5MP at 25fps

Video Input 4 Channel Conventional Connection (1 x RJ-45 Network)

Support

Video Output HDMI: 1920x1080 (1080P), VGA: 1280x1024, 1024x768

Bandwidth Incoming 32Mbps
Bandwidth Outgoing 32Mbps
Decoding Support H.265/H.264

Recording Real-Time 4CH 5MP **FPS** 100 (PAL) / 120 (NTSC)

Resolution 2592x1944

Playback 4 Channels Simultaneously

Analytics support Camera Tampering, Line Crossing, Sterile Area,

Object Monitoring

Alarm Input IP Camera inputs only
Alarm Output IP Camera outputs only
Storage 1 x SATA (Up to 6TB)

USB Port 2 x USB2.0

Network RJ-45: 100Mbps

Audio Input IP Camera inputs



NVR5-8200X+(MM)

SURNIP-PRO8001



























H.265 Stand Alone NVR 8CH 5MP at 25fps with PoE

Video Input 8 Channel PoE / Conventional Connection

(8 x RJ-45 + 1 x RJ-45 Network) Support

Video Output HDMI: 1920x1080 (1080P), VGA: 1280x1024/1024x768

Bandwidth Incoming 40Mbps
Bandwidth Outgoing 40Mbps
Decoding Support H.265/H.264
Recording Real-Time 8CH 5MP
FPS 200 (PAL) / 240 (NTSC)

Resolution 2592x1944

Playback 8 Channels Simultaneously

Analytics support Camera Tampering, Line Crossing, Sterile Area,

Object Monitoring

Alarm Input IP Camera inputs only
Alarm Output IP Camera outputs only
Storage 1 x SATA (Up to 6TB)

USB Port 2 x USB2.0
Network RJ-45: 100Mbps
Audio Input IP Camera inputs



NVR5-8200PX+(MM)





































H.265 Stand Alone NVR 8CH 8MP at 25fps Face recognition

Video Input 8 Channel Conventional Connection

(1 x RJ-45 Network) Support

Video Output HDMI: 4K, 1080P, 1280x1024, 1024x768,

VGA: 1080P, 1280x1024, 1024x768

Bandwidth Incoming 80Mbps Bandwidth Outgoing 80Mbps **Decoding Support** H.265 / H.264

Recording Real-Time 8CH 8MP or lower **FPS** 200 (PAL) / 240 (NTSC) **Playback** 8 Channels Simultaneously

Analytics Face Recognition, Smart Search,

Camera Tampering, Line Crossing, Sterile Area,

Object Monitoring

8 on device + Depends on Camera **Alarm Input Alarm Output** 4 on device + Depends on Camera

Storage 1 x SATA (Up to 8TB) **USB Port** 1 x USB3.0, 1 x USB2.0 Network RJ-45: 100Mbps **Audio** Two way audio

Audio Input 1 Channel on device (RCA) and IP Camera inputs

Audio Output 1 Channel on device (RCA)



NVR8-8200FA

SURNIP-PRO8004



























H.265 Stand Alone NVR 8CH 8MP at 25fps with PoE Face recognition

Video Input 8 Channel PoE / Conventional Connection

> $(8 \times RJ-45 + 1 \times RJ-45 \text{ Network})$ Support HDMI: 4K, 1080P, 1280x1024, 1024x768,

VGA: 1080P, 1280x1024, 1024x768

Bandwidth Incoming 80Mbps Bandwidth Outgoing 80Mbps **Decoding Support** H.265 / H.264

Video Output

Recording Real-Time 8CH 8MP or lower **FPS** 200 (PAL) / 240 (NTSC) **Playback** 8 Channels Simultaneously

Analytics Face Recognition, Smart Search,

Camera Tampering, Line Crossing, Sterile Area,

Object Monitoring

Alarm Input 8 on device + Depends on Camera **Alarm Output** 4 on device + Depends on Camera

1 x SATA (Up to 8TB) Storage **USB Port** 1 x USB3.0, 1 x USB2.0 Network RJ-45: 100Mbpsbps **Audio** Two way audio

Audio Input 1 Channel on device (RCA) and IP Camera inputs

Audio Output 1 Channel on device (RCA)



NVR8-8200PFA

































H.265 Stand Alone NVR 16CH 8MP at 25fps

Video Input 16 Channel Conventional Connection

(1 x RJ-45 Network) Support

Video Output HDMI: 1920x1080 (1080P)/4K,

1280x1024, 1024x768

Bandwidth Incoming 112Mbps
Bandwidth Outgoing 112Mbps
Decoding Support H.265 / H.264

Recording Real-Time 16CH 8MP or lower

FPS 400 (PAL) / 480 (NTSC)

Playback 16 Channels Simultaneously

Alarm Input 4 on device + Depends on Camera

Alarm Output 1 on device + Depends on Camera

Storage 2 x SATA (Up to 8TB)

USB Port 2 x USB2.0

Network RJ-45: 1000MbpsMbps Audio Two way audio

Audio Input 1 Channel on device (RCA) and IP Camera inputs

Audio Output 1 Channel on device (RCA)



NVR8-16400A(1U)

SURNIP-PRO16001





























H.265 Stand Alone NVR 16CH 8MP at 25fps supports Face recognition

Video Input 16 Channel Conventional Connection

(1 x RJ-45 Network) Support

Video Output HDMI: 4K, 1920x1080, 1280x1024, 1024x768

Bandwidth Incoming 160Mbps **Bandwidth Outgoing** 160Mbps **Decoding Support** H.265, H.264

Recording Real-Time 16CH 8MP

FPS 400 (PAL) / 480 (NTSC)

Playback 16 Channels Simultaneously

Analytics Face Recognition, Smart Search, Camera Tampering,

Line Crossing (Old + DDA), Sterile Area (Old + DDA),

Object Counting (Old + DDA), Item Monitoring,

Crowd Gathering

Alarm Input 8Ch + IPC Inputs
Alarm Output 4Ch + IPC Outputs
Storage 2 x SATA (Up to 8TB Each)

 USB Port
 2 x USB2.0

 Network
 RJ-45: 1000Mbps

Audio Input 1 Channel on device (RCA)
AudioOutput 1 Channel on device (RCA)



NVR8-16400FA(1U)

































H.265 Stand Alone NVR 16CH PoE 8MP at 25fps supports Face recognition

Video Input 16 PoE Channel / via Standard network connection

(16x RJ-45 + 1 x RJ-45 Network Port)

HDMI: 4K, 1920x1080, 1280x1024, 1024x768 **Video Output**

Bandwidth Incoming 160Mbps Bandwidth Outgoing 160Mbps **Decoding Support** H.265, H.264

Recording Real-Time 16CH 8MP **FPS** 400 (PAL) / 480 (NTSC) **Playback** 16 Channels Simultaneously

Analytics Face Recognition, Smart Search, Camera Tampering,

> Line Crossing (Old + DDA), Sterile Area (Old + DDA), Object Counting (Old + DDA), Item Monitoring,

Crowd Gathering

Alarm Input 8Ch + IPC Inputs **Alarm Output** 4Ch + IPC Outputs 2 x SATA (Up to 8TB Each) Storage **USB Port** 1 x USB2.0, 1 x USB3.0 Network RJ-45: 1000Mbps

Audio Input 1 Channel on device (RCA) **Audio Output** 1 Channel on device (RCA)



NVR8-16400PFA(1U)

SURNIP-PRO16003































H.265 Stand Alone NVR 32CH 8MP at 25fps supports Face recognition

Video Input 32Ch over Network

Video Output HDMI1: (4K 30/60Hz, 1080P, 1280x1024, 1024x768),

HDMI2: + VGA: (1080P, 1280x1024, 1024x768)

Bandwidth Incoming 192Mbps Bandwidth Outgoing 192Mbps

Decoding Support H.265 / H.265+ / H.265S / H.264

Recording Real-Time 32CH 8MP **FPS** 800 (PAL) / 960 (NTSC)

Analytics Camera Tampering, Line Crossing (DDA / Pixel Based),

Sterile Area (DDA / Pixel Based), Object Monitoring,

Object Counting (DDA), Crowd Gathering,

People Intrusion, Smart Search, Face Recognition, LPR

Alarm Input 8 + IP Camera inputs **Alarm Output** 4 + IP Camera outputs **Storage** 2 x HDD (Up to 10TB Each) **USB Port** 2 x USB2.0, 1 x USB3.0

Network 2x1000/100/10Mbps self-adaptive Ethernet interface

with Fault Tolerance / Dual Network Configuration

Audio 2-Way audio

Audio Input 1 Channel on device (RCA) + IP Camera inputs

Audio Output 1 Channel on device (RCA) **Playback Local** 16 Channels Simultaneously **Playback Remote** 32 Channels Simultaneously on IE,

4 Channels Simultaneously on H5



NVR8-32800FA(1U)

SURNIP-PRO32001































Security Superstore Shelly Beach saleshc@securitysperstore.co.za 072 250 7822



H.265 Stand Alone NVR 32CH 8MP at 25fps with 16CH PoE support Face recognition

Video Input 32 Channel Support (17 x RJ-45 Ports),

16 Channel PoE / Standard Network Connection

(via 16 x RJ-45 /Network),

16 Channel Standard Connection17 (via 1 RJ-45 Network Port)

Video Output VGA: 1280x1024, HDMI: 1920x1080 (1080P),

3840x2160 (4K)

Bandwidth Incoming 256Mbps **Bandwidth Outgoing** 256Mbps **Decoding Support** H.265, H.264

RecordingReal-Time 32CH 8MPFPS800 (PAL) / 960 (NTSC)Playback16 Channels Simultaneously

Analytics Face Recognition, Smart Search, Camera Tampering,

Line Crossing, Sterile Area, Object Monitoring

Alarm Input 16 Channel on device (Dry-Contact) + IP Camera inputs
Alarm Output 1 Channel on device (Dry-Contact) + IP Camera outputs

Storage8 x SATA (Up to 8TB Each)USB Port1 x USB2.0, 1 x USB3.0NetworkRJ-45: 1000MbpsAudio2 Way audio

Audio Input 1 Channel on device (RCA) + IP Camera inputs

Audio Output 1 Channel on device (RCA)



NVR8-32800F-16P(2U)

SURNIP-PRO32002





























H.265 Stand Alone NVR 32CH 8MP at 25fps supports Face recognition with RAID

Video Input 32 Channel via Standard network connection

(1 x RJ-45 Network Port)

Video Output VGA (HDMI Mirror): 1280x1024, 1920x1080 (1080P),

HDMI1: 1280x1024, 1920x1080 (1080P),

HDMI2: 1280x1024, 1920x1080 (1080P), 3840x2160 (4K)

Bandwidth Incoming 256Mbps
Bandwidth Outgoing 256Mbps
Decoding Support H.265, H.264
Recording Real-Time 320

Recording Real-Time 32CH 8MP **FPS** 800 (PAL) / 960 (NTSC)

Analytics Face Recognition, Smart Search, Camera Tampering, Line

Crossing (Old + DDA), Sterile Area (Old + DDA), Object Counting (Old + DDA), Item Monitoring, Crowd Gathering

Alarm Input 8 Dry Contacts + IP Camera inputs
Alarm Output 4 Dry Contacts + IP Camera outputs

 Storage
 8 x SATA (Up to 8TB Each)

 USB Port
 2 x USB2.0, 1 x USB3.0

 Network
 2xRJ-45: 2x1000Mbps Each

Audio 2 Way audio

Audio Input 1 Channel on device (RCA) + IP Camera inputs
Audio Output 1 Channel on device (RCA) + IP Camera outputs

Playback Local16 Channels SimultaneouslyPlayback Remote32 Channels Simultaneously

RAID 0/1/5/6/10 Support



NVR8-32800RFA(2U)









































H.265 Stand Alone NVR 64CH 8MP

Video Input 64 Channel via Standard network connection

Video Output HDMI1: 1280x1024, 1920x1080 (1080P), 3840x2160 (4K),

HDMI2: 1280x1024, 1920x1080 (1080P), VGA: (HDMI Mirror) 1024x768, 1280x1024,

1920x1080 (1080P)

Bandwidth Incoming 320Mbps
Bandwidth Outgoing 320Mbps
Decoding Support H.265, H.264

RecordingReal-Time 64CH 8MPFPS1600 (PAL) / 1920 (NTSC)Playback16 Channels SimultaneouslyAlarm Input8 Dry Contacts + IP Camera inputsAlarm Output4 Dry Contacts + IP Camera outputs

Storage 8 x SATA (Up to 8TB Each), 2 x E-SATA (Up to 8TB Each)

USB Port2 x USB2.0, 1 x USB3.0Network2xRJ-45: 1000Mbps Each

Audio 2 Way audio

Audio Input 1 Channel on device (RCA) + IP Camera inputs

Audio Output 1 Channel on device (RCA)
RAID 0/1/5/6/10 Support



NVR8-641600R(2U)

SURNIP-PRO64001







































H.265 Stand Alone NVR 128CH 8MP at 25fps

Video Input 2 x RJ-45 Network (1000Mbps) Support

Video Output HDMI: x 2 + VGA, Dual display mode, HDMI1:4K,

1920x1080 (1080P), 1280x1024,

HDMI2: / VGA:1920x1080 (1080P), 1280x1024

Bandwidth Incoming 384Mbps
Bandwidth Outgoing 384Mbps
Decoding Support H.265, H.264

Recording Real-Time 128CH 8MP, 5MP, 4MP, 3MP, 1080P,

960P, 720P, D1

FPS 3200(PAL) / 3840 (NTSC)

Resolution 8MP & lower

Playback 16 Channels Simultaneously (locally), 9Channels (Remotlly).

Alarm Input 8 Physical Alarm channels + IP Camera inputs
Alarm Output 4 Physical Alarm channels + IP Camera outputs only

Storage 16 x SATA Hot swap (Up to 8TB Each)

USB Port 1 x USB3.0, 2 x USB2.0

Network 2 x 1000Mbps Audio Two way audio

Audio Input 1 Channel + Depends on Camera inputs

Audio Output 1 Channel on device (RCA)

RAID 0/1/5/6/10 Support with Hot Swap

E-Sata 1



NVR8-128RT(3U)

SURNIP-PRO128001

ossia



























Camera H.265 S-Sight Series Bullet IR 20M (1 LED Array) 2.8mm lens 2MP with PoE

Sensor 1/2.8" CMOS (16:9)

Resolution 1920x1080 25/30FPS (2MP)

Lens 2.8mm (102°)

True Day & Night ICR

IR Range 20m (1 High-Power IR LED)

Compression H.265 / H.264

Image Enhancement WDR/BLC/HLC/ROI Support

General Analytics Camera Tampering

Standard Analytics (Pixel-Based) Line Crossing, Sterile Area

PoE Support
ONVIF Support
IP Rate IP67
Weight ~240g

Power DC12V/~420mA / PoE/~5.4W



12-320IPB-28

SURCIP-PROB007











Camera H.265 S-Sight Series Dome/Turret IR 20M (1 LED Array) 2.8mm Lens 2MP with PoE

 Sensor
 1/2.8" CMOS (16:9)

 Resolution
 1920x1080/25FPS (2MP)

Lens 2.8mm (103.7°)

True Day & Night ICR

IR Range 20m (1 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only)

Image Enhancement WDR, BLC, HLC, ROI Support

General Analytics Camera Tampering

Standard Analytics Line Crossing, Sterile Area

PoE Support ONVIF Support IP Rate IP67 450g

Power DC12V/350mA / PoE/5W
SD Card Support (Up to 128GB)
Audio Built-in Microphone



DI-320IPSN-28





















Camera H.265 S-Sight Series Dome/Turret IR 40M (2 LED Array) 2.8-12mm lens 2MP with PoE

Sensor 1/2.9" CMOS

Resolution 1920x1080/25FPS (2MP)

Lens 2.8-12mm Mega-Pixel Vari-Focal

True Day & Night ICR

IR Range 40m (3 IR LED Array)

Compression H.265/H.264

Image Enhancement D-WDR/BLC/HLC Support

General Analytics Support
PoE Support
ONVIF Support
IP Rate IP67
Weight 670g

Power DC 12V/~ 620mA /PoE/ 9.5W

SD Card Support (Up to 128GB)
Audio Support (Up to 128GB)



DI-320IPS-VF

SURCIV-PROD001



















Camera H.265 S-Sight Series Bullet IR 20M (1 LED Array) 2.8mm lens 2MP with PoE

Sensor 1/2.8" CMOS (16:9)

Resolution 1920x1080 25/30FPS (2MP)

Lens 2.8mm (106°)

True Day & Night ICR

IR Range 20m (1 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only)

Image Enhancement D-WDR/BLC/HLC/ROI Support

General Analytics Camera Tampering
Standard Analytics Line Crossing, Sterile Area

PoE Support

ONVIF Support IP Rate IP67
Weight ~390g

Power DC12V/354mA / PoE/4.4W SD Card Support (Up to 256GB)



12-320IPSN-28-V2





















Camera H.265 S-Sight Series Bullet IR 40M (2 LED Array) 2.8-12mm lens 2MP with PoE

Sensor 1/2.8" CMOS (16:9)

Resolution 1920x1080/ 25/30FPS (2MP) **Lens** 2.8-12mm (93.5°-31.9°)

True Day & Night ICR

IR Range 40m (2 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only)

Image Enhancement D-WDR/BLC/HLC/ROI Support

General Analytics Camera Tampering
Standard Analytics Line Crossing, Sterile Area

PoE Support
ONVIF Support
IP Rate IP67
Weight Weight

Power DC12V/~480mA / PoE/~6.5W SD Card Support (Up to 128GB)



14-320IPSN-VF

SURCIV-PROB002



















Camera H.265 S-Sight Series Dome/Turret IR 20M (1 LED Array) 2.8mm Lens 4MP with PoE

 Sensor
 1/2.7" CMOS (16:9)

 Resolution
 2560x1440/25FPS (4MP)

Lens 2.8mm (110°)

True Day & Night ICR

IR Range 20m (1 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only)

Image Enhancement D-WDR, BLC, HLC, ROI Support

General Analytics Camera Tampering

Standard Analytics Line Crossing, Sterile Area

PoE Support
ONVIF Support
IP Rate IP67
Weight ~450g

Power DC12V/~400mA / PoE/~5.2W SD Card Support (Up to 128GB)
Audio Built-in Microphone



DI-340IPS-28



















Camera H.265 S-Sight Series Dome/Turret IR 40M (2 LED Array) Motorized 2.8-12mm lens 4MP with PoE

 Sensor
 1/2.7" CMOS (16:9)

 Resolution
 2560x1440/25FPS (4MP)

Lens 2.8-12mm MVF with Auto Focus (94°-35.7°)

True Day & Night ICR

IR Range 40m (3 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only)

Image Enhancement WDR, BLC, HLC, ROI Support

General Analytics Camera Tampering

Standard Analytics Line Crossing, Sterile Area

PoE Support
ONVIF Support
IP Rate IP67
Weight ~640g

Power DC12V/~900mA / PoE/~10W
SD Card Support (Up to 128GB)
Audio Built-in Microphone



DI-340IPS-MVF

SURCIM-PROD001

















Camera H.265 S-Sight Series Bullet IR 20M (1 LED Array) 2.8mm lens 4MP with PoE

Sensor 1/2.7" CMOS (16:9) **Resolution** 2560x1440/25FPS (4MP)

Lens 2.8mm (110°)

True Day & Night ICR

IR Range 20m (1 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only)

Image Enhancement True WDR (120dB), BLC, HLC, ROI

General Analytics Camera Tampering

Standard Analytics Line Crossing, Sterile Area

PoE Support
ONVIF Support
IP Rate Support
Weight 390g

Power DC 12V/~ 420mA /PoE/~ 5.4W

SD Card Support (Up to 128GB)



12-340IPSN-28-V2





















Camera H.265 S-Sight Series Bullet IR 40M (2 LED Array) Motorized 2.8-12mm lens 4MP with PoE

 Sensor
 1/2.7" CMOS (16:9)

 Resolution
 2560x1440/25FPS (4MP)

Lens 2.8-12mm MVF with Auto Focus (94°-35.7°)

True Day & Night ICR

IR Range 40m (2 High-Power IR LED)

Compression H.265 / H.264 / MJPEG (Substream only) **Image Enhancement** Digital WDR, BLC, HLC, ROI Support

General Analytics Camera Tampering

Standard Analytics Line Crossing, Sterile Area

PoE Support
ONVIF Support
IP Rate IP67
Weight ~650g

Power DC12V/~780mA / PoE/~7.4W

SD Card Support (Up to 128GB)



14-340IPSN-MVF-V2

SURCIM-PROB001





















Camera H.265 Eye-Sight Series Mini dome IR 10M 2.8mm Lens 2MP with PoE

 Sensor
 1/2.8" CMOS (16:9)

 Resolution
 1920x1080/25FPS (2MP)

Lens 2.8mm (108°)

True Day & Night ICR

IR Range 10m (2 High-Power IR LED)

Compression H.265S/H.264S, H.265+/H.264+/H.265

/H.264/MJPEG

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

General Analytics Camera Tampering

Al (Object Recognition) DDA Sterile Area, DDA Line Crossing,

DDA Object Counting

AI (Face Detection) 10 Faces per frame

PoESupportONVIFSupportWeight350g

Power DC 12V/~ 340mA/PoE/4.7W

SD Card Support (Up to 128GB)

Audio in built-in Microphone



DMA-320IPE-28

























Camera H.265 Eye-Sight Series Dome/Turret IR 20M (1 LED Array) 2.8mm Lens 2MP with PoE

Sensor 1/2.8" CMOS

Resolution1920x1080/25FPS (2MP)Lens2.8mm Mega-Pixel Fixed

True Day & Night ICR

IR Range 20m (1 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support
ONVIF Support
IP Rate IP67
Weight 490g

Power DC 12V/~ 350mA /PoE/ 7.5W

SD Card Support (Up to 128GB)
Audio in built-in Microphone



DI-320IPE-28

SURCIP-PROD004



















Camera H.265 Eye-Sight Series Dome/Turret IR 40M (2 LED Array) Motorized 2.8-12mm lens 2MP with PoE

Sensor 1/2.8" CMOS

Resolution 1920x1080/25FPS (2MP)

Lens 2.8-12mm Mega-Pixel Motorized

True Day & Night ICR

IR Range 40m (3 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support
ONVIF Support
IP Rate IP67
Weight 670g

Power DC 12V/~ 620mA /PoE/ 9.5W

SD Card Support (Up to 128GB)

Audio in built-in Microphone



DI-320IPE-MVF

SURCIM-PROM001

























Camera H.265 Eye-Sight Series Bullet IR 40M (2 LED Array) 3.6mm lens 2MP with PoE

Sensor 1/2.8" CMOS

Resolution1920x1080/25FPS (2MP)Lens3.6mm Mega-Pixel Fixed

True Day & Night ICR

IR Range 40m (2 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support
ONVIF Support
IP Rate IP67
Weight 690g

Power DC 12V/~ 330mA /PoE/ 6.5W

SD Card Support (Up to 128GB)

Audio in Support



14-320IPE-36

SURCIP-PROB066



















Camera H.265 Eye-Sight Series Bullet IR 40M (2 LED Array) Motorized 2.8-12mm lens 2MP with PoE

Sensor 1/2.8" CMOS

Resolution 1920x1080/25FPS (2MP)

Lens 2.8-12mm Mega-Pixel Motorized

Vari-Focal lens with auto-focus

True Day & Night

IR Range 40m (2 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support
ONVIF Support
IP Rate IP67
Weight 690g

Power DC 12V/~ 330mA /PoE/ 6.5W SD Card Support (Up to 128GB)

Audio in Support



14-320IPE-MVF

SURCIM-PROB002

























Camera H.265 Eye-Sight Series Bullet IR 60M (4 LED Array) Motorized 2.8-12mm lens 2MP with PoE

1/3" CMOS (16:9) Sensor Resolution 1920x1080

Lens 2.8-12mm MVF with Auto Focus (103°-32°)

True Day & Night

IR Range 60m (4 High-Power IR LED) Compression H.265S/H.264S, H.265+/H.264+

/H.265/H.264/MJPEG

Frame rate 1-25/30FPS In Normal Mode.

1-50/60FPS in HFR Mode

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

General Analytics Camera Tampering

AI (Object Recognition) DDA Sterile Area, DDA Line Crossing,

DDA Object Counting

AI (Face Detection) 10 Faces per frame

AI (Heatmap) Support PoE Support **ONVIF** Support **IP Rate IP67** Weight ~1040g

Power DC12V/~910mA / PoE/~8.2W

SD Card Support (Up to 128GB)

Audio in/out Support Alarm in/out Support



16-320IPEN-MVF

SURCIM-PROB003























Camera H.265 Eye-Sight Series Dome/Turret IR 20M (1 LED Array) 2.8mm Lens 4MP with PoE

Sensor 1/3" CMOS

Resolution 2592X1520/25FPS (4MP) Lens 2.8mm (108°) Fixed

ICR True Day & Night

IR Range 20m (1 IR LED Array)

Compression H.265/H.264

WDR/BLC/HLC/ROI Support **Image Enhancement**

General Analytics Camera Tampering

AI (Object Recognition) DDA Sterile Area, DDA Line Crossing,

DDA Object Counting

AI (Face Detection) 10 Faces per frame

PoE Support **ONVIF** Support **IP Rate** IP67 Weight 450g

Power DC 12V/~ 527mA /PoE/ 5.4W **SD Card** Support (Up to 128GB)

Audio in built-in Microphone



DI-340IPE-28























Camera H.265 Eye-Sight Series Dome/Turret IR 40M (2 LED Array) Motorized 2.8-12mm lens 4MP with PoE

Sensor 1/3" CMOS

Resolution 2592X1520/25FPS (4MP)

Lens 2.8-12mm Mega-Pixel Motorized

True Day & Night ICR

IR Range 40m (3 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support
ONVIF Support
IP Rate IP67
Weight 670g

Power DC 12V/~ 620mA /PoE/ 9.5W SD Card Support (Up to 128GB)

Audio in built-in Microphone



DI-340IPE-MVF

SURCIM-PROD002





















Camera H.265 Eye-Sight Series Bullet IR 40M (2 LED Array) 3.6mm lens 4MP with PoE

Sensor 1/3" CMOS

Resolution2592X1520/25FPS (4MP)Lens3.6mm Mega-Pixel Fixed

True Day & Night ICR

IR Range 40m (2 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support
ONVIF Support
IP Rate IP67
Weight 690g

Power DC 12V/~ 330mA /PoE/ 6.5W SD Card Support (Up to 128GB)

Audio in Support



14-340IPE-36























Camera H.265 Eye-Sight Series Bullet IR 40M (2 LED Array) Motorized 2.8-12mm lens 4MP with PoE

1/3" CMOS Sensor

Resolution 2592X1520/25FPS (4MP)

Lens 2.8-12mm Mega-Pixel Motorized

Vari-Focal lens with auto-focus

True Day & Night

IR Range 40m (2 IR LED Array)

H.265/H.264 Compression

WDR/BLC/HLC Support **Image Enhancement**

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoE Support **ONVIF** Support **IP Rate IP67** Weight 690g

DC 12V/~ 330mA /PoE/ 6.5W **Power SD Card** Support (Up to 128GB)

Audio in Support



14-340IPE-MVF

SURCIM-PROB004





















Camera H.265 Eye-Sight Series Bullet IR 60M (4 LED Array) Motorized 2.8-12mm lens 4MP with PoE

Sensor 1/3" CMOS (16:9)

Resolution 2592X1520/25FPS (4MP)

Lens 2.8-12mm MVF with Auto Focus (94.3°-29.9°)

True Day & Night

IR Range 60m (4 High Power IR LED) H.265S/H.264S*, H.265+ Compression

/H.264+/H.265/H.264

True WDR (120dB), BLC, HLC, ROI Support **Image Enhancement**

General Analytics Camera Tampering

AI (Object Recognition) DDA Sterile Area, DDA Line Crossing,

DDA Object Counting

AI (Face Detection) 10 Faces per frame

AI (Heatmap) Support PoE Support **ONVIF** Support **IP Rate IP67** Weight 1040g

Power DC12V/~910mA / PoE/~8.2W SD Card Support (Up to 256GB)

Audio in/out Support Alarm in/out Support

Local Record Micro SD up to 256GB



16-340IPEN-MVF

SURCIM-PROB005























Security Superstore Shelly Beach





Camera H.265 Eye-Sight Series Bullet IR 60M (4 LED Array) Motorized 2.8-12mm lens 8MP with PoE

Sensor 1/3" CMOS

Resolution 3840x2160/20FPS (8MP)

Lens 2.8-12mm Mega-Pixel Motorized

Vari-Focal Lens with Auto-Focus

True Day & Night ICR

IR Range 60m (4 IR LED Array)

Compression H.265/H.264

Image Enhancement WDR/BLC/HLC Support

Analytic Functions Object Detection, Face Detection

& Advanced Analytic Functions

PoESupportONVIFSupportIP RateIP67Weight1040g

Power DC 12V /790mA /PoE/ 11.04W

SD Card Support (Up to 128GB)

Audio in/out Support
Alarm in/out Support

Local Record Micro SD up to 128GB



16-380IPE-MVF

SURCIM-PROB006





















Camera Smart-Sight series Face Recognition Turret/Dome 2MP IR 40M (2LED Array) Motorized 7-22mm lens with POE

Sensor 1/2.8" CMOS

Resolution 1920x1080/25FPS (2MP)

Lens 7-22mm MVF with Auto Focus (44°-17.6°)

True Day & Night ICF

Compression H.265 / H.264 / MJPEG

Image EnhancementTrue WDR (120dB), BLC, HLC, ROIAnalytic FunctionsFace Detection, Face Recognition

PoE Support
ONVIF Support
IP Rate IP67
Weight 1040g

Recognition distance

Power DC12V~320mA / AC24V~160mA / PoE~6W

SD Card Support (Up to 128GB)
Audio 1Ch Input, 1Ch Output
Alarm Alarm Out

Recognition per second Up to 10 face detections and 3 face

recognitions per second 60cm - 12m distance

Face Database Up to 10000 faces, Add face via WEB or VMS Image Settings AWB, AGC Adjustable, Exposure Mode (Auto),

Sharpness, Saturation, Brightness & Contrast Adjustable



DW-320FR-MVF2

SURCIM-PROD003

















Security Superstore Shelly Beach



Camera Smart-Sight series Face recognition Bullet 2MP white LED Motorized 7-22mm lens with POE

Sensor 1/2.8" CMOS

Resolution 1920x1080/25FPS (2MP)

Lens 7-22mm MVF with Auto Focus (44° - 17.6°)

True Day & Night ICR

Compression H.265 / H.264 / MJPEG

Image EnhancementTrue WDR (120dB), BLC, HLC, ROIAnalytic FunctionsFace Detection, Face Recognition

PoESupportONVIFSupportIP RateIP67Weight1040g

Power DC12V~320mA / AC24V~160mA / PoE~6W

SD Card Support (Up to 128GB)
Audio 1Ch Input, 1Ch Output
Alarm Alarm Out

Recognition per second Up to 10 face detections and 3 face

recognitions per second

Recognition distance 60cm - 12m distance

Face Database Up to 10000 faces, Add face via WEB or VMS
Image Settings AWB, AGC Adjustable, Exposure Mode (Auto),

Sharpness, Saturation, Brightness & Contrast Adjustable



TW-320FR-MVF2

SURCIP-PROP001

















Camera Smart series LPR Bullet 2MP IR 40M (2LED Array) Motorized 7-22mm Lens with POE

Sensor 1/2.8" CMOS

Resolution 1920x1080/25FPS (2MP) **Lens** 7-22mm Mega-Pixel Motorized

Vari-Focal Lens with Auto-Focus (44°-17.6°)

True Day & Night ICR

 IR Range
 60m (4 High-Power IR LED)

 Compression
 H.265S/H.264S, H.265+/H.264+

/H.265/H.264, MJPEG (Substream only)

Image Enhancement True WDR(120dB), BLC, HLC, ROI Support

LPR Analytics Support

Detection Speed 0-70Km/h

PoE Support

ONVIF Support

IP Rate IP67

Weight 1040g

Power DC12V/~910mA / PoE/~11W SD Card Support (Up to 128GB)

Audio in/out Support
Alarm in/out Support

Database Up to 10,000 License Plates (Internal Storage)



16-320LPR-MVF2

SURCIM-PROL002

























Camera H.265 S-Sight active deterrence Series Dome/Turret IR LED Motorized Lens 4MP with PoE

Sensor 1/3" CMOS (16:9)

Resolution 2592X1520 25/30FPS (4MP)

Lens 2.8-12mm MVF with Auto Focus (94.2°-29.8°)

True Day & Night ICR

IR Range 40m (2 High-Power IR LED)

Compression H.265+/H.264+/H.265/H.264/MJPEG

(Substream only)

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

General Analytics Camera Tampering

AI (Object Recognition) DDA™ Sterile Area, DDA™ Line Crossing

PoE Support
ONVIF Support
IP Rate IP66
Weight ~640g

Power DC 12V/~ 900mA /PoE/ ~10W

SD Card Support (Up to 256GB)

Audio Built-in Microphone and Speaker + Audio input

Strobe light Red/Blue



DI-340AD-MVF

SURCIP-PROB068



























Camera H.265 S-Sight active deterrence Series Bullet IR LED Motorized Lens 4MP with PoE

Sensor 1/3" CMOS (16:9)

Resolution 2592X1520/ 25/30FPS (4MP)

Lens 2.8-12mm MVF with Auto Focus (94.2°-29.8°)

True Day & Night ICR

 IR Range
 40m (2 High-Power IR LED)

 Compression
 H.265+/H.264+/H.265/H.264

(Main and Substream) MJPEG

(Substream only)

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

General Analytics Camera Tampering

Al (Object Recognition) DDA™ Sterile Area, DDA™ Line Crossing

PoE Support
ONVIF Support
IP Rate IP66
Weight ~ 650g

Power DC 12V/~ 780mA /PoE/ ~ 7.4W

SD Card Support (Up to 256GB)

Strobe light Red/Blue



14-340AD-MVF

SURCIP-PROB008

























Security Superstore Shelly Beach



Camera H.265 IP Series Fisheye 6MP with PoE

1/2.9" CMOS (3096 x 2196 - 16:9) Sensor

Resolution 6 Mega-Pixel (Max)

1.07mm (360° for Ceiling Mount Lens

/ 180° For Wall Mount)

True Day & Night

IR Range 15m (6 High Power Wide Angle IR LED) H.265 / H.264 / MJPEG (Substream only) Compression **Image Enhancement** Digital WDR / BLC / HLC / ROI / 3D-DNR Motion Detection and Privacy Masking **General Analytics**

PoE Support **ONVIF** Support

Power DC12V/~420mA / PoE/~5.4W **SD Card** Event/Schedule based Main

/Substream recording (Up to 256GB)

Alarm Alarm in + Alarm out

Min. Illumination Day: 0.1lux / Night: 0.068lux

(@F2.0, AGC on) Olux with IR on

Analog Video Output CVBS (BNCx1)

Vandal Proof IK10



FEI-360IPN

SURCIP-PROF001











Camera H.265 Dummy PIR IR 10M (24 LEDs) 3.7mm Pinhole Lens 2MP with PoE

Sensor 1/2.8" CMOS Sensor Resolution 2 Mega-Pixel

Lens 3.7mm Mega-Pixel Lens

True Day & Night IR Cut Removable **IR Range** 10m IR Illumination

H.265 (H.264 Compatible) Compression

Image Enhancement DWDR, BLC, HLC, ROI, 3D Noise Reduction **Detection** Motion Detection and Privacy Masking

General Analytics Camera Tampering, Line Crossing, Sterile Area

PoE Support ONVIF Support

Audio Built-in Microphone + Audio input

Min. Illumination 0 Lux (IR on) **Local Storage** Support



IV-320IP-37



































Camera H.265 Hidden 3.7mm lens 2MP

Sensor 1/2.8" CMOS (16:9) Sensor

Resolution2 Mega-PixelLens3.7mm (89°)

True Day & Night ICR

Compression H.265S/H.264S, H.265+/H.264+

/H.265/H.264/MJPEG

Image Enhancement True WDR (120dB), BLC, HLC,

ROI, 3D Noise Reduction

Detection Motion Detection and Privacy Masking

Min. Illuminatio Day: 0.1lux / Night: 0.005lux

(@F1.6, AGC on) Olux with IR on

General Analytics Camera Tampering

Al (Object Recognition) DDA Sterile Area, DDA Line

Crossing, DDA Object Counting

AI (Face Detection) 10 Faces per frame

ONVIF Support

Power DC12V/~400mA

SD Card Micro SD card up to 256GB

Audio 1-Way Audio (Built-in Microphone)



MC-322IPE-37

SURCIP-PROC002













Camera H.265 S-Sight Rainbow Series Dome/Turret White LED 2.8mm Lens 2MP with PoE

Sensor 1/2.8" CMOS (16:9)

Resolution 1920x1080 25/30FPS (2MP)

Lens 2.8mm (105.2°)

 IR Range
 25m (2 High-Power White LED)

 Compression
 H.265 / H.264 / H.265+ / H.264+

/ MJPEG (Substream only)

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

Full-Color24/7 Full-Color Day ModeGeneral AnalyticsCamera TamperingStandard AnalyticsLine Crossing, Sterile Area

PoE Support ONVIF Support IP Rate IP67

Power DC 12V/~ 420mA /PoE/ ~5.4W

SD Card Support (Up to 128GB)
Audio Support (Up to 128GB)

Weigh ~450g



DV-320SRN-28

SURCIP-PROD006



















Security Superstore Shelly Beach saleshc@securitysperstore.co.za 072 250 7822



Camera H.265 S-Sight Rainbow Series Bullet White LED 3.6mm Lens 2MP with PoE

1/2.8" CMOS (16:9) Sensor

1920x1080/ 25/30FPS (2MP) Resolution

Lens 3.6mm (84.6°)

IR Range 25m (2 High-Power White LED) H.265 / H.264 / H.265+ / H.264+ Compression

/ MJPEG Compression

Image Enhancement True WDR (120dB), BLC, HLC, ROI

Full-Color 24/7 Full-Color Day Mode

General Analytics Camera Tampering

Standard Analytics Line Crossing, Sterile Area

PoF Support **ONVIF** Support **IP Rate IP67** Weight ~390g

Power DC12V/~420mA / PoE/~5.4W **SD Card** Support (Up to 128GB)

Audio Built-in Microphone



BSV-320SRN-36

SURCIP-PROB009





















Camera H.265 E-Sight Rainbow Series Dome/Turret White LED 3.6mm Lens 4MP with PoE

Sensor 1/2.8" CMOS (16:9)

Resolution 2560x1440 25/30FPS (4MP) Lens 3.6mm Fixed Lens (77.9°) 25m (2 High-Power White LED) **IR Range** Compression

H.265/H.265+/H.264/H.264+/MJPEG

(Substreams only)

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

Full-Color 24/7 Full-Color Day Mode **General Analytics Camera Tampering**

AI (Object Recognition) DDA™ Sterile Area, DDA™ Line

Crossing, DDA™ Object Counting

AI (Face Detection) 10 Faces per frame

PoE Support **ONVIF** Support **IP Rate IP67** Weight ~450g

Power DC 12V/~ 400mA /PoE/~5.2W

SD Card Support (Up to 256GB)

Audio input Built-in Microphone + Audio input



DL-340IPERN-36

























Camera H.265 E-Sight Rainbow Series Bullet White LED 3.6mm Lens 4MP with PoE

1/2.8" CMOS (16:9) Sensor

Resolution 2560x1440/ 25/30FPS (4MP) Lens 3.6mm Fixed Lens (77.9°) 25m (2 High-Power White LED) **IR Range** Compression H.265/H.265+/H.264/H.264+

/MJPEG (Substream Only) Compression

Image Enhancement True WDR (120dB), BLC, HLC, ROI Support

Full-Color 24/7 Full-Color Day Mode

General Analytics Camera Tampering

AI (Object Recognition) DDA™ Sterile Area, DDA™ Line

Crossing, DDA™ Object Counting

AI (Face Detection) 10 Faces per frame

PoE Support **ONVIF** Support **IP Rate** IP67 Weight ~ 650g

Power DC 12V/~ 780mA /PoE/ ~ 7.4W

SD Card Support (Up to 256GB)



TL-340IPERN-36

SURCIP-PROB010





















Camera Wireless PnV 1080P Hidden Fixed IP camera with IR with EU & US Soket

Quick Set-up - Provision-ISR advanced Plug & View **Features**

> cameras are ideal for monitoring your home, office or business at both day night. iPhone/iPad/ Android viewer app, iOS/Android Mobile App:

Live view, Remote playback, Local SnapShot/video recording

Wireless Support (802.11b/g/n)

3.6mm Lens

Resolution 2MP - 1920x1080

Compression H.264

Detection Motion detection Min. Illumination Day & night vision **Detection** Motion detection

Audio 2 Way Audio with Built-in Microphone & Speaker

SD Card Local recording on Micro SD



R-838































Camera Wireless PnV 1080P Pan/Tilt IP camera with IR

Features Quick Set-up – Provision-ISR advanced Plug & View

cameras are ideal for monitoring your home, office or business at both day & night, iPhone/iPad/Android viewer app, iOS/Android Mobile App: Live view, Gesture Control, Remote playback, Local S

napShot/video recording

Wireless Support (802.11b/g/n)

Lens3.6mmResolution2MPCompressionH.264

DetectionMotion detectionMin. IlluminationDay & night visionDetectionMotion detection

Audio 2 Way Audio with Built-in Speaker/Microphone

 Pan
 355°

 Tilt
 120°

SD Card Local recording on Micro SD



PT-838

SURCIP-PROW001































Camera Wireless PnV 1080p Waterproof fix IP camera with IR with EU & US Soket

Features Quick Set-up – Provision-ISR advanced Plug & View

cameras are ideal for monitoring your home, office or business at both day & night. iPhone/iPad /Android viewer app, iOS/Android Mobile App: Live view, Gesture Control, Remote playback,

Local SnapShot/video recording

Wireless Support (802.11b/g/n)

Lens4mmResolution2MPCompressionH.264

DetectionMotion detectionMin. IlluminationDay & night visionDetectionMotion detection

Audio 2 Way Audio with Built-in Speaker/Microphone

SD Card Local recording on Micro SD



WP-919





















Camera Wireless IPC 30M (3pcs LED array) 3.6mm lens 3MP

Wireless Camera (Compatible with WR-04IPC-V2)

Sensor 1/3" CMOS (16:9) **Lens** 3.6mm (90°)

Resolution3 Mega Pixel, 2304x1296IR Range30m IR IlluminationCompressionH.265 / H.264

Detection Motion Detection, 3-Axis

True Day & Night ICR

Min. Illumination 0 Lux (IR ON) Min. Illumination

Image Enhancement3D Noise ReductionDetectionMotion Detection, 3-Axis

IP Rate IP66
Power DC12V



SURCHW-PRO001













4ch Repeater for Wi-Fi camera model I3-330WIP536

Wireless Camera I3-390WIP36)

Resolution2 Mega-Pixel (Max)CompressionH.265 (HEVC)DetectionMotion DetectionDetectionMotion Detection

ONVIF Support
Power 12VDC Input



WR-04IPC

SURZSU-PRO001













Camera IP Bullet IR PTZ 2MP X4 Zoom IR 50m distance with POE

1/2.9" CMOS Sensor Sensor

Lens 2 Mega-Pixel

IR Range 50m **True Day & Night ICR**

0 Lux (IR ON) Min. Illumination Min. Illumination Digital WDR, 3D Noise Reduction Image Enhancement

H.265(HEVC)/H.264 Compression

Detection Motion Detection and Privacy Masking

Zoom x4 (2.8-12mm) **ONVIF** Support

IP66 Water-proof and Dust-proof **IP Rate**

Power PoE / 12VDC / 2A



15PT-320IPMX4-P

SURCIP-PROP004



























Camera IP Bullet IR PTZ 2MP X10 Zoom IR 50m distance with POE

1/2.9" CMOS Sensor Sensor

Lens 2 Mega-Pixel

IR Range 50m **True Day & Night ICR**

Min. Illumination 0 Lux (IR ON) Min. Illumination Image Enhancement Digital WDR, 3D Noise Reduction

Compression H.265(HEVC)/H.264

Motion Detection and Privacy Masking **Detection**

Zoom x10 (5.1-51mm)

ONVIF Support

IP Rate IP66 Water-proof and Dust-proof

PoE / 12VDC / 2A Power



I5PT-320IPMX10-P





























Camera IP PTZ 2MP X20 Zoom high speed Pan/Tilt/Zoom IR 80m distance

IR Range 80m
True Day & Night ICR

Image Enhancement Digital WDR, 3D-DNR Noise Reduction, WB/BLC/AGC

Compression H.265 **Video Stream** Dual

Preset speed 120°/Sec (max)
Preset accuracy up to 0.1°

Pan Endless 360° Rotation

Tilt 180° Continuous Tilt with Auto Flip

Preset Positions 256

Patterns 4 Pattern, 8 Scan Routes and 8 Cruise Lanes

Park ActionSupportWeb-clientSupportONVIFSupport

IP Rate IP66 Water-proof and Dust-proof



MZ-20IPM-2(IR)

SURCIP-PROP003

























Camera IP PTZ 2MP X25 Zoom high speed Pan/Tilt/Zoom IR 100m distance with DDA Analytics (Including Bracket)

IR Range Smart IR Distance: 100m
Image Enhancement 3D-DNR Noise Reduction

Compression H.265

Analytics DDA™ Analytics with Auto-Tracking, Face Recognition Analytics

Preset speed 80°/sec (max), Preset accuracy: up to 0.1°

Pan Endless 360° Pan Rotation

Tilt 180° Continuous Tilt with Auto Flip

Preset Positions 300

Patterns 4 Pattern, Scan Route, and 8 Cruise Lanes

Park ActionSupportWeb-clientSupportPower-Off MemorySupportSD CardSupport

IP Rate IP66 Water-proof and Dust-proof

Power PoE+ (802.3at) / DC12V/~480mA (Not included)

Wall Bracket Included



Z4-25IPE-2(IR)

























Camera IP PTZ 2MP X25 Zoom high speed Pan/Tilt/Zoom IR 150m distance with DDA Analytics (Including Bracket)

IR Range Smart IR Distance: 150m
Image Enhancement 3D-DNR Noise Reduction

Compression H.265

Analytics DDA Analytics with Auto-Tracking, Face Recognition Analytics

Preset speed 120°/Sec (max)
Preset accuracy up to 0.1°

Pan Endless 360° Pan Rotation

Tilt 180° Continuous Tilt with Auto Flip

Preset Positions 300

Patterns 4 Pattern, Scan Route, and 8 Cruise Lanes

Park Action Support
Web-client Support
Power-Off Memory Support
SD Card Support
Audio In/Out Support
Alarm In/Out Support

IP Rate IP66 Water-proof and Dust-proof

Power PoE+ Wall Bracket Included



Z5-25IPE-2(IR)

SURCIP-PROP009

























Camera IP PTZ 4MP X25 Zoom high speed Pan/Tilt/Zoom IR 100m distance with DDA Analytics (Including Bracket)

IR Range Smart IR Distance: 100m
Image Enhancement 3D-DNR Noise Reduction

Compression H.265

Analytics DDA™ Analytics with Auto-Tracking, Face Recognition Analytics

Preset speed Preset speed of 80°/Sec (max)

Preset accuracy up to 0.1°

Pan Endless 360° Pan Rotation

Tilt 180° Continuous Tilt with Auto Flip

Preset Positions 300

Patterns 4 Pattern, Scan Route, and 8 Cruise Lanes

Park ActionSupportWeb-clientSupportPower-Off MemorySupportSD CardSupport

IP Rate IP66 Water-proof and Dust-proof

Power PoE+

Wall Bracket Wall Bracket included



Z4-25IPE-4(IR)

























Camera IP PTZ 4MP X25 Zoom high speed Pan/Tilt/Zoom IR 150m distance with DDA Analytics (Including Bracket)

IR Range Smart IR Distance: 150m Image Enhancement 3D-DNR Noise Reduction

Compression H.265

Analytics DDA Analytics with Auto-Tracking, Face Recognition Analytics

Preset speed 120°/Sec (max) **Preset accuracy** up to 0.1°

Pan Endless 360° Pan Rotation

Tilt 180° Continuous Tilt with Auto Flip

Preset Positions 300

Patterns 4 Pattern, Scan Route, and 8 Cruise Lanes

Park Action Support Web-client Support **Power-Off Memory** Support

SD Card SD Card Support

Audio In/Out Support Alarm In/Out Support

IP Rate IP66 Water-proof and Dust-proof

Power PoE+ **Wall Bracket** Included



Z5-25IPE-4(IR)

SURCIP-PROP010





















Camera IP PTZ 4MP X32 Zoom high speed Pan/Tilt/Zoom IR 200m distance with DDA Analytics (Including Bracket)

IR Range Smart IR Distance: 200mB3:B20 Image Enhancement 3D-DNR Noise Reduction

H.265 Compression

Analytics DDA Analytics with Auto-Tracking, Face Recognition Analytics

240°/Sec (max) **Preset speed Preset accuracy** up to 0.1°

Endless 360° Pan Rotation Pan Tilt 220° Continuous Tilt

Preset Positions

Patterns 4 Pattern, Scan Route, and 8 Cruise Lanes

Park Action Support Web-client Support **Power-Off Memory** Support **SD Card** Support Audio In/Out Support Alarm In/Out Support

IP Rate IP66 Water-proof and Dust-proof

Power PoE++ **Wall Bracket** Included



Z6-32IPE-4(IR)





























Vari-Focal F1.5 CS mount 1/1.8" P-IRIS 3.6mm-10mm 6MP lens

Details

6 Mega-Pixel Lens Auto Iris Lens 3.6-10mm Vari-Focal



SURZSU-PRO003

Vari-Focal DC Auto Iris 2.8-12mm 3MP lens

Details 3 Mega-Pixel Lens

Auto Iris Lens 2.8~12mm Vari-Focal Suitable for 1/2.9" Sensors



02812DCMP-3

SURZSU-PRO002



Monitor 10.1 inch Standalone LCD with IP5 panel HDMI & VGA White shell

Details Screen Size: 10" TFT Screen

Resolution: 1024x600 TV System: PAL / NTSC Power Supply: DC 12V, 1A Video Input: 1VP-P, 750hm

Inputs: AV1, AV2, VGA, HDMI, Power Work Temperature: -10° C \sim 60°C Viewing Angle: 85° (All Directions)

Contrast Ratio: 300:01:00 Brightness: 350CD/m2

Weight: 1.2Kg

Dimension: 250W x 163H x 16D mm



PR-IPS10-W

SURMON-PRO004

Tester 4.3 inch AHD/TVI/CVI/CVBS with RS485 up to 8MP with EU & US socket

Details 4.3" TFT LCD Display

8MP 4 in 1 support: AHD / CVI /TVI / CVBS

CoC Support

Image settings support

Installation without external Power Source:

12VDC Ouput (Plug Supplied)

5VDC Output (Micro USB Plug Supplied)

Network Cable Tester Included Audio in with Built-in Speaker

PAL/NTSC Support Status LED Indicators

Built-In Long-Life Rechargeable Battery Hands Free Operation (Arm strap supplied)

Light Weight



TM-434In1-8

TOOCCT-PRO01268























Power supply DC 12V 5A with 4 channel terminal block

Details 12V 5A power supply - 4 DC Terminals.

High efficiency and environmental friendly design

Optimal design for easy installation

Stable power signal to support clear images

Full AC Input range: AC100~240V Output Voltage: DC12V±5% Over-current protection Short circuit protection Auto Recovery



PR-12V5A-4T

POWDPS-016

Power Supply 12V 3A

Details 12V 3A power supply - 1 DC Plug.

High efficiency and environmental friendly design

Optimal design for easy installation

Stable power signal to support clear images

Full AC Input range: AC100~240V Output Voltage: DC12V±5% Over-current protection Short circuit protection

Auto Recovery



PR-12V3A

POWDCP-12V3A011



Power supply Provision ISR 12V 20A Professional Rack mountable for 16CH

Details High efficiency and environmental friendly design

Optimal design for easy installation

Stable power signal to support clear images

Over-current protection

"Over-voltage" output protection

Short circuit protection

Lock

Individual Status LED for each Channel

Thermal Fuses



PR-20A16CH(1U)

POWDPS-PRO018

Power supply Professional 9CH 12V/10A with socket

Details High efficiency and environmental friendly design

Optimal design for easy installation

Stable power signal to support clear images

Over-current protection

"Over-voltage" output protection

Short circuit protection

Lock

Individual Status LED for each Channel

Thermal Fuses



PR-10A9CH+

POWDPS-PRO001



Power supply Professional 9CH 12V/10A with room for backup battery with socket

Details High efficiency and environmental friendly design

Optimal design for easy installation

Stable power signal to support clear images

Over-current protection

"Over-voltage" output protection

Short circuit protection

Lock

Individual Status LED for each Channel

Thermal Fuses

Backup Battery Support (Backup Battery not included)



PR-10A9CH-B

POWDPS-PRO017

Power supply Professional 16CH 2V/12A with socket

Details High efficiency and environmentally friendly design

Optimal design for easy installation

Stable power signal to support clear images

Over-current protection

"Over-voltage" output protection

Short circuit protection

Lock

Individual Status LED for each Channel

Thermal Fuses DC12V/12A



PR-12A16CH+

POWDPS-PRO002



Junction box for I6-/DI-VF IP66

Details Large Water-proof Junction Box

Weight: 512 g

Dimensions: 139.3x50 mm

Suitable for:

16 New Bullet Camera (All Models)

DAI-VF New Dome Anti-Vandal Camera (All Models)
DI-VF New Turret Dome Camera (All Models)



PR-JB14IP66

SURZSU-PRO015

Junction box for I4-/I2-/DI-Fix IP66

Details Small Water-proof Junction Box

Weight: 380 g

Dimensions: 117.9x47 mm

Suitable for:

14 New Bullet Camera (All Models)12 New Bullet Camera (All Models)

DAI-Fixed Lens New Dome Anti-Vandal Camera (All Models)
DI-Fixed Lens New Turret Dome Camera (All Models)



PR-JB12IP66

SURZSU-PRO014

Junction Box Small

Details Suitable for:

Bullet Camera with Fixed Lens Eyeball camera with Fixed Lens



PR-B37JB

SURZSU-PRO005

Security Superstore Shelly Beach saleshc@securitysperstore.co.za 072 250 7822



Junction Box Small Plastic for AHD cameras

Details Suitable for:

Bullet camera with fixed lens Eyeball camera with fixed lens Bullet camera with fixed lens



PR-B42PJB

SURZSU-PRO007

Junction Box Waterproof for IP models I4/I5/I8/DI for AHD models DI VF lens

Details Suitable for:

Eyeball camera with VF lens Bullet Camera with VF/MVF lens Eyeball camera with VF lens



PR-B55JB

SURZSU-PRO009

DC Jack Male

Details DC jack male.



PR-C08

CABDCJ-002

Security Superstore Shelly Beach saleshc@securitysperstore.co.za 072 250 7822



DC Jack Female

Details

DC jack female..



PR-C09

CABDCJ-004

DC Cable (25 cm length)

Details

DC cable (25 cm length).



PR-C10

CABDCJ-001

DC Cable Female (15 cm)

Details

DC cable female (15 cm).



PR-C11

CABDCJ-003





USB ALARM EXPANSION BOX 16CH ALARM INPUT 6CH ALARM OUTPUT

Details 6 Ala

6 Alarm Inputs (Dry Contact)6 Alarm Output (Dry Contact)

USB Interface Power LED Indicator



I/O-1606

SURZSU-PRO019

Active Horn Speaker 30W 12V-24V with 3.5mm stereo male sound input Vol control

Details Total Distortion: 5% Max at 1KHz 1W

Resonance Frequency: 700 \pm 15%Hz at 1V, 25 °C Rated Frequency Range: 300Hz $^\sim$ 5.5K Hz (-20dB band) Sound Pressure Level: 112 \pm 3dB 1w/m @ 1K Hz

Rated Impedance: ACR 8 Ohm

Work Environment: Temperature -20°C~+40°C, Humidity

45%~85%

Dimensions: $285(W) \times 205(H) \times 280(L)mm$

Weight: 2.1kg ± 10% Power Input: 12VDC/2A



PR-HS30W

SURZSU-PRO020



Wall pendant mount bracket for PTZ

Details Suitable for: New PTZ Line



PR-WB-Z

SURZSU-PRO018