

Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

1 Identification

Product identifier

- Trade name: POWERFOAM
- · Application of the substance / the mixture One-component polyurethane foam hand held

Details of the supplier of the safety data sheet

· Manufacturer/Supplier: **DEWALT Industrial Tools** 701 East Joppa Road Towson, MD 21286 USA

· Information department: Telephone: 800-524-3244

- · Emergency telephone number:
- CHEMTREC: 800-424-9300 (within continental USA) CHEMTREC: +1 703 527-3887 (outside USA)

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1

Sensitization - Skin 1

Carcinogenicity 2

Acute Toxicity - Inhalation 4 Skin Irritation 2 Eye Irritation 2A Sensitization - Respiratory 1 H222 Extremely flammable aerosol.

- H229 Pressurized container: May burst if heated.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Single Exposure 3 Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to organs through prolonged or repeated exposure. 2

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

diphenylmethanediisocyanate, isomeres and homologues

Hazard statements Extremely flammable aerosol.

Pressurized container: May burst if heated.

(Contd. on page 2)

US



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

Harmful if inhaled. ((Causes skin irritation.	Contd. of page 1)
Causes serious eye irritation.	
May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an a reaction.	llergic skin
Suspected of causing cancer.	
May cause respiratory irritation.	
May cause damage to organs through prolonged or repeated exposure.	
· Precautionary statements	
Obtain special instructions before use.	
Keep out of reach of children.	
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No sn	nokina.
Do not spray on an open flame or other ignition source.	
Do not pierce or burn, even after use.	
Do not breathe vapours/spray.	
Wear protective gloves/protective clothing/eye protection.	
In case of inadequate ventilation wear respiratory protection (a protective mask with an ap	propriate das
filter - i.e. type A1 according to standard EN 14387).	, i 3
If on skin: Wash with plenty of water/soap.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese	ent and easy
to do. Continue rinsing.	5
IF exposed or concerned: Get medical advice/attention.	
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Dispose of container to in accordance with local/regional/national/international regulation.	
Additional information:	
Persons already sensitised to diisocyanates may develop allergic reactions when using this	s product.
Persons suffering from asthma, eczema or skin problems should avoid contact, including c	
contact, with this product. This product should not be used under conditions of poor ventila	
protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387	is used.
Contains isocyanates. May produce an allergic reaction.	
Information pertaining to particular dangers for man and environment	t:
· NFPA ratings (scale 0 - 4)	
Health = 1	
Fire = 0	
3 Reactivity = 3	
· HMIS-ratings (scale 0 - 4)	
HEALTH 1 Health = 1	
FIRE 0 Fire = 0	
$\frac{1}{100} = 3$	
[·] Other hazards	
· Results of PBT and vPvB assessment Not applicable.	

3 Composition/information on ingredients

[•] Chemical characterization: Mixtures

 \cdot **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

⁻US



Safety Data Sheet acc. to OSHA HCS

Printing date 02/14/2023

Reviewed on 02/14/2023

Trade name: POWERFOAM

	(Contd. of page 2)	
Dangerous comp	ponents:	
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	35-45%
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate	10-15%
CAS: 75-28-5	isobutane	1-10%
CAS: 115-10-6	dimethyl ether	1-10%
CAS: 74-98-6	propane	1-10%

4 First-aid measures

[•] Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Immediately call a doctor.
- · Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

[•] Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Carbon monoxide (CO) Nitrogen oxides (NOx) Hydrogen cyanide (HCN)
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

(Contd. of page 3) [•] Environmental precautions: Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. Do not allow product to reach sewage system or any water course. Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals · PAC-1: CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 0.15 mg/m³ 5500* ppm CAS: 75-28-5 isobutane CAS: 115-10-6 3,000 ppm dimethyl ether CAS: 74-98-6 propane 5500* ppm · PAC-2: CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 3.6 mg/m³ CAS: 75-28-5 isobutane 17000** ppm CAS: 115-10-6 dimethyl ether 3800* ppm 17000** ppm CAS: 74-98-6 propane · PAC-3: CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 22 mg/m³ CAS: 75-28-5 isobutane 53000*** ppm CAS: 115-10-6 dimethyl ether 7200* ppm CAS: 74-98-6 33000*** ppm propane

7 Handling and storage

[·] Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

- [•] Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility:
- Store away from oxidizing agents.

(Contd. on page 5)

US



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

(Contd. of page 4) Do not store together with akalis (caustic solutions). • Further information about storage conditions: Keep receptacle tightly sealed. Store in dry conditions. Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. • Storage class: 2B • Specific end use(s) No further relevant information available. • Additional information about design of technical systems: No further data; see item 7.

[•] Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

CAS: 115-10-6 dimethyl ether

WEEL Long-term value: 1000 ppm

· Additional information: The lists that were valid during the creation were used as basis.

• Exposure controls

Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

(Contd. of page 5)

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical pro	operties
 Information on basic physe General Information Appearance: Form: Color: Odor: 	Aerosol According to product specification Characteristic
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	235 °C (455 °F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Heating may cause an explosion.
 Explosion limits: Lower: Upper: 	1.8 Vol % 8.5 Vol %
· Vapor pressure at 20 °C (68 °F)	: 3000 hPa (2,250.2 mm Hg)
· Density:	Not determined.
 Solubility in / Miscibility with Water: 	Insoluble.
 Solvent content: VOC content: 	22.2 % 213,3 g/l
[•] Other information	No further relevant information available.

10 Stability and reactivity

[.] Reactivity No further relevant information available.

(Contd. on page 7)

US



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

(Contd. of page 6)

- [•] Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- [•] **Incompatible materials:** No further relevant information available.
- [•] Hazardous decomposition products:

Nitrogen oxides (NOx) Hydrogen cyanide (prussic acid) Carbon monoxide

11 Toxicological information

[•] Information on toxicological effects

• Acute toxicity:

- · LD/LC50 values that are relevant for classification:
- CAS: 115-10-6 dimethyl ether
- Inhalative LC50/4 h 308 mg/l (rat)

CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate

- Oral LD50 3,600 mg/kg (rat)
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization:
- Sensitization possible through inhalation.
- Sensitization possible through skin contact.
- Subacute to chronic toxicity:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- [·] Toxicity
- Aquatic toxicity: No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- [•] Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 8)

3



Trade name: POWERFOAM

(Contd. of page 7)

Reviewed on 02/14/2023

[•] Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Safety Data Sheet acc. to OSHA HCS

- [•] Results of PBT and vPvB assessment Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

[•] Waste treatment methods

· Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

[•] Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

UN-Number		
DOT	UN1950	
IMDG, IATA	1950	
UN proper shipping name		
DOT	Aerosols, flammable	
IMDG, IATA	AEROSOLS	
Transport hazard class(es	;)	
DOT, IMDG, IATA		
Class	2.1 Gases	
Label	2.1	
Packing group		
DOT, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for us	ser Warning: Gases	
EMS Number:	F-D,S-U	
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

(Contd. of page 8)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

• TSCA (Toxic Substances Control Act):

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

CAS: 115-10-6 dimethyl ether

CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

D;CBD

· TLV (Threshold Limit Value)

None of the ingredients is listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

diphenylmethanediisocyanate, isomeres and homologues

Hazard statements Extremely flammable aerosol.

Pressurized container:May burst if heated.

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/14/2023

Trade name: POWERFOAM

(Contd. of page 9) Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. **Precautionary statements** Obtain special instructions before use. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe vapours/sprav. Wear protective gloves/protective clothing/eye protection. In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387). If on skin: Wash with plenty of water/soap. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of container to in accordance with local/regional/national/international regulation. **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out. 16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact:

- · Date of preparation / last revision 02/14/2023
- Abbreviations and acronyms:
 Flammable Aerosols 1: Aerosols Category 1
 Acute Toxicity Inhalation 4: Acute toxicity Category 4
 Skin Irritation 2: Skin corrosion/irritation Category 2
 Eye Irritation 2A: Serious eye damage/eye irritation Category 2A
 Sensitization Respiratory 1: Respiratory sensitisation Category 1
 Sensitization Skin 1: Skin sensitisation Category 2
 Specific Target Organ Toxicity Single Exposure 3: Specific target organ toxicity (single exposure) Category 2 Aspiration Hazard 1: Aspiration hazard Category 1

US