

A920MAX

SPLENDID Smart Mobile



Food & Beverage



Fashion & Retail



Transportation



Paydroid Powered
by Android 10



PCI PTS 6.x
SRED



HD+ Display
Gravity Sensor



Up to 13MP
Rear-Facing






















5G or 4G
Connectivity

SMARTPOS



SPECIFICATIONS

| | | |
|---|-----------------------------|---|
|  | Operating System | PayDroid Powered by Android 10 |
|  | Processor | Cortex A53 Quad-Core, 1.3GHz + Secure Processor |
|  | Memory | 4G Version: 1GB DDR3 RAM + 8GB eMMC Flash (Optional: 2GB+16GB) 5G Version: 2GB DDR3 RAM Extended + 16GB eMMC Flash (Optional: 3GB+32GB / 4GB+64GB) Extended MicroSD Card Slot up to 128GB |
|  | Card Readers | Chip & PIN Contactless Magnetic Stripe |
|  | Cameras | 5MP AF Rear Camera with Flashlight Optional: 8MP/13MP AF Rear Camera Optional: 0.3MP Top-Side Professional Barcode Scanner |
|  | Displays | 4G Version: 6" IPS HD+ Multi-Point Capacitive Touch Screen 5G Version: 6.5" IPS HD+ Multi-Point Capacitive Touch Screen with Gravity Sensor |
|  | Comms Configurations | 5G + WiFi 2.4GHz/5GHz + Bluetooth 5.0 4G + WiFi 2.4GHz/5GHz + Bluetooth 5.0 |
|  | Battery | 2500mAh 6.4V, 16Wh (Equivalent 5000mAh 3.2V) |
|  | Printer | 80mm/Sec Paper Roll Outer Diameter: 40mm |
|  | SIM / SAM | 1 Micro SIM + 2 PSAM Optional: 1 Micro SIM + 1 Mini SIM + 1 PSAM Optional: eSIM |
|  | Positioning | AGPS GPS GLONASS BEIDOU Galileo |
|  | Keys / Buttons | 4 Keys: Power ON/OFF Volume+ Volume- Quick Scan Button |
|  | Audio | 1 Buzzer 1 Speaker 1 Microphone |
|  | Ports | 1 Type C USB OTG 6 PIN POGO PIN |
|  | Adapter | Input: 100 - 240V AC, 50Hz / 60Hz Output: 5.0V DC, 2.0A |
|  | Physical | 186.3 x 80 x 54.9mm, 413g (Including Battery) |
|  | Accessories | 5V/2A Adapter USB Type C Charging Cable Optional: L920MAX-BC: Charging Base Optional: L920MAX-BM: Charging +Multi-Functional Base Optional: L920MAX-BE: Charging + Wireless Communication Base |
|  | Environmental | 0°C ~ 45°C (32°F ~ 113°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing |
|  | Certifications | PCI PTS 6.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless UPI qIICS Amex ExpressPay Discover D-PAS JCB J/Speedy Interac Flash TQM CE RoHS FCC IC UL PTCRB PURE CB |

