

Designed to give an ergonomic and flexible mounting platform for your payment terminal and prevent damage due to the traditional "back and forth" movements with each transaction.

## **Features**

Manufactured in robust mild steel
Durable powder coated finish
Smooth 60° tilt and 190° swivel action
Dual cable entry options
Flange cover to conceal fixing holes
Freestanding base plate with rubber feet
Stand supplied fully built for a simple install
Plate attaches easily to stand with enclosed screws
Upgradeable in the field with a simple top plate swap



## FREESTANDING VERSION TO SUIT CLOVER MINI

## **Installation instructions**

- 1. Select the desired position for your payment terminal.
- 2. Fix the terminal stand to the free standing base plate using the 4 off M5 screws provided
- 3. Place the full unit on the countertop and choose whether the unit is best swiveling clockwise or anticlockwise.
- 4. Position the base plate so that sufficient access can be gained to the terminal by both the customer and vendor when the unit is swiveled through its 190°.
- 5. If the cables are to be fed through the bottom of the base pole then drill a large hole in the countertop to accept them. This is not necessary if the countertop cable

entry is to be used.

- 6. With the power switched off, feed the cables through the desired base pole entry and up through the top exit of the pole. Ensure that sufficient cable length is fed through the top of the pole to allow connection to the terminal.
- 7. Connect the cables to the payment terminal.
- 8. Fit the payment terminal onto the cradle plate and fit the two M6 screws to secure in place as per the adjacent image.
- 9. Switch on the terminal power supply.

Illinois 60035

1530 Old Skokie Rd

**Highland Park** 

Tel: 877 298 6939