

# **DISCOUNT**

## **CREDIT CARD SUPPLY**

DCCSUPPLY.COM [SALES@DCCSUPPLY.COM](mailto:SALES@DCCSUPPLY.COM) 847-266-1220

### **First Data FD35/FD40 Protective Spill Cover Installation Instructions**

#### **CONGRATULATIONS!**

**You have made a great choice to protect your device from spills, bacteria, and grime while extending the life of your Terminal/PIN Pad!**

#### **Instructions:**

1. Gently lay the spill cover over the device making sure the top left corner of the cover hugs the device.
2. VERY IMPORTANT STEP: Pull the left side of the spill cover down on the left side of the device so it is snug/flush with the side of the device.
3. Remove the white Mylar adhesive strip on this left side, taking care not to remove adhesive from the cover.
4. Gently stretch the cover across the device from left to right so that the cover lines up with the keys while smoothing out the cover.
5. Remove the white Mylar adhesive strips in this specific order to get the best adhesion:  
1.Left side 2. Middle 3. Top 4. Bottom 5. Right
6. Finish by smoothing down the bubbles and adjusting the fit.

**And now your PIN Pad is protected!**

#### **Tips for Care and Use**

- This cover is durable, but it is made of plastic, so treat it gently.
- Do not use sharp objects or pens as they may puncture the cover.
- Clean with a damp cloth or antibacterial wipe. Do not remove the cover to clean it.