# Link/2500

Smart, sleek, simple.
Payment excellence at its finest





JSA-CAN\_DATASHEET\_LINK\_2500\_ING\_221110. All rights reserved. This document is not binding and the specifications above can be modified without prior consent. ©2022



# With the Link/2500, Ingenico brings payment acceptance solution to any mobile solution.

## **Highest security**

The Link/2500 is PCI-PTS 5.x certified. Its Telium Tetra OS uses the latest cryptographic schemes with future-proof key length.

#### All payment options

In addition to EMV Chip & PIN, swipe and sign, Link/2500 supports the broadest range of contactless standards allowing NFC couponing and wallet use cases.

### **Designed for accessibility**

Thanks to an integrated speaker which could provide vocal assistance and a real mechanical keypad with raised marking, Link/2500 is built for the most demanding use.

#### **Designed for mobility**

Featuring a pocket-sized, light weight and robust design the Link/2500 is the perfect business acceptance point for mobile solutions.

### User-friendly and intuitive interface

Featuring a sleek design, Link/2500 is versatile and intuitive thanks to a bright 2.4" color display and a USB-C connector.

#### **Secure Telium TETRA OS**

Backed by 40 years of experience and with its userfriendly interface, the Telium TETRA operating system includes the best security mechanisms embedded to protect transaction privacy and leverages Ingenico's unique portfolio of payment applications.

### Compatible with Ingenico's suite of services

Keeping the solutions connected, the Link/2500 works in unison with Ingenico's supporting service platforms, meaning merchants will have access to business services such as estate management reporting. Software updates and day-to-day support deliver a hassle-free experience.



The Link/2500 is supported by our Cloud Services

			LINK/ 2500 Standard	LINK/ 2500 (Integration)
Processor	Application     & Crypto processor	• Cortex A5	~	<b>∀</b>
Memory	• Internal	• 256 MB Flash, 128 MB RAM	<b>⋄</b>	<
os		Telium TETRA	<b>▽</b>	<b>✓</b>
SIM / SAM		• Up to 2	Optional	N/A
Card Readers	Magstripe     Smart card     Contactless	ISO 1/2/3, 500K lifespan     EMV Level 1,     50K lifespan     EMV / iSO14443	<ul><li>✓</li><li>✓</li></ul>	· · · · · · · · · · · · · · · · · · ·
Display	• Color	2.4" color display, backlit, QVGA (240×320 pixels)	<b>✓</b>	<b>✓</b>
Keypad	Mechanical	20 keys, raised marking	~	<
Audio	Buzzer     Speaker		<b>y</b>	V N/A

· Host and Device (Both)

· USB power/data & serial

docking pads (2500i)

N/A

			LINK/ 2500 Standard	LINK/ 2500 (Integration)
Terminal Connectivity	LAN     Apple iAP2 Chip	Bluetooth class II     WiFi (Dual band)	<b>&gt; &gt; &gt;</b>	N/A
Terminal Size	• L x W x H	• 5.07 × 2.75 × 0.67" (129 × 70 × 17 mm) • 5.07 × 2.75 × 0.59" (129 × 70 × 15 mm)	✓ N/A	N/A
Power Supply	• Terminal	• 5V 1A	Optional	Optional
Battery	• Li-ion	***************************************	1200mAh (removable)	600mAH
Weight	• Full featured		5.46 oz (155g)	5.89 oz (167g)
Environment	Charging Temperature Operating Temperature Storage Temperature Operating Humidity	• 32°F to 104°F (0°C to +40°C) • -14°F to 122°F (-10°C to +50°C) • -4°F to 131°F (-20°C to +55°C) • 85% non-condensing at 104°F (+40°C)	<ul><li></li><li></li><li></li></ul>	<ul><li></li><li></li><li></li><li></li><!--</th--></ul>
Accessories	Cable     iCON Case	• USB A to USB C: 1.5m	Bluetooth	Optional  Bluetooth & USB
Security		PCI PTS v5.x online & offline certified	<	<b>▽</b>



Terminal Connections

• USB Type C

