

Installation Guide

Estimated time to completely install the system is 3.5 hours.

STEP 1



The Switch Panel is small enough

and can be mounted almost

anywhere on the dash.

STEP 2



Install Mist Controller Mounts 1" Aluminum Angle Bar (Top) 1" Aluminum Square Bar (Bottom)

STEP 3



Mount Mist Controller

NOTE: Installation was performed on an older ClubCar.Mist Controller location may differ on other carts.

Final Steps

STEP 1



Connect red wire to positive and black wire to negative of 12vdc source





Add water



Remove front cover (4 bolts)

STEP 1



Drill 2" hole in Dash

STEP 2

Mist Controller mounting holes are

11.5"W x 6"H. Mounting brackets

should be installed to meet

those specifications.



Prepare for Switch Panel by using a file on the sides of the hole to widen hole to accept switch.

STEP 3




Insert Switch Panel



Connect Switch Cable to Mist Controller

STEP 4

STEP 1



Panel

Switching



Locate Water Bottle

STEP 2



Mount Water Bottle

STEP 3



Drill 7/8" hole in floor board **Insert Grommet** Push Dual Tubing through hole

STEP 4



Connect both Blue and Black Tubing

STEP 5



Run Tubing under cart and connect Tubing to the Mist Controller

STEP 1



Locate misting fan by drilling 1/4" hole

STEP 2



Install mounting bracket

STEP 3



Install Mister Fan to bracket

STEP 4



Drill 7/8" hole/install grommet in both sides of front cover

STEP 5



Push tubing/power cable through grommet to Mist Controller

STEP 6



Connect blue tube to water/black tube to air/power cable to power (each side)

STEP 3



Adjust mister fan up/down lock in place

Complete and ready for Cool Misting.