




77020

GALLERY



PRODUCT ATTRIBUTES

Brand	Expamet
Generic Ref	770
Product Range	Wall Ties

Product Sub-range	Bed Joint Reinforcement
Product Type	Crack Control Expanded Mesh Reinforcement
European Standard/ETA	BS EN845-3:2013+A1:2016
Material	Stainless Steel 1.4301 to BS EN10088-2:2014
Coating/Finish/Colour	Mill Finish
Length 1/Projection	20m
Width/Wing Length	175mm
Plaster/Render/Joist depth	10-12mm Bed Joint Thickness
Material Gauge	0.3mm
Individual Weight (kg)	1.82
Fire Rating	Euroclass A1
Installation requirement 1	Mesh must be bedded and covered in fresh mortar before laying course above
Installation requirement 2	Overlap ends by 75mm
Installation requirement 3	Use at maximum 225mm vertical centres, providing a 600mm projection beyond jambs
Unit of Sale EAN	5014316527705
Sales Qty	1
Packaging material	0
Packaged transit weight	1.82
Features/Benefits 1	Used to reduce cracking in masonry around areas of high stress e.g. windows or doors
Features/Benefits 2	No joints, interweaving or welds to fail under stress
Features/Benefits 3	Can easily be cut to size using tin-snips or aviation cutters

HEALTH AND SAFETY INFORMATION

1. Identification

'Expamet'
Birtley Group Ltd
Mary Ave,
Birtley,
DH3 1JF
UNITED KINGDOM
(0191) 410 6631

2. Composition

Stainless Steel 1.4301 to BS EN10088-2:2014

3. Hazards Identification

Possible cuts from sharp steel edges.
Toxic and irritant fumes from high temperatures

4. First aid measures

Skin and eye contact: Treat cuts from steel edges as required.
Ingestion: Not applicable.
Inhalation: Remove from source of fumes and dust.

5. Fire fighting measures

Non-flammable material.

6. Accidental release measures

Not applicable.

7. Handling and storage

Bands and straps must not be used for lifting.
Use suitable PPE when handling products.
Assess manual handling risks before lifting.
Products should be stacked on firm level ground in dry conditions.

8. Exposure controls

Wear personal protection such as gloves and safety goggles when handling products.
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene including proper washing of hands, after contact.

9. Physical and chemical properties

Products are supplied in various lengths, widths and gauges.
Metallic grey appearance.

10. Stability and reactivity

Products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

11. Toxicological information

High temperatures can produce fumes.

12. Ecological information

No known Hazard.

13. Disposal considerations

Recycle or dispose of in accordance with Waste Management Licensing Regulations.

14. Transport information

Not classified as hazardous for transport.

15. Regulatory information

Products are articles and have no registration obligation under REACH.

16. Other information

All products must be installed in accordance with Expamet Building Products' published instructions.

Where structural products are to be removed from an existing installation, care must be taken to ensure that the procedure followed does not compromise the loading/installation restrictions applicable to the products.

Actual fixing installations must comply with current Health and Safety requirements.