IMORTANT Read these instructions before installing and using this product.



Failure to follow the instructions and safety precautions in this manual can result in serious injury or death.

"V" Grip Handlebar and Tube Mount



Keep these instructions in a safe location for future reference **Tools needed:** 2-7/16" wrenches

Mounting Instructions:





1. Determine where on the front or rear rack of the ATV you want to mount the racks. Next we recommend placing the Forks on the gun, bow or other item you intend to carry in the rack. This will help you determine how far apart to space the racks on your ATV.

For Guns the racks should be usually be spaced about 18" to 22" inches apart and be placed on the gun at the pistol grip area and fore-end area.

For bows the limbs should be placed in the bow limb slot as close to the riser as possible



2. Place the Low Profile Mounting Block on the tube you want to mount it too. Place the "U" bolt through the 2 holes on either side of the "V" of the Mounting Block.



Tighten the nylock nuts on the ends of the "U" Bolt. Alternate while tightening to ensure even pressure.

- 3. To attach "V" Grip Fork to the low profile mounting block, first screw the handle nut on the 3/8" mounting stud. Then place the 3/8" mounting stud through hole on the top of the mounting block. Tighten the handle nut to lock the fork in the desired position.
- 4. Place the item you want to carry in the forks. For a better fit, the Forks can be rotated 360 degrees.
- 5. Place the snubber into one of the three mounting positions on the Fork that will best hold your item. Pull the snubber over the item to the opposite side and secure it into one of the three mounting positions on that side. Always insure your item is strapped in securely.