



AUTOPA's range of Plain Round Bollards offers a simple and cost effective means of establishing control over parking and access. Plain Round bollards are ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The complete range of Plain Round Bollards is available in diameters from 48mm to 406mm and is available with extended legs for casting into concrete or with a flange plate for bolting down.

Colour coated options and removable versions are also available.

Plain Round Bollard 1000mm Above Ground

Galvanised

Product details

- 3mm wall thickness
- Concrete in 300mm (below ground)
- 3 bolts required per bollard (bolt down)
- Round flange plate – 133mm x 5mm – 48mm and 60mm diameters
- Round flange plate – 180mm x 5mm – 76mm to 114mm diameters

Installation & use

Bolt down to a suitable concrete surface.
 Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.
 Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.
 Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
 +44 (0)1788 550556

AUTOPA Limited
 Cottage Leap, Rugby, Warwickshire CV21 3XP

