Carat House In-Direct Package





Carat House In-Direct package

- Simple & quick to install
- Submersible pump supplies harvested rainwater on demand to the header tank where it is then gravity-fed to the WCs & washing machine
- The header tank controls the operation of the system, supply of harvested rainwater and backup mains water to the WCs
- Dual valve system within the header tank prioritises rainwater supply over mains water, maximising the use of all available rainwater to save on mains water consumption
- Mains water switchover point is at a lower level in the header tank and becomes operational when rainwater is not available from the underground Platin tank
- Mains water backup supply is not reliant on power supply or pump pressure and therefore guarantees supply of water to WCs at all times

Scope of supply

- Underground tank (choice of tanks available, sizes vary according to property type)
- 2 Telescopic lid (choice of telescopic lid available, depending on tank location)
- Minimax filter supplied in accordance with type of tank
- 4 Submersible pump with floating water intake
- § Float switch (connected from mains water backup unit to the underground tank)
- 6 Header tank package

Supplied by others

- 100mm diameter duct pipe to contain; float sensor cable, power cable for pump
- (8) 100mm diameter drainage pipe connected from downpipes to the inlet at the top of the tank (all downpipes brought into one pipe for connection to the filter)
- ① 100mm diameter pipe for overflow from the tank to mains drainage network or soakaway

| Dimensions/weight | 2,700 litres (700 US gallons) | 3,750 litres (1,000 US gallons) | 4,800 litres (1,250 US gallons) | 6,500 litres (1,700 US gallons) |
|-------------------|-------------------------------|---------------------------------|---------------------------------|---------------------------------|
| Length (I) | 2,080mm (81.9") | 2,280mm (89.8") | 2,280 (89.8") | 2,390 (94.1") |
| Width (w) | 1,565mm (61.6") | 1,755mm (69.1") | 1,985mm (78.2") | 2,190mm (86.2") |
| Height (h) | 2,010mm (79.12") | 2,200mm (86.6") | 2,430mm (95.65") | 2,710mm (10.68") |
| Ø tank dome (d) | 800mm (31.5") | 800mm (31.5") | 800mm (31.5") | 800mm (31.5") |
| Weight | 120kg | 150kg | 185kg | 220kg |



