

## Technical Datasheet

Lotrak<sup>®</sup> Base is a woven polypropylene geotextile suitable for use as a basic separator fabric in a wide range of civil engineering applications. The main purpose of this geotextile is to prevent the loss of construction aggregates into the underlying soil.

TEST	STANDARD		BASE
Tensile Strength (kN/m)	EN 10319	<b>Warp</b>	10
		<b>Weft</b>	9
Elongation at max. load (%)	EN 10319	<b>Warp</b>	22
		<b>Weft</b>	15
CBR Puncture Resistance (N)	EN ISO 12236		1500
Cone Drop Penetration (mm)	EN 918		18
Pore Size 90% finer than (microns)	EN ISO 12956		200
Water Permeability $V_{I_{H50}}$	EN ISO 11058		0.010
Water Flow Rate (l/m <sup>2</sup> /sec)	EN ISO 11058		10
Effect of UV Light	The polypropylene (PP) used contains a UV inhibitor		
Roll Size (m)		<b>Width</b>	4.5
		<b>Length</b>	100



### All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2022. The intellectual property in the products is owned and protected by Don & Low or its licensors.