

MSDS#: KIP071103-VAP

Material Safety Data Sheet VERSACRYL ACRYLIC POLYMER Page 1 of 5

Section I - Product and Company Identification

Product Name: VERSACRYL ACRYLIC POLYMER MSDS Initial Approval Date: 15/02/2012

Chemical Name: N/A MSDS Prepared by: BSQ

Family: Acrylic Polymer Manufacturer: KEYSTONE INDUSTRIES

Product Use: Dental Polymer

616 Hollywood Av, Cherry Hill, NJ 08002

Emergency Phone Numbers: 131126

Information Contacts: (03) 95321799

Section II - Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL	IARC/NTP/OSHA	
Dibenzoyl Peroxide	94-36-0	202-327-6	Benzoyl Peroxide	5 mg/m3	5 mg/m3	3/no/no	< 0.2

N/F - None Established N/DA - No Data Available

Hazard Symbols: Xi

This product is not considered hazardous by OSHA Hazard Communication Standard.

Risk Phrases: R36/37/38

Safety Phrases: S18, S22, S24/25, S38

Section III - Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- May cause allergic skin reaction.
- May cause eye irritation.
- Dust may cause irritation of the nose, throat, and lungs.
- This product may contain particulates, not otherwise classified (Nuisance Dust)

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Eyes or skin (No absorption); inhalation of dust.

Eye Higher concentration can irritate eyes. May cause eye irritation or damage.

Skin Repeated or prolonged exposure may cause allergic skin rashes.

Ingestion Higher concentration can irritate respiratory system.

Inhalation Possible temporary discomfort due to inhalation of dust concentration above the permissible exposure

limit. Dust may cause irritation of the nose, throat, and lungs.

Sub-Chronic Effects Effects of Acute and Chronic Over Exposure: It is not known to cause significant health problems. It is

considered an inert or nuisance dust. Avoid inhalation of dust. Keep dust out of eyes to prevent

possible irritation.

NOTE: Refer to Section 11, Toxicological Information for Details

Section IV - First Aid Measures

First Aid for Eye Flush with plenty of water for 15 minutes, occasionally lifting the upper and lower eyelids. Get

medical aid if symptoms persist.

First Aid for Skin Wash throughly with soap and water. Obtain medical aid if discomfort persists.

First Aid for Inhalation In case of exposure to a high concentration of polymer dust, remove person to fresh air. If breathing

has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion Never give anything by mouth to an unconscious person. Get medial aid. Do NOT induce vomiting. If

conscious and alert, rinse mouth and drink 2 to 4 cupfuls of milk or water.



MSDS#: KIP071103-VAP

VERSACRYL ACRYLIC POLYMER **Material Safety Data Sheet** Page 2 of 5

Section V - Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
572°F/304°C (Tag Closed Cup)	LEL: 20 g/m ³ (dust cloud)	(voi 76) N/E
("% - " - " - " - " - " - " - " - " - "	UEL: N.A.	"

Method:

Extinguishing Media: Water spray, water foam, carbon dioxide, dry chemical.

Fire Fighting Avoid extinguishing methods that generate dust clouds. Water streams can disperse dust into

Instructions: air, producing a fire hazard and possible explosion hazard. Fire-fighters should wear self-

contained breathing apparatus.

Unusual Hazards: Polymer dust is combustible but not easily ignited. The explosive limits of the polymer particles

suspended in air are approximately those of coal dust.

Section VI - Accidental Release Measures

Spill or Release **Procedures**

Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills.

Section VII - Handling and Storage

Handling Observe precautions found on the label. Wash face and hands thoroughly with soap and water

after handling and before eating, drinking or smoking. Avoid prolonged or repeated contact

with skin. Avoid contamination. Use only with adequate ventilation.

Storage Store in cool, dry place away from heat, sparks, flame and direct sunlight. Close container

after each use. Ground all metal containers when transferring. Use explosion-proof equipment

Store away from combustibles and incompatible materials.

Polymer dust is combustible, explosive limits of the polymer particles suspended in air are **Explosion Hazard**

approximately those of coal dust.

Section VIII - Exposure Controls / Personal Protective Equipment

Engineering Controls Use good local exhaust at processing equipment, including buffers, sanders, grinders and

polishers. High temperature processing equipment should be well ventilated. Use explosionproof equipment. Provide ventilation if necessary to control exposure levels below airborne

exposure limits.

Personal Protective Equipment

General Dust collectors are recommended for handling powder in bulk.

> To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety

showers.

Eye/ Face Protection Use safety glasses and have eye flushing equipment immediately available.

Skin Protection Minimize contamination by following good industrial practice. Although waering gloves is an

option, wearing nitrile, neoprene, pvc, latex or other impermeable gloves is recommended.

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with a minimum rating of N95 may be permissible

> under certain limited circumstances where airborne concentrations are expected to exceed exsposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepeice airline respirator in the positive pressure mode with

emergency escape provisions. Follow OSHA repsirator regulations found in 29 CFR 1910.134 or

Eurpean Standard EN 149.





Material Safety Data Sheet

VERSACRYL ACRYLIC POLYMER Page 3 of 5

Section IX - Physical and Chemical Properties

Fine, white/pink powder Faint odor in bulk. N/A N/A N/A 0.0	Appearance	Odor & Odor Threshold	PН	Specific Gravity	Viscosity	% Volatile
	Fine, white/pink powder		N/A	N/A	N/A	0.0

Freezing Point	Temperature	Partitioning Coefficient Log Po/w	Pressure:	Density	Rate		In Water (20°C)
N/A	392°F/200°C	N/A	N/A	N/A	N/A	N/A	insoluble

Flash Point	Flammable Limit	Auto-ignition Temperature
(°F/°C)	(vol%)	(vol%)
580°F/304°C (Tag Closed Cup)	LEL: 20 g/m ³ (dust cloud)	N/E
	UEL: N.A.	

Section X - Stability and Reactivity

Stability:

Stable

Hazardous Decomposition Products:

Methyl methacrylate monomers and Carbon Dioxide

Conditions to Avoid:

Heating above 200°C/392°F

Incompatibility (Materials to Avoid):

Strong oxidizing agents

Hazardous Polymerization:

will not occur

Section XI - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
N/DA	N/DA	N/DA	mild	mild

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	None	None

Section XII - Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA	
Chemical Oxygen Demand	N/DA	

Section XIII - Disposal Considerations

May be disposed of in a landfill or incinerated. Follow Federal, State and Local regulations for disposal.

Section XIV - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	N/A





Emergency Response Guidebook (ERG) #:	N/A	
IATA (DGR):		
Proper Shipping Name:	Non-Regulated Material	
Class or Division:	N/A	
UN or ID Number:	N/A	
Packaging Instructions:		
Emergency Response Guidance (ICAO)#:		
IMO (IMDG):		
Proper Shipping Name:	Non-Regulated Material	
Class or Division:	N/A	
UN or ID Number:	N/A	
Special Provisions & Stowage/Segregation:	None	
Emergency Schedule (EmS)#:		
Other Information:	Flash point > 100°C	

Section XV - Regulatory Information

US Federal Regulations

US Federal Regulations	THE THE STATE OF T
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP's) or ozone dipleting substances (ODS's), as defined by the U. S. Clean Air Act: NONE
Clean Water Act: Priority Pollutant	This product contains the following chemicals listed under the U.S. Clean Water Act Priority Pollutant List: NONE
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is not considered a hazardous chemical under the OSHA Hazard Communication Standard.
RCRA	This product contains no chemicals considered to be hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 304	This product contains no chemicals regulated under Sec. 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List).
SARA Title III: Section 311-312:	This product does not contain hazardous substances under the OSHA Hazard Communication Standard, and is not regulated under Section 311-312 (40 CFR 370).
SARA Title III: Section 313:	This product contains the following chemicals outlined in SARA Title III: Section 313: • Benzoyl Peroxide CAS #94-36-0.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

State Regulations

State Regulations	
CA Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
MA Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
NJ Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
PA Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
FL Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0
MN Right-to-Know Law:	Benzoyl Peroxide CAS #94-36-0




Material Safety Data Sheet VERSACRYL ACRYLIC POLYMER Page 5 of 5

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Benzoyl Peroxide CAS #94-36-0 is on the DSL list. WHMIS = C, D2B, B4
EINECS: European Inventory:	 Versacryl Acrylic Polymer: HAZARD SYMBOLS: Xi: Irritant RISK PHRASES: R36/37/38: Irritating to eyes, respiratory system and skin SAFETY PHRASES: S18: Handle and open container with care, S22: do not breath dust, S24/25: avoid contact with skin and eyes, S38: in case of insufficient ventilation, wear suitable respiratory equipment.

Section XVI - Other Information

Hazard Rating System (Pictograms)



* - Respiratory protection may be necessary depending on conditions of use. Refer to Section VIII of this MSDS for respiratory protection guidelines.

OSHA PEL for nuisance dust: 15 mg/m³ (total dust)

5 mg/m³ (respirable dust)

ACGIH PEL for nuisance dust: 10 mg/m³

Revised Sections since Last Version:	07/31/2003 Initial Issue	
	11/02/2006 Added part numbers.	
	02/05/2008 Added part numbers	

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 131126.