



AF125 Accelerator Free White Nitrile 12"Gloves





Key Features

- Accelerator free formulation lower risk of dermatitis potential
- Sulfur free
- Latex free 100% nitrile
- Packaged for Class 100 (ISO5/M3.5) applications
- Compliant with ASTM and IEST-RP-CC005.3 standards
- Average surface resistance 10⁹ Ohms per square unit
- RoHS Compliant
- P3 Polar Process
- For industrial use only
- Sizes: S XL
- Pack: 100 Gloves/Double Bag

Industrial Applications

- IC and disk drive manufacturing
- Electronics
- Life Sciences
- Laboratories
- Precision Optics
- Controlled environment manufacturing

Quality Assurance Conformity

ANSI/ESD STM11.11-2015 FDA Pyrogenic Substances Test
ANSI/ESD STM11.12-2015 FDA/ISO 10993-11

ASTM D3577-09(2015) USP <88>/ISO 10993-10 ASTM D3578 - 05(2015) ANSI/ASQ Z1.4-2003 (R2013)

ASTM D6319 - 10(2015) MIL-STD-105

ASTM F719-81(2012) ASTM F1671 / F1671M - 13

ASTM F720 - 13 ASTM F1383-99a / F1383-12e1

EN 455-1&2 IEST-RP-CC005
FDA 1000 ml Watertight Test FFDCA Compliance

About QRP Gloves

Founded in 1974, QRP Gloves, Inc. is a global growth company and leading independent supplier of gloves and fingercots for use in industry.

Known for innovations such as the first Class 100 cleanroom latex glove, first carbon-free ESD control glove and first ESD control finger cot, all QRP products are engineered to increase yields in industrial applications, high technology manufacturing, aerospace, biotechnology and pharmaceuticals.

For further information about QRP Gloves, Inc., feel free to call us at: 800-832-3882, ext. 250, PO Box 27466 Tucson, AZ 85726 or email us: info@QRPGloves.com



AF125 Accelerator Free White Nitrile 12"Gloves

| GLOVE COMPOSITION | | | | | | | | |
|--------------------|--------------------------------|-----------------|-----------|--|--|--|--|--|
| Material: | Nitrile (Accelerator free NBR) | Material Color: | White | | | | | |
| Mil Thickness: | 6 | Length: | 12 inches | | | | | |
| Country of Origin: | Maylasia | Product ID: | AF125 | | | | | |

| Physical Data | | | | | | | | | |
|----------------------|--|--------|----------------|----------------|----------|-----------|-----------|--|--|
| Dimensions: | Length | | Width | Thickness (mm) | | | | | |
| | Inches | mm | mm | | Finger | Palm | Cuff | | |
| X-Small | 12 | 300±10 | 74 <u>+</u> 3 | 0. | .18±0.03 | 0.15±0.03 | 0.12±0.03 | | |
| Small | 12 | 300±10 | 84 <u>+</u> 3 | 0. | .18±0.03 | 0.15±0.03 | 0.12±0.03 | | |
| Medium | 12 | 300±10 | 94 <u>+</u> 3 | 0. | .18±0.03 | 0.15±0.03 | 0.12±0.03 | | |
| Large | 12 | 300±10 | 104 <u>+</u> 3 | 0. | .18±0.03 | 0.15±0.03 | 0.12±0.03 | | |
| X-Large | 12 | 300±10 | 115 <u>+</u> 3 | 0. | .18±0.03 | 0.15±0.03 | 0.12±0.03 | | |
| XX-Large | 12 | 300±10 | 125 <u>+</u> 3 | 0. | .18±0.03 | 0.15±0.03 | 0.12±0.03 | | |
| Tensile Properties: | (ASTM D3578-95) | | | | | Aged | Unaged | | |
| | Tensile Strength (MPa) | | minimum | | 14 | 14 | | | |
| | Ultimate Elongation (%) | | minimum | | 700% | 700% | | | |
| Physical Appearance: | White ambi gloves, rolled beaded cuff | | | | | | | | |
| Powder Coating: | None | | | | | | | | |
| Case Pack: | 100 gloves (packed by weight) per pack 10 packs/ | | | | | ase | | | |

Storage: Store in a cool, dry location, away from sources of light. Avoid extremes of heat or cold. Recommended storage temperature range: $50^{\circ}F - 86^{\circ}F$ ($10^{\circ}C - 30^{\circ}C$)

PROTECTION STANDARDS









The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all-inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. QRP, Inc does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation. User assumes all risks. In the interests of continual product improvement, specifications subject to change without notice. The information contained in this sheet relates only to the specific material designated herein and does not relate to use in combination with other material or in any process. The information presented is from sources deemed to be reliable, but the thoroughness or completeness is not guaranteed.

Note: Gloves are included in the Manufactured Article Exemption of the Hazard Communications Regulations in the Code of Federal Regulations (29 CFR 1910.1200). As a result, an SDS is not required. QRP endeavors to provide as much information as is possible about the product in its catalog and product information sheets.

rev: 4Nov2019

