

BioClean-D™ Overboots - Sterile S-BDOB

Lightweight sterile overboots with an elasticated opening, for secure, fitted personal protection

- Reduced contamination risks: BioClean-D™ Overboots S-BDOB are made from lightweight low-linting CleanTough™ material, lowering the risk of contamination in the cleanroom environment
- Optimized fit: These protective overboots' elasticated opening ensures a secure fit, for dependable personal protection that remains firmly in place
- Enhanced features: Equipped with easy tie fastenings and a slip-resistant sole, these overboots ensure a firm, adjustable hold and help prevent possible workplace injuries
- Sterility assurance: The boots are sterilised by gamma irradiation, with sterility assurance level (SAL) of 10-6
- CAUTION: Please contact Ansell Customer Service for specific chemotherapy drug permeation times and recommendations



Key Features and Benefits

- Lightweight low-linting CleanTough™ fabric: Fewer contamination risks
- Elasticated opening: A more secure, more comfortable fit
- Slip-resistant sole and easy tie fastenings: Secure fit, for safer use

Industries

- Controlled and Critical Environments
- Production and Manufacturing
- Pharmaceutical Manufacturing
- Biotechnology Manufacturing
- Medical Device Manufacturing







BioClean-D™ Overboots - Sterile S-BDOB

TECHNICAL DATA SHEET

PRODUCT INFORMATION

| Material | CleanTough™ |
|-------------------------------|---|
| Audit Standards | Manufacturing QMS Audit Standards ISO 9001, PPE Regulation 2016 425 Module D |
| Standards | ASTM F739, CE 0598, EN ISO 13688:2013, EN 1149-5:2008, EN 13934-1, EN 13935-2, EN 530, EN 6530, EN 7854, EN 863, EN 9073-4, EN ISO 14325, ISO 11137-1:2006, Category III, EN 13034:2005 + A1:2009 |
| Packaging Overview | One pair per sealed inner PE bag; 15 inner bags per sealed outer PE bag; five outer bags per lined carton (75 pairs) |
| Country Of Origin | China |
| Sterilization Method | GAMMA irradiation (25 kGy) |
| Sterilization Minimum Dose | 25kGy |
| Sterility Assurance Level | 10-6 |
| Cleanroom Class | Class 10/ISO 4 & EU GMP Grade A |
| Shelf Life | Three (3) years from date of manufacture. |
| Construction | Bound seams with single needle stitching |
| Characteristics | *NOTE: BioClean CleanTough material is static dissipative and, with a charge half decay time of 0.07 sec, and so are ideal for use in a static-safe environment. |

MATERIAL PERFORMANCE TEST RESULTS

| TEST | RESULT | PERFORMANCE CLASS |
|--|------------------------|-------------------|
| Abrasion Resistance | 10 to 100 cycles | 1 |
| Flex Cracking Resistance | 5,000 to 15,000 cycles | 3 |
| Trapezoidal Tear Resistance Cross Direction (CD) | CD 29.3 N | 2 |
| Trapezoidal Tear Resistance Machine Direction (MD) | MD 55.5 N | 3 |
| Tensile Strength Cross Direction (CD) | CD 48 N | 1 |
| Tensile Strength Machine Direction (MD) | MD 97 N | 2 |
| Puncture Resistance | 8 N | 1 |
| Repellence to Liquids - 30% H ₂ SO ₄ | 96.3% | 3 |
| Repellence to Liquids - 10% NaOH | 97.6% | 3 |
| Repellence to Liquids - O-Xylene | 95.7% | 2 |
| Repellence to Liquids - Butan-1-ol | 96.6% | 3 |
| Penetration by Liquids - 30% H ₂ SO ₄ | 0% | 3 |
| Penetration by Liquids - 10% NaOH | 0% | 3 |
| Penetration by Liquids - O-Xylene | 0% | 3 |
| Penetration by Liquids - Butan-1-ol | 0% | 3 |
| Seam Strength ² | 70 N | 2 |
| Electrostatic Charge Half Decay Time, t ₅₀ (secs) | 0.07 | PASS |

Seam not destroyed





BioClean-D™ Overboots - Sterile S-BDOB

PARTICLE SHEDDING TEST RESULTS

| TEST | RESULT |
|--------------------------------------|---------------------------|
| Particle Shedding (Helmke Drum Test) | ≥ 0.5Qm (counts/min) <260 |

ASTM F739-12 TEST METHOD RESULTS

| DRUG | Mean Breakthrough Time (MBT), Minutes Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.1 Qg/cm² /min |
|--------------------------|---|
| CISPLATIN | >240 |
| CARMUSTINE | <6 |
| CYCLOPHOSHAMIDE | 217 (275,162,215) |
| DOXORUBICINHYDROCHLORIDE | >240 |
| 5-FLUOROURACIL | >240 |
| METHOTREXATE | >240 |
| ETOPOSIDE | >240 |
| PACLITAXEL | <10 |
| THIOTEPA | 30 (28,30,33) |

Results achieved under controlled laboratory conditions, by accredited external testing laboratory.

SIZE CHART

Universal

ORDERING INFORMATION

| | SIZE | Universal |
|--------|-------------|-----------|
| S-BDOB | REORDER NO. | S-BDOB |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Performance Standards and Regulatory Compliance









Ansell, $^{\textcircled{8}}$ and $^{\textcircled{m}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{e}}$ 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.



