

Low allergy potential and reliable protection for clean environments

Nitrilite® 93-401 is a non-sterile accelerator free nitrile glove with very low levels of ionic content and particles for reliable product protection. Designed for use in Class 10 (ISO 4) clean room environments.

- Compatible with Class 10 (ISO 4)
- Very low levels of ionic content and particulate for excellent product protection
- Nitrile formulation free of latex proteins and accelerators to avoid susceptibility of Type I or IV allergic reactions



Industries

- Biotechnology Manufacturing
- Medical Device Manufacturing
- Electronics manufacturing

Recommended For

- Clean room cleaning and preparing
- Blending, compounding solids and liquids
- Spill or leakage cleanup
- Transferring liquids and solids
- Loading centrifuges and chromatography columns
- Assembly of parts
- Weighing and dispensing of solid and liquid raw materials



Nitrilite®

93-401Clean Nitrile Glove

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
Color	Natural
Shape	Ambidextrous
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001:2015
Regulatory	Category III, EN ISO 21420:2020, EN ISO 374-1:2016, EN ISO 374-5:2016, FDA21 CFR 177-2600-US Food Contact Approved
Packaging	50 gloves per inner bag ; 2 inner bags per master polybag ; 10 master polybags per (1000 gloves) per liner bag
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
Available sizes	S (6-6.5), M (7-7.5), L (8-8.5), XL (9-9.5), XXL (10-10.5), XS (5-5.5)
Powder Content	Powder-Free
External Glove Surface	Textured Fingers
Internal Glove Surface	Powder-Free, Chlorinated
Cleanroom Class	Class 10/ISO 4
Shelf Life	5 Years
Tested for use with Chemotherapy Drugs	No
Protein Level	N/A: contains no natural rubber latex
Anti-static	Yes EN1149
Vulcanization Chemical Accelerators	• None



Nitrilite®

93-401 **Clean Nitrile Glove**

Physical Properties		Testing Method
Typical Length (mm/in)	300 / 12	EN 420/ASTM D3767
Freedom from Holes	1.5 AQL	EN 455-1/ASTM D3577
Typical Particle Count ≥0.5µm (counts / cm²)	< 400 particles / cm²	IEST-RP-CC005.4
Target Single Wall Palm Thickness (mm/mil)	0.11 / 4.3	EN 420/ASTM D3767
Target Single Wall Finger Thickness (mm/mil)	0.13 / 5.1	EN 420/ASTM D3767
Target Single Wall Cuff Thickness (mm/mil)	0.08 / 3.1	EN 420/ASTM D3767
Ultimate tensile strength (MPa) Before Aging	≥ 18	ASTM D412-06a

IONIC CONTENT

Concentration in µg/cm²	Typical	Concentration in µg/cm²	Typical
Calcium	0.175	Potassium	0.006
Chloride	N/A	Sodium	0.012
Lithium	0.0001	Sulphate	0.004
Magnesium	0.001	Zinc	0.017
Nitrate	0.048		

PERFORMANCE STANDARDS AND REGULATORY COMPLIANCE





For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01 Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Ansell, $^{\textcircled{R}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{M}}$ 2022 Ansell Limited. All Rights Reserved.

Ansell