

FRESHPOINT F1000

SINGLE STAGE FILTRATION SYSTEMS





APPLICATIONS

· Drinking water

FEATURES · BENEFITS

- · Effortless click-in cartridge change-outs
- Built-in check valve system means no need to turn off water for cartridge change-outs
- 3/8" push fittings for easy insulation

MODELS

F1000B1B, Chlorine taste, odor and advanced chemical reduction

INSULATION TIPS

- Choose a mounting location suitable to support the full weight of the system when operating.
- · Install vertically with the cartridge hanging down.
- System may be installed with cartridge flush to the baseboard if desires as the mechanical assist level pushes cartridge straight out.

OPERATION TIPS


- Replace cartridge every 750 gallons or 1 year (or if flow was diminished)
- System designed with integrated check valves so cold water line does not need t be shut-off to perform cartridge change-outs.

INCLUDES

- Side faucet
- Installation kit
- · Installation and operational manual



FRESHPOINT F1000 SINGLE STAGE- Technical Data



SPECIFICATIONS

- Systems (Model/Part No.) F1000-B1B/158838
- Inlet Size 3/8" QC
- Dimensions

 12.25" H X 3.5" W X 4.8" D
 (311 mm X 90 mm X 122mm)
- System Weight 1.80 lbs
- Contaminant Reduction (See chart below)
- Micron Rating

 0.50 (F1000-B1B only)
- Approximate Filter life* Up to 1 year
- * Filter life dependent on gallon usage and overall incoming water quality.

- Capacity
 750 Gallons (2839.06 Liters)
- System Production Rate (See chart below)
- Certifications F1000-B1B: NSF/ANSI Standards 42,53 CSA Standard B483.1
- Feed Pressure Range 40 - 100 psi(2.75 - 6.89 bar)
- Temperature Range 40 - 100°F (4.4 - 37.8°C)
- Replacement Cartridge For F1000-B1B: F1B1-RC/55120-96

Part No.	Model No.	System Production Rate	Substance Reductions Claims
158838	F1000-B1B	0.60 gpm	Chlorine Taste & Odor, Lead, Atrazine, Lindane, Nominal Particulate, Class I, Cyst: NSF/ANSI Standard 53 certified to reduce cysts such as <i>Cryptosporidium</i> and <i>Giardia</i> by mechanical means.

EPA EST. NO. 082989-CHN-001



The Model F1000-B1B is Tested and Certified by NSF International against NSF/ANSI Standards 42 and CSA B483.1 for the reduction of substances specified on the service manual or at www.nsf.org.



