

## **EventSeries®**

# Install Grade MultiPair Analogue/Digital Audio Cables 110 $\Omega$ AES/EBU LSZH FireFighter®

### **Application**

Event® 110Series Pre-Jacketed digital/analogue audio multicore, individually foil shielded and overall foil shield. The individual elements of this multicore has the same low loss characteristics as our 110-1601 single pair product which delivers real 110  $\Omega$  AES/EBU performance. The foil screen can easily be removed with pair sheath for easier termination. The finished product is ideal for use in public buildings where LSZH cables are specified.

### Cable Design

**Shielded Pair** 

**Conductor** Oxygen Free Tinned Copper (7 x 0.20mm) 0.22m<sup>2</sup>

InsulationFoam Polyethylene (PE) with skinPair2 cores twisted to a pair (Blue/White

**Drain Wire** Stranded tinned copper

**Screen** Overall Aluminium/polyester tape (Aluminium Inside)

**Sheath** LSZH FireFighter® Ø 3.50 mm

Core

**Assembly** Multiple pair counts layed up with fillers where needed

**Tape** Polyester tape wrapped around pairs

**Drain Wire** Stranded tinned copper

**Screen** Overall Aluminium/polyester tape (Aluminium Inside)

Outer Jacket LSZH FireFighter® Ø see table

**Colour** Black

#### **Characteristics**

- For use in stage box systems or fixed installation
- 110Ω AES\EBU performance
- Flame Retardent acc. to IEC 60332-1
- Halogen Free acc. to IEC 60754-1
- Smoke Density acc. to IEC 61034-1





## **EventSeries®**

# Install Grade MultiPair Analogue/Digital Audio Cables 110 $\Omega$ AES/EBU LSZH FireFighter®

#### **Technical Data**

Max. Working Voltage		250 V
Test Voltage		1500 V ac/1 min
Capacitance (Conductor/Shield) max		74.35 pF/m
Characteristic Impedance	10 MHz	110 Ω
Nom. Attenuation		14.9 dB/100m
Conductor Resistance		< 88 <b>Ω</b> /km
Insulation Resistance		> 500 M <b>Ω</b> /km
Min. Bending Radius		7.5 x Ø
Working Temperature		-30°C up to +85°C

#### **Contact Details**

Websitewww.2b-wired.comTelephone+44 (0) 330 088 9271Emailinfo@2b-wired.com



## **EventSeries®**

# Install Grade MultiPair Analogue/Digital Audio Cables 110 $\Omega$ AES/EBU LSZH FireFighter®

### **Specification**

Cross Section	Part Number	No. of Pairs	Overall Diameter mm ± 10%	Weight kg/km
0	110-i4602	2	9.1	92
	110-i4604	4	10.7	145
	110-i4608	8	14.0	207
	110-i4612	12	17.1	308
	110-i4616	16	19.1	388
	110-i4624	24	25.6	577
	110-i4632	32	26.2	732

#### **Contact Details**

Website www.2b-wired.com
Telephone +44 (0) 330 088 9271
Email info@2b-wired.com