

EventSeries®

OFC Professional Starquad Microphone Cable MLX4

Application

MLX4 is a professional grade oxygen free microphone cable. It has a LAP screen and an enlarged sheath which is made of a very soft and flexible compound mix with matt finish. For use in noisy areas since the starquad design cancels out interference and external noise, so it's ideal for noisy areas. The cable also has a kevlar strength member adding to the cables durability

Cable Design

Conductor	Oxygen Free Copper (28 x 0,10mm) 0,22m2
Insulation	Special Polymer
Pair	2 pairs twisted to a starquad formation (Red / Blue / Green / White)
Strain Relief	Kevlar strength member with cotton fillers
Shield	Bare copper spiral screen
Outer Jacket	TPM
Colour	See specification table






Technical Data

Nom. Capacitance (cond./cond.)	90 pF/m
Nom. Capacitance (cond./cond./screen)	180 pF/m
Conductor Resistance	85 Ω /km
Insulation Resistance	20 M Ω *km
Operating Voltage	50/75 V AC/DC
Test Voltage (core:core at 50Hz eff. for 1 minute)	> 1.2 kV
Test Voltage (core:screen at 50Hz eff. for 1 minute)	> 1 kV

EventSeries®

OFC Professional Starquad Microphone Cable MLX4

Specification

Cross Section	Part Number	Overall Diameter mm	Colour
	MLX4-01	7.0 ± 0.25	Black
	MLX4-02	7.0 ± 0.25	Blue
	MLX4-04	7.0 ± 0.25	Red

Contact Details

Websitewww.2b-wired.com**Telephone**

+44 (0) 330 088 9271

Emailinfo@2b-wired.com