

EventSeries®

OFC Professional Microphone Cable MLX2

Application

MLX2 is a professional grade oxygen free microphone cable. It has a LAP screen and an enlarged sheath which is made of a very soft and flexible compound mix with matt finish. The cable also has a kevlar strength member adding to the cables durability.



Cable Design

Conductor	Oxygen Free Copper (28 x 0.10mm) 0.22m ²
Insulation	Special Polymer
Pair	1 pair (Red/Blue)
Strain Relief	Kevlar strength member with cotton fillers
Shield	Bare copper spiral screen
Outer Jacket	TPM
Colour	See specification table

Technical Data

Nom. Capacitance (cond./cond.)	90 pF/m
Nom. Capacitance (cond./cond./screen)	180 pF/m
Conductor Resistance	85 Ω/km
Insulation Resistance	100 MΩ*km
Operating Voltage	50/75 V AC/DC
Test Voltage (at 50Hz eff. for 1 minute)	> 1 kV

EventSeries®

OFC Professional Microphone Cable MLX2

Specification

Cross Section	Part Number	Overall Diameter mm	Colour
	MLX2-01	6.35	Black
	MLX2-02	6.35	Blue
	MLX2-03	6.35	Green
	MLX2-04	6.35	Red
	MLX2-05	6.35	Grey
	MLX2-06	6.35	Yellow
	MLX2-08	6.35	Orange
	MLX2-09	6.35	Violet

Contact Details

Website
Telephone
Email

www.2b-wired.com
+44 (0) 330 088 9271
info@2b-wired.com