

AMC-E Series USB3.0 HD PTZ Camera






AMC-E200U3

Features


- Up to 1080P60 HD video format;
- USB 3.0 output, compatible with USB2.0;
- 12x optical zoom, up to 72.5° FOV ;
- Support standard UVC protocol;
- Come with IR remote controller;
- With OSD menu, supports image flip;
- Provide an extra DVI-D video interface;
- Support standard VISCA & Pelco communication protocols;
- RS232IN/IR & RS232OUT/RS485 control interface, support daisy chain;
- Special mechanical PTZ driving system, ensure precise positioning.

Dimensions




- | | |
|---------------|--------------------|
| ① USB3.0 | ④ RS-232OUT/RS-485 |
| ② DVI-D | ⑤ DC12V |
| ③ RS-232IN/IR | |

Accessories



Wall Bracket



Ceiling Plate

Technical Data

Model		AMC-E200U3
Camera		
Image Sensor	1/2.8" Exmor CMOS, 2.14MP	
Resolution	1920x1080P/60/50/30/25/20/15/10/5 1280x720P/60/50/30/25/20/15/10/5 1024x768P/60/50/30/25/20/15/10/5 800x600P/60/50/30/25/20/15/10/5 640x480P/60/50/30/25/20/15/10/5	
Focal Length	3.9mm - 46.8mm	
Iris	F1.6 - F2.8	
Optical Zoom	12X	
Digital Zoom	12X	
Field of View	Horizontal 72.5° - 6.3°	
Focus	Auto, Manual, PTZ Trigger AF, One Push	
Minimum Illumination	0.5Lux	
Shutter Speed	1/1 - 1/10,000s	
AGC	Auto / Manual	
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Automatic Tracking, Sodium , Fluorescent	
AE Control	Auto, Manual, Shutter Priority, Iris Priority, Intelligence	
BLC	Yes	
WDR	Yes	
Noise Reduction	2D / 3D	
Pan & Tilt		
Pan Range	-170° ~ +170°	
Tilt Range	-30° ~ +90°	
Pan Speed	0.1° ~ 120°/ s	
Tilt Speed	0.1° ~ 80°/ s	
Preset Number	256	
OSD	Yes	
Image Flip	Yes	
Interface		
Video Output	USB3.0, DVI-D	
Control Interface	USB3.0, RS-232IN/IR, RS-232OUT/RS-485	
General		
Control Protocol	VISCA and Support Daisy Chain, PELCO-D, PELCO-P	
Address	0~63	
Power Supply	DC12V	
Dimension (L×W×H)	243mm x 145mm x 163mm	
Weight	1.2kg	
Color	Grey	