



Features

Safety Sealed Packaging (S-XL) 100 Gloves/Box, 10 Boxes/Case
Safety Sealed Packaging (XXL) 90 Gloves/Box, 10 Boxes/Case

- Soft Nitrile with Easy Donning Feature
- Black Color
- 4 mil thickness, 9.5-inch cuff
- Exceptional strength and durability
- Superior puncture resistance
- Textured finish for excellent grip
- Better chemical barriers than latex gloves
- Excellent tactile sensitivity and comfortable fit
- Dated Lot Codes for quality assurance and traceability

BlackSeal® LT Manufacturing Standards

***Brand new state-of-the-art manufacturing plant with computer-controlled market leading technology**

Defect	Inspection Level	AQL
Pinholes (FDA 1000 ml watertight test)	G1	1.5
Visual Defects (Major)	G1	2.5
Visual Defects (Minor)	G1	4.0
Dimensions	S-2	4.0

BlackSeal® LT Powder-Free Nitrile Exam Gloves

Size	Reorder#
Small	774-6
Medium	774-7
Large	774-8
X-Large	774-9
2X-Large	774-0

All specifications are subject to change without notice.

Specifications

Size	Glove Length	Palm Width	Cuff Thickness	Palm Thickness	Finger Thickness
Small	240	85	0.08 ± 0.01	0.11 ± 0.01	0.13 ± 0.01
Medium	240	95	0.08 ± 0.01	0.11 ± 0.01	0.13 ± 0.01
Large	240	105	0.08 ± 0.01	0.11 ± 0.01	0.13 ± 0.01
X-Large	240	115	0.08 ± 0.01	0.11 ± 0.01	0.13 ± 0.01
2X-Large	240	125	0.08 ± 0.01	0.11 ± 0.01	0.13 ± 0.01

Quality Standards

Testing Methods

- Meets or exceeds the following standards: ASTM D6319 (USA), EN 455 (1&2), FDA, CE, NFPL, UL
- Meets the Viral Penetration Test (ASTM F1671-03)
- Quality sampled in accordance with MIL STD 105E

Physical Properties

Property	ASTM Minimum	BlackSeal® LT
	Before Aging	Before Aging
Tensile (MPa)	14	16
Elongation (%)	500	550
	After Aging	After Aging
Tensile (MPa)	14	16
Elongation (%)	500	400